

DESIGNER NOTES

STRUCTURAL APPROACH SLABS SHALL BE USED ON ALL I.H. BRIDGES AND U.S.H. BRIDGES. STRUCTURAL APPROACH SLABS ARE RECOMMENDED FOR BRIDGES CARRYING TRAFFIC VOLUMES GREATER THAN 3500 AADT (FUTURE DESIGN YEAR). OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER. SEE BRIDGE MANUAL SECTION 12.11 FOR ADDITIONAL GUIDANCE.

STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED STRUCTURES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.

QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.

◆ CONSTRUCTION JOINT REQUIRED WHEN WIDTH OF SUPERSTRUCTURE EXCEEDS 90'. RUN REINFORCEMENT THROUGH THE JOINT.

LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).

STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.). WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).

★ THE BID ITEM FOR SS901 AND SS601 BARS SHALL BE STANDARD SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS STRUCTURES".

DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND THE FDM.

SEE STANDARD 9.01 FOR BACKFILL AND BASE AGGREGATE DENSE 1-1/4 INCH DETAILS. SHOW "DESIGN DATA" INFORMATION ON FIRST SHEET OF PLANS

DESIGN DATA

CONCRETE STRENGTH (STRUCTURAL APPROACH SLAB AND FOOTING), f'c: 4,000 P.S.I.
 BAR STEEL REINFORCEMENT GRADE 60, fy: 60,000 P.S.I.
 ALLOWABLE SOIL BEARING PRESSURE: 2,000 P.S.F.

LEGEND

- ▲ SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE).
- SEE PARAPET STANDARD DETAILS FOR LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET.


BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BEND	BAR SERIES	LOCATION
SS901			5'-0"	X		CONC. ABUT. DIAPH. TO APPROACH SLAB
SS901			5'-0"	X		CONC. BACKWALL TO APPROACH SLAB
SS601			3'-0"			STRUCTURE SLAB TO APPROACH SLAB

STAINLESS STEEL (A1 ABUT. - GIRDER SPAN)
 STAINLESS STEEL (A3 & A4 ABUT.)
 STAINLESS STEEL (A1 ABUT. - SLAB SPAN)

BAR MARK	COAT	NO. REQ'D.	LENGTH	BEND	BAR SERIES	LOCATION
T501	X			X		APPROACH SLAB FTG. - STIRRUP
T802	X					APPROACH SLAB FTG. - TRANS.
T803	X			X		APPROACH SLAB - LONG. - BOT.
T804	X			X		APPROACH SLAB - LONG. - BOT. - WALL
T505	X					APPROACH SLAB - LONG. - TOP.
T506	X					APPROACH SLAB - LONG. - WALL
T507	X					APPROACH SLAB - TRANS. - BOT.
T508	X					APPROACH SLAB - TRANS. - TOP.
T509	X		4'-10"	X		APPROACH SLAB - TRANS. - TOP - WALL
T510	X		4'-1"	X		APPROACH SLAB - TRANS. - TOP - WING
T411	X		3'-0"	X		APPROACH SLAB - TRANS. - WALL



STRUCTURAL APPROACH SLAB

BUREAU OF STRUCTURES

DATE: _____

APPROVED: *Laura Shadewald*

1-21

SECTIONS A-A THRU G-G ARE SHOWN ON STANDARD 12.11 & 12.12