



★ STD. HOOK (TYP.)
ROTATE AND STAGGER
AS NEEDED.



SECTIONS P1 AND P2 ARE
DETAILED ON STANDARD 7.04


NOTES

- PROVIDE A SUITABLE LIFTING DEVICE FOR THE PRECAST CAP AND COLUMN UNIT(S). CAST-IN-PLACE ALTERNATIVE IS NOT ALLOWED.
- STIRRUPS AT THE GROUTED COUPLERS ARE SIZED BASED ON A XX" OUTER DIAMETER COUPLER SLEEVE. ADJUST STIRRUP DIMENSIONS AS REQUIRED IF THE ACTUAL COUPLER SLEEVE DIAMETER DIFFERS.
- MANUFACTURER TO DETERMINE THE PRECAST PIER COLUMN LENGTHS ASSUMING 1/2" STEEL SHIMS AT THE TOP AND BOTTOM OF THE COLUMN.
- BID ITEM "PRECAST PIER COLUMNS" PAID PER PLAN VALUE AS BOTTOM OF PIER CAP ELEVATION MINUS TOP OF FOOTING ELEVATION.

DESIGNER NOTES

- PIERS SHALL BE SUPPORTED BY A MINIMUM OF 3 COLUMNS. WHEN MULTIPLE PIER CAPS ARE USED EACH SEGMENT SHALL BE SUPPORT BY A MINIMUM OF 2 COLUMNS.
- THE FOLLOWING SPECIAL PROVISIONS SHALL BE USED:
GROUTED BAR COUPLERS (SPV.0060.XXX)
PRECAST PIER COLUMNS (SPV.0090.XXX)
PRECAST PIER CAPS (SPV.0090.XXX)
- THE MAXIMUM WEIGHT OF EACH PRECAST ELEMENT SHALL BE 90 KIP.
- GROUTED COUPLER SLEEVES MAY BE OVERSIZED TO ALLOW FOR ADDITIONAL LATERAL TOLERANCE IN THE FIELD. STANDARD WISDOT PRACTICE IS TO OVERSIZE COUPLER SLEEVES BY 1 BAR SIZE. ADJUST SHEAR STIRRUPS AS NECESSARY TO ACCOUNT FOR LARGER DIAMETER COUPLER SLEEVES.
- VERIFY SEVERAL MANUFACTURER'S COUPLER SLEEVE DIMENSIONS PRIOR TO DESIGN. ASSUME THE MAXIMUM DIAMETER OF COUPLER SLEEVE FOR COLUMN REINFORCEMENT DESIGN.
- SEE STANDARDS 13.01 AND 13.07 FOR ADDITIONAL PIER NOTES AND DETAILS.




DETAILS AS SHOWN ON THIS STANDARD ARE INTENDED FOR REQUIRED PRECAST PIERS DESIGNED TO MEET PROJECT SPECIFIC REQUIREMENTS (REQUIREMENT FOR THE I-39/90 PROJECT). STATEWIDE WISDOT PREFERS ALLOWING PRECAST PIERS AS ALTERNATIVES TO CAST-IN-PLACE PIERS. SEE 7.1.4.1, 2 IN THE BRIDGE MANUAL AND STANDARDS 7.05 AND 7.06 FOR ADDITIONAL GUIDANCE.



*MAKE ALL FOOTING LENGTHS
THE SAME WITHIN A GIVEN PIER

MATERIAL PROPERTIES:
CONCRETE MASONRY f'c = 3,500 P.S.I.
BAR REINFORCEMENT, GRADE 60 fy = 60,000 P.S.I.

PRECAST PIER CAP AND COLUMNS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15



CONTRACTOR NOTES

THE CONTRACTOR SHALL FOLLOW THIS STANDARD WHEN PRECAST PIERS ARE USED IN LIEU OF THE CAST-IN-PLACE PIER. THE USE OF OPTIONAL PRECAST PIER DETAILS SHALL ONLY BE USED WHEN PLANS INDICATE ALLOWANCE OR WITH APPROVAL BY THE BUREAU OF STRUCTURES.

PROVIDE A SUITABLE LIFTING DEVICE FOR THE PRECAST CAP, COLUMN AND BEARING BLOCK UNIT(S).
STIRRUPS AT THE GROUTED COUPLERS ARE SIZED BASED ON A XX" OUTER DIAMETER COUPLER SLEEVE. ADJUST STIRRUP DIMENSIONS AS REQUIRED IF THE ACTUAL COUPLER SLEEVE DIAMETER DIFFERS.

MANUFACTURER TO DETERMINE THE PRECAST PIER COLUMN LENGTHS ASSUMING 1/2" STEEL SHIMS AT THE TOP AND BOTTOM OF THE COLUMN.
GROUTED COUPLER SLEEVES MAY BE OVERSIZED TO ALLOW FOR ADDITIONAL LATERAL TOLERANCE IN THE FIELD. STANDARD WISDOT PRACTICE IS TO OVERSIZE COUPLER SLEEVES BY 1 BAR SIZE. ADJUST SHEAR STIRRUPS AS NECESSARY TO ACCOUNT FOR LARGER DIAMETER COUPLER SLEEVES.

ALL PRECAST ELEMENTS AND DIAPHRAGM ITEMS PAID PER C.J.P BID ITEMS. NO ADDITIONAL PAYMENT WILL BE PROVIDED FOR THE PRECAST PIER OPTION.

THE FOLLOWING SPECIAL PROVISIONS SHALL BE USED:

- GROUTED BAR COUPLERS(SPV.0060.XXX)
- PRECAST PIER COLUMNS(SPV.0090.XXX)
- PRECAST PIER CAPS(SPV.0090.XXX)

THE FOLLOWING ADDITIONAL STANDARDS SHALL BE USED:

- STANDARD 7.04 - PRECAST PIER CAP AND COLUMN DETAILS
- STANDARD 7.06 - PRECAST BEARING BLOCKS DETAILS

DESIGNER NOTES

INCLUDE THE FOLLOWING NOTE ON AT LEAST ONE PIER SHEET FOR EACH PIER:

THE CONTRACTOR MAY FURNISH A PRECAST CONCRETE PIER IN LIEU OF THE CAST-IN-PLACE PIER WITH THE ACCEPTANCE OF THE SHOP DRAWINGS BY THE STRUCTURES DESIGN SECTION. THE PRECAST CONCRETE PIER SHALL CONFORM TO PRECAST DETAILS IN CHAPTER 7 STANDARDS OF THE CURRENT WISCONSIN DOT BRIDGE MANUAL AND SPECIAL PROVISIONS RELATED TO PRECAST ELEMENTS WITH THE EXCEPTION OF METHOD OF PAYMENT. PAYMENT FOR THE PRECAST PIER SHALL BE BASED ON THE QUANTITIES AND PRICES BID FOR THE ITEMS LISTED IN THE "TOTAL ESTIMATED QUANTITIES" FOR THE CAST-IN-PLACE PIER.

PROVIDE CAST-IN-PLACE DETAILS ONLY. PRECAST PIER REFERENCES ARE FOR DESIGNER INFORMATIONAL PURPOSES ONLY AND SHALL NOT BE PLACED ON THE PLANS. PRECAST PIER CONFIGURATION SHALL BE INTERCHANGEABLE BETWEEN C.J.P. AND PRECAST OPTIONS.

ONLY THE PIER CAP LENGTH AND COLUMN LENGTHS SHALL BE MODIFIED. ALL NOTED DIMENSIONS SHALL BE FOLLOWED.

PIERS SHALL BE SUPPORTED BY A MINIMUM OF 3 COLUMNS. WHEN MULTIPLE PIER CAPS ARE USED, EACH SEGMENT SHALL BE SUPPORTED BY A MINIMUM OF 2 COLUMNS.

PROVIDE A CONCRETE DIAPHRAGM BETWEEN PIER CAP SEGMENTS.

MULTIPLE PIER CAP SEGMENTS MAY BE SET AT DIFFERENT ELEVATIONS TO ACCOMMODATE BEARING ELEVATIONS BEYOND CONCRETE BEARING BLOCK LIMITS.

THE MAXIMUM WEIGHT OF EACH PRECAST ELEMENT SHALL BE 90 KIP.

SEE STANDARDS 7.03, 7.04, 7.06, 13.01 AND 13.07 FOR ADDITIONAL PIER NOTES AND DETAILS.


LEGEND

- ☆ STD. HOOK (TYP.) ROTATE AND STAGGER AS NEEDED.
- DIMENSION IS FROM BOTTOM OF PIER CAP TO LOW BEAM SEAT.

POLICY AND DETAILS REGARDING THE USE OF PRECAST PIER CAPS AND COLUMNS IS BEING DEVELOPED BY THE BUREAU OF STRUCTURES IN CONJUNCTION WITH THE I-39/90 PROJECT. SEE 7.1.4.1.2 FOR ADDITIONAL GUIDANCE.

PRECAST PIER (OPTIONAL) CAP AND COLUMNS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15

MATERIAL PROPERTIES:
CONCRETE MASONRY $f'c = 3,500$ P.S.I.
BAR REINFORCEMENT, GRADE 60 $f_y = 60,000$ P.S.I.



**PARTIAL TRANSVERSE SECTION
AT DIAPHRAGM PIER**


STD. 19.35 SHOWN (STD. 19.33 & 19.34 SIM.)

BILL OF BARS

TOTAL COATED: XX LBS


BAR MARK	NO. REQ'D.	LENGTH	COAT	BENT	LOCATION
P450		3'-5"	X		TOP & BOT. TRANS.
P451			X		TOP & BOT. LONG.
P552		1'-"	X		PIER DIAPHRAGM - BOTH FACES HORIZ. - BTWN GIRDERS
P553		1'-"	X	X	PIER DIAPHRAGM - VERT. - BTWN GIRDERS

NOTE: THIS BILL OF BARS IS SHOWN FOR INFORMATION ONLY. PRECAST PIER SHOP DRAWINGS SHALL INCLUDE BILL OF BARS FOR DIAPHRAGM REINFORCEMENT. PAYMENT FOR ALL ITEMS ASSOCIATED WITH THE OPTIONAL PRECAST PIERS SHALL BE INCLUDED IN THE CAST-IN-PLACE CONCRETE BID ITEMS.




S553


▲ MATCH SIMILAR DIAPHRAGM REIN. AS SHOWN IN CONTRACT PLANS.



PLAN



PLAN



ELEVATION

TABLE "A"

SKIEW ANGLE	BEARING BLOCK WIDTH (MIN.)	LONG. BAR LENGTH ●
0° TO 15°	3'-3"	2'-11"
15° TO 20°	3'-6"	3'-2"
> 20°	3'-9"	3'-5"

CONTRACTOR NOTES

THE CONTRACTOR SHALL FOLLOW THIS STANDARD WHEN PRECAST PIERS ARE USED IN LIEU OF THE CAST-IN-PLACE PIER.

PRECAST CONCRETE DETAIL NOTES

PRECAST BEARING BLOCK DETAILS SHALL ONLY BE USED WHEN PLANS INDICATE ALLOWANCE FOR PRECAST PIERS.

* PRECAST HEIGHT = VARIES (5" MIN. TO 1'-11 1/4" MAX.). MANUFACTURER TO DETERMINE THE PRECAST BEARING BLOCK HEIGHT ASSUMING 1/4" GROUT AT THE BOTTOM OF THE BEARING BLOCK.

GROUT 1/4" BENEATH PRECAST ELEMENT.

POLICY AND DETAILS REGARDING THE USE OF PRECAST PIER CAPS AND COLUMNS IS BEING DEVELOPED BY THE BUREAU OF STRUCTURES IN CONJUNCTION WITH THE I-39/90 PROJECT. SEE 7.1.4.1,2 FOR ADDITIONAL GUIDANCE.


**PRECAST BEARING BLOCK
DETAILS**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15

LEGEND

- ◆ #5 BARS (COATED) AT 1'-0" (2'-0" LONG). THESE BARS MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE.
- ◇ WHEN THIS DIMENSION ≥ 4" THIS ADDITIONAL REINFORCEMENT SHALL BE ADDED. MAX. SPA. OF HORIZ. #4 BARS = 1'-0".
- USE 1'-3" FOR SLAB SPANS AND FOR GIRDER SPANS WITH NO PAVING NOTCH. USE 1'-6" FOR GIRDER SPANS WITH NO PAVING NOTCH, BUT WHERE 36W", 45W", 54", 54W", 70", 72W" OR 82W" GIRDERS ARE USED, AND SKEW > 25°. USE 1'-3" FOR SLAB SPANS WITH A PAVING NOTCH, BUT NO STRUCTURAL APPROACH SLAB. USE 1'-11" FOR GIRDER SPANS WITH A PAVING NOTCH, BUT NO STRUCTURAL APPROACH SLAB. USE 1'-7" FOR SLAB SPANS WITH A STRUCTURAL APPROACH SLAB. (STD. 12.10) USE 2'-3" FOR GIRDER SPANS WITH A STRUCTURAL APPROACH SLAB. (STD. 12.10)
- DIMENSION IS FROM BOTTOM OF ABUTMENT TO LOW BEAM SEAT OR LOW SIDE OF SLAB TYPE SUPERSTRUCTURE.
- ▽ 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- ▲ KEYED CONST. JOINT FORMED BY BEVELED 2" x 6".
- ** WINGWALL WIDTH SHALL BE 1'-6" WHEN "M" RAILING, VERTICAL FACE PARAPET "TX", OR SINGLE SLOPE PARAPET "565S" IS USED. WINGWALL WIDTH SHALL BE 1'-9" WHEN TYPE "NY3" OR "NY4" RAILING IS USED.
- USE #5 BARS AT 6" SPA. IN OUTSIDE THIRDS OF BODY LENGTH WHEN THE WING LENGTH > 20'-0" AND WING HEIGHT > 10'-0".
- ☆ WHEN BODY SECTION IS > 50'-0"± LONG PROVIDE VERTICAL CONSTRUCTION JOINT. RUN BAR STEEL THRU JOINT AND SEAL JOINT WITH 18" RUBBERIZED MEMBRANE WATERPROOFING. SEE STD. 12.09 FOR ALTERNATE CONSTRUCTION JOINT.
- ⊙ SHOW ALL BARS FOR CLARITY.



RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE. THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

DESIGNER NOTES


LAP LENGTHS FOR HORIZONTAL BARS SHALL BE BASED ON A "CLASS C" TOP TENSION LAP SPLICE.

PILING SPACING IN ABUTMENT BODY SHALL BE 8'-0" MAX. FOR ALL TYPES OF PILING. THE MAX. PILE SPACING FROM THE END OF THE ABUT. BODY TO THE FIRST PILE SHALL BE THE MINIMUM OF ONE-HALF PILE SPACE OR 2'-6".


CONCRETE POURED UNDER WATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 STANDARD SPECIFICATIONS.

THE SEMI-EXPANSION SEAT SHALL BE USED WHEN REQUIRED AS STATED IN CHAPTER 12, FIGURE 12.7-1 OF THE BRIDGE MANUAL OR WHENEVER A WING PILE IS REQUIRED.


THE FIXED SEAT CANNOT BE USED WHEN A WING PILE IS REQUIRED (SEE STD 12.02 FOR CRITERIA)



TYPE A1 WITH FIXED SEAT




TYPE A1 WITH SEMI-EXPANSION SEAT




WING WITHOUT PILE

DISTANCE OR EQUIVALENT STD. HOOK	BAR SIZE
1'-9"	5
2'-1"	6
2'-9"	7
3'-8"	8
4'-7"	9
5'-10"	10



WING WITH PILE




SLAB SPAN WITH FIXED SEAT

GIRDER SPAN WITH FIXED SEAT

SLAB SPAN WITH SEMI-EXPANSION SEAT

GIRDER SPAN WITH SEMI-EXPANSION SEAT

ABUTMENT TYPE A1 (INTEGRAL ABUTMENT)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 1-15




FRONT ELEVATION

DESIGNER NOTES


PIILING SPACING IN ABUTMENT FOOTING SHALL BE 8'-0" MAXIMUM.
 WHEN BODY SECTION IS MORE THAN 50'-0" LONG, PROVIDE VERTICAL CONSTRUCTION JOINT. RUN BAR STEEL THRU JOINT. SEAL JOINT WITH 18" RUBBERIZED MEMBRANE WATERPROOFING. SEE STD. 12.09 FOR ALTERNATE CONSTRUCTION JOINT.
 IN "FRONT ELEVATION" VIEW, GIVE ELEVATION OF ALL BEARING AREAS AND ELEVATION AT BOTTOM OF PARAPETS AT EACH END OF WINGS. ALL ELEVATIONS ARE TAKEN AT FRONT FACE OF BACKWALL.
 LAP LENGTHS FOR HORIZONTAL BARS SHALL BE BASED ON A "CLASS C" TOP TENSION LAP SPLICE.
 PARAPET NOT SHOWN IN PLAN VIEW FOR CLARITY.

LEGEND


- ▣ 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZ. AND VERT. JOINTS ON BACKFACE ABOVE FOOTING.
- △ KEYED CONSTRUCTION JOINT FORMED BY BEVELED 2" X 6".
- #4 AT 9" BEAM SEAT. SPACE AT 1'-0" BETWEEN SEATS. THIS STEEL IS REQUIRED ONLY IF DIMENSION "A" EXCEEDS 4".
- † 1'-5" WHEN VERTICAL FACE PARAPET TYPE "TX" IS USED.
- * 4" WHEN VERTICAL FACE PARAPET TYPE "TX" IS USED.
- ** WINGWALL WIDTH SHALL BE 1'-6" WHEN TYPE "M" RAILING, VERTICAL FACE PARAPET "TX", OR SINGLE SLOPE PARAPET "56SS" IS USED. "56SS" SHOULD NOT BE USED ON A SIDEWALL. WINGWALL WIDTH SHALL BE 1'-9" WHEN TYPE "NY3" OR "NY4" RAILING IS USED.
- ☒ 3'-3" (SLOPE PAVING), 4'-6" (HEAVY RIPRAP)
- PAVING NOTCH IS 1'-0" WIDE BY 1'-4" DEEP IF STRUCTURAL APPROACH SLAB (STD. 12.12) IS USED.
- ☆ SIDE WALL IS 1'-3" WIDE IF STRUCTURAL APPROACH SLAB (STD. 12.12) IS USED.
- ⊙ SHOW ALL BARS FOR CLARITY.



KEY DETAIL



SECTION B-B



A3 BARS (TYP.)


BAR SIZE	DISTANCE*
#5	1'-5"
#6	1'-9"
#7	2'-3"
#8	3'-0"
#9	3'-9"
#10	4'-10"

* OR EQUIVALENT STANDARD HOOK

WING WITH SIDEWALK

PLAN

WING WITH SLOPED FACE PARAPET



SECTION THRU BODY

ALL FOOTING BARS NOT IDENTIFIED ARE #5 BARS

h = WING HEIGHT (FT.)
 $P = \chi D C (P D C)^2 \chi D W (P D W)^2 \chi L L (L L) (k / F T.)$

PILE REACTIONS PER FOOT IN KIPS

FRONT ROW = $P [(0.22 \times X / 4.25)] + [(n + 2.25) / 705] + 4.6$
 BACK ROW = $P [(0.78 \times X / 4.25)] - [(n + 2.25) / 705] + 16.8$


(PILES MUST ALSO BE DESIGNED TO ACCOUNT FOR LATERAL LOADS)

P k/FT.	FOOTING STEEL SIZE
20	#6
40	#7
62	#8
75	#9

ABUTMENT TYPE A3

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15



APPROACH SLAB PLAN

DESIGNER NOTES

STRUCTURAL APPROACH SLABS AND PARAPETS SHALL BE USED ON ALL LH, BRIDGES AND U.S.H. BRIDGES. OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER.

STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED BRIDGES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.

QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.

CONSTRUCTION JOINT REQUIRED WHEN WIDTH OF SUPERSTRUCTURE EXCEEDS 90'. RUN REINFORCEMENT THROUGH THE JOINT.

LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).

STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.), WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).

THE BID ITEM FOR S5901 BARS SHALL BE STANDARD SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS STRUCTURES".

DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND FDM SDD 802 OR 803.

LEGEND

SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE).

SEE PARAPET STANDARD DETAILS FOR LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET.

DESIGN DATA

CONCRETE STRENGTH, f'c: 4,000 P.S.I.
 BAR STEEL REINFORCEMENT, GRADE 60, fy: 60,000 P.S.I.
 ALLOWABLE SOIL BEARING PRESSURE: 2,000 P.S.F.


NOTE: FOR NEW STRUCTURES ON NEW ALIGNMENTS, BASE AGGREGATE DENSE 1-1/4 INCH AS PER FDM 14-5 AND BRIDGE MANUAL FIGURE 12.6-2 SHALL BE UTILIZED. FOR REPLACEMENT STRUCTURES ON EXISTING ALIGNMENTS, THE EXISTING SOIL MAY REMAIN IN PLACE IF THE REGION SOILS ENGINEER DETERMINES THAT THE EXISTING SOIL BEARING PRESSURE MEETS THE REQUIREMENT ABOVE.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENDS	BAR SERIES	LOCATION
S5901			5'-0"	X		CONC. ABUT. DIAPH. TO APPROACH SLAB

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENDS	BAR SERIES	LOCATION
T501	X			X		APPROACH SLAB FTG. - STIRRUP
T802	X					APPROACH SLAB FTG. - TRANS.
T803	X			X		APPROACH SLAB - LONG. - BOT.
T804	X					APPROACH SLAB - LONG. - BOT. - WALL
T505	X					APPROACH SLAB - LONG. - TOP.
T506	X					APPROACH SLAB - LONG. - WALL
T507	X					APPROACH SLAB - TRANS. - BOT.
T508	X					APPROACH SLAB - TRANS. - TOP.
T509	X		4'-3"	X		APPROACH SLAB - TRANS. - TOP - WALL
T510	X		4'-1"	X		APPROACH SLAB - TRANS. - TOP - WING
T411	X		3'-0"	X		APPROACH SLAB - TRANS. - WALL




STRUCTURAL APPROACH SLAB FOR TYPE A1 ABUTMENTS

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
 1-15


SECTIONS A-A THRU E-E ARE SHOWN ON STANDARD 12.11




SECTION A-A
(AT MSE WINGWALLS)




SECTION E-E
(AT MSE WINGWALLS)




SECTION B-B
(AT WINGWALLS PERP. TO BRIDGE)



SECTION B-B
(AT WINGWALLS PARALLEL TO BRIDGE)



SECTION C-C



SECTION D-D

SECTION THRU APPROACH SLAB

MEASURED NORMAL TO ABUTMENT

LEGEND

- (T02) STEEL TROWEL TOP SURFACE OF FOOTING AND PLACE MULTIPLE LAYERS (0.03" MIN. TOTAL THK.) OF POLYETHYLENE SHEETS OVER THE ENTIRE TOP OF FOOTING.
- (T03) PLACE MULTIPLE LAYERS (0.03" MIN. TOTAL THK.) OF POLYETHYLENE SHEETS OVER THE ENTIRE TOP OF SUBGRADE BENEATH SLAB.
- ▲ SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE).

DESIGNER NOTES


- STRUCTURAL APPROACH SLABS AND PARAPETS SHALL BE USED ON ALL I.H. BRIDGES AND U.S.H. BRIDGES. OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER.
- STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED BRIDGES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.
- QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.
- LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).
- STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.). WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).
- ★ THE BID ITEM FOR SS901 BARS SHALL BE STANDARD SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS STRUCTURES".
- DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND FDM SDD 802 OR 803.
- SEE PARAPET STANDARD DETAILS FOR REINFORCEMENT, LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET, ETC.
- BELOW THE APPROACH SLAB FOOTING AND STRUCTURAL APPROACH SLAB, SHOW BASE AGGREGATE DENSE 1-1/4 INCH AS PER FDM 14-5 AND BRIDGE MANUAL FIGURE 12.6-2.
- FOLLOW FDM 14-10-15 REQUIREMENTS FOR ROADWAY APPROACH PAVEMENT.

**STRUCTURAL APPROACH SLAB
DETAILS FOR TYPE A1 ABUTMENTS**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15

SECTIONS SHOWN HERE ARE FROM STANDARD 12.10



APPROACH SLAB FTG. = XX'-XX"

APPROACH SLAB WIDTH = XX'-X"

APPROACH SLAB PLAN

DESIGNER NOTES

STRUCTURAL APPROACH SLABS AND PARAPETS SHALL BE USED ON ALL I.H. BRIDGES AND U.S.H. BRIDGES. OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER.

STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED BRIDGES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.

QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.

CONSTRUCTION JOINT REQUIRED WHEN WIDTH OF SUPERSTRUCTURE EXCEEDS 90'. RUN REINFORCEMENT THROUGH THE JOINT.

LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).

STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.). WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).

THE BID ITEM FOR SS901 BARS SHALL BE STANDARD SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS STRUCTURES".

DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND FDM SDD 802 OR 803.

LEGEND

SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

SEE PARAPET STANDARD DETAILS FOR LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET.

DESIGN DATA

CONCRETE STRENGTH, f'_c: 4,000 P.S.I.
 BAR STEEL REINFORCEMENT, GRADE 60, f_y: 60,000 P.S.I.
 ALLOWABLE SOIL BEARING PRESSURE: 2,000 P.S.F.


NOTE: FOR NEW STRUCTURES ON NEW ALIGNMENTS, BASE AGGREGATE DENSE 1-1/4 INCH AS PER FDM 14-5 AND BRIDGE MANUAL FIGURE 12.6-2 SHALL BE UTILIZED. FOR REPLACEMENT STRUCTURES ON EXISTING ALIGNMENTS, THE EXISTING SOIL MAY REMAIN IN PLACE IF THE REGION SOILS ENGINEER DETERMINES THAT THE EXISTING SOIL BEARING PRESSURE MEETS THE REQUIREMENT ABOVE.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REOD.	LENGTH	BENT	BAR SERIES	LOCATION
SS901			5'-0"	X		CONC. BACKWALL TO APPROACH SLAB

BAR MARK	COAT	NO. REOD.	LENGTH	BENT	BAR SERIES	LOCATION
T501	X			X		APPROACH SLAB FTG. - STIRRUP
T802	X					APPROACH SLAB FTG. - TRANS.
T803	X			X		APPROACH SLAB - LONG. - BOT.
T804	X					APPROACH SLAB - LONG. - BOT. - WALL
T505	X					APPROACH SLAB - LONG. - TOP.
T506	X					APPROACH SLAB - LONG. - WALL
T507	X					APPROACH SLAB - TRANS. - BOT.
T508	X					APPROACH SLAB - TRANS. - TOP.
T509	X	4'-3"	X			APPROACH SLAB - TRANS. - TOP - WALL
T510	X	4'-1"	X			APPROACH SLAB - TRANS. - TOP - WING
T411	X	3'-0"	X			APPROACH SLAB - TRANS. - WALL



STRUCTURAL APPROACH SLAB FOR TYPE A3 & A4 ABUTMENTS

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE: 1-15

SECTIONS A-A THRU F-F ARE DETAILED ON STANDARD 12.13


MAXIMUM LENGTH OF SINGLE POUR = 65'-0" WHEN REQUIRED.
PLACE KEYED VERTICAL CONST. JOINT NEAR POINT OF DEADLOAD CONTRAFLEXURE.
(SEE STANDARD 12.09 FOR ALTERNATE CONSTRUCTION JOINT DETAILS)

GIVE ELEVATIONS AT CENTER OF COLUMN WHEN CAP IS SLOPING AND FOR ALL CONCRETE SLAB SPAN STRUCTURES

LEVEL (SEE DESIGNER NOTES)

LEVEL UNLESS DIM. "A" IS 9" GREATER THAN MIN. DEPTH. SLOPE BOTTOM OF CAP WHEN THIS WOULD BE EXCEEDED.

GIVE ELEVATION OF BEAM SEATS.



SLOPING BEAM SEAT DETAILS

DESIGNER NOTES

ALL BAR SPLICES TO BE BASED ON "CLASS C" TENSION LAP SPLICE UNLESS OTHERWISE SHOWN.

SLOPE TOP OF COLUMNS TO MATCH CAP WHEN THE BOTTOM OF THE CAP IS SLOPED. DETAIL BOTTOM OF CAP REINFORCEMENT TO CLEAR VERTICAL COLUMN REINFORCEMENT.

CAPS MAY BE MORE THAN 3" WIDER THAN COLUMNS IF THE EXTRA WIDTH IS NECESSARY TO SATISFY THE MINIMUM EDGE DISTANCE CRITERIA ADJACENT TO BEARINGS

BEARING SEAT AREAS SHALL BE LEVEL EXCEPT FOR THE TWO CASES LISTED BELOW:

1. FOR GIRDERS WITH 1/2" ELASTOMERIC BEARING PADS WHEN THE BOTTOM OF THE GIRDERS SLOPE MORE THAN 1%.
2. WHEN A CAP IS USED FOR CONCRETE SLAB SUPERSTRUCTURES MAKE THE TOP OF THE CAP PARALLEL TO GRADE. SEE STANDARD 18.01.

BEAM SEATS MAY BE ANGLED TO MATCH SKEW AT THE DESIGN ENGINEER'S DISCRETION.


SEE STANDARD 12.01 FOR ADDITIONAL REINFORCING STEEL IN BEARING AREA FOR BEAM SEATS OF NON-SLOPED CAPS THAT ARE 4" OR MORE ABOVE LOWEST BEAM SEAT.

EPOXY COAT BAR STEEL DOWN TO TOP OF FOOTINGS IN ALL PIERS UNDER EXPANSION JOINTS AND ON ALL PIERS AT GRADE SEPARATIONS.


BAR STEEL REQUIRED FOR BENDING IN PIER CAP SHALL BE DETAILED IN LENGTHS AS REQUIRED FOR CONSTRUCTIBILITY AND BY DESIGN SPECIFICATIONS. MAXIMUM REQUIRED BAR STEEL IN THE TOP OF THE PIER CAP (NEGATIVE MOMENT STEEL) MAY BE DETAILED FULL LENGTH IF A MINOR COST INCREASE.

SEE BRIDGE MANUAL 13.4.10 FOR MULTI-COLUMNED PIER DESIGN REGARDING VEHICULAR COLLISION FORCE. THE PIER OPTIONS REPRESENTED ON THIS STANDARD DO NOT MEET THE REQUIREMENTS OF AASHTO LRFD 3.6.5. FOR VEHICULAR COLLISION FORCE.



△ NORMALLY THIS LAP IS OMITTED AND FOOTING DOWELS EXTENDED INTO THE CAP IF THE LAP IS GREATER THAN ONE-HALF THE COLUMN HEIGHT.




ELEVATION
LOOKING UP STATION



END VIEW




PLAN VIEW SHOWING END OF CAP REIN.



PLAN


SHOWING BOTH SQUARE AND ROUND ENDED CAP

*MAKE ALL FOOTING LENGTHS THE SAME WITHIN A GIVEN PIER.



SECTION P1

DIMENSION BARS TO CLEAR ANCHOR BOLTS ON STEEL GIRDER STRUCTURES




SECTION P2


MULTI-COLUMNED PIER	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 7-12

GIRDER STRUCTURES


CONCRETE SLAB STRUCTURES




ELEVATION
LOOKING UP STATION




PLAN




END VIEW



CONST. JT. DETAIL



SECTION P1



ALTERNATE SECTION P1

DESIGNER NOTES

ALL BAR SPLICES TO BE BASED ON "CLASS C" TENSION LAP SPLICE UNLESS OTHERWISE SHOWN.

OPTIONAL KEYED CONSTRUCTION JOINTS IN SHAFT, IF PROVIDED, SHALL BE PLACED APPROXIMATELY 2'-0" ABOVE NORMAL WATER ELEVATION. OPTIONAL KEYED CONSTRUCTION JOINTS IN SHAFT SHOULD BE PROVIDED SO THAT THE MAXIMUM HEIGHT OF POUR NEED NOT EXCEED 25'-0". DETAIL BAR SPLICES AT OPTIONAL JOINTS IF THE BAR PROJECTION WOULD BE GREATER THAN 20'-0". RUSTICATIONS SHOWN IN "CONST. JT. DETAIL" MAY BE OMITTED AT THE OPTION OF THE DESIGNER.

KEYED CONSTRUCTION JOINTS SHALL BE FORMED BY BEVELED KEYWAY 4" DEEP X 1/3 THICKNESS OF SHAFT X 4'-0" LESS THAN LENGTH OF SHAFT.

A STANDARD SHAFT TAPER OF 10% MAY BE USED AT THE OPTION OF THE DESIGNER. (LATERAL DIRECTION ONLY)

SHAFT MAY BE TAPERED IN ONE OR TWO DIRECTIONS WHEN REQUIRED FOR STRUCTURAL REASONS.

A NON-STANDARD SHAFT CROSS-SECTION, SHAPE, OR TAPER, NOT REQUIRED FOR STRUCTURAL REASONS, MAY BE USED ONLY WITH THE APPROVAL OF THE STRUCTURES DESIGN SECTION.

BEARING SEAT AREAS SHALL BE LEVEL EXCEPT FOR THE TWO CASES LISTED BELOW:

1. FOR GIRDERS WITH 1/2" ELASTOMERIC BEARING PADS WHEN THE BOTTOM OF THE GIRDERS SLOPE MORE THAN 1%. SEE STANDARD 13.01.

2. FOR CONCRETE SLAB SUPERSTRUCTURES MAKE THE TOP OF CAP PARALLEL TO GRADE. SEE STANDARD 18.01.

BEAM SEATS MAY BE ANGLED TO MATCH SKEW AT THE DESIGN ENGINEER'S DISCRETION.

SEE STANDARD 12.01 FOR ADDITIONAL REINFORCING STEEL IN BEARING AREA FOR BEAM SEATS OF NON-SLOPED CAPS THAT ARE 4 INCHES OR MORE ABOVE THE LOWEST BEAM SEAT.

THIS MAXIMUM VERT. BAR SPACING APPLIES ONLY WHEN THE VERTICAL REINFORCEMENT IS 1% OR MORE OF THE GROSS CONCRETE AREA.

SEE STANDARD 13.01 FOR MINIMUM OFFSETS FROM BEARINGS TO SIDES OF CAP AND TO ADJACENT BEARING SEAT STEPS.

EPOXY COAT BAR STEEL DOWN TO TOP OF FOOTINGS IN ALL PIERS UNDER EXPANSION JOINTS AND ON ALL PIERS AT GRADE SEPARATIONS.

INCREASE THIS DIMENSION IF NECESSARY TO PREVENT BATTERED PILES FROM DRIVING INTO SHEET PILING. ALSO INCREASE DIMENSION TO FACILITATE OVERHEAD SHEETING CLEARANCE IF THE TOP OF PIER IS BEYOND NORMAL SEAL SIZE AND NO CONSTRUCTION JOINT IS PROVIDED IN THE SHAFT/CAP REGION (E.G. TAPERED WALL PIERS OR SHORTER HAMMERHEADS WITH RADIUS TRANSITION FROM SHAFT TO CAP).

MAXIMUM SPACING BETWEEN UNRESTRAINED VERTICAL BAR AND RESTRAINED (TIED ACROSS MEMBER) VERTICAL BAR IS 24 INCHES.

PLAN NOTES


THE BAR SPLICES AT THE OPTIONAL KEYED CONSTRUCTION JOINTS MAY BE ELIMINATED WHETHER OR NOT THE JOINT IS UTILIZED. PAYMENT WILL BE FOR THE ACTUAL BARS INSTALLED.

HAMMERHEAD PIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: *Bill Oliva*

DATE:
1-15




SECTION P1


2" x 6" BEVELED KEYWAY BETWEEN GIRDERS ON PRESTRESSED GIRDER SUPERSTRUCTURES. REFER TO STANDARD 19.33, 19.34, 19.35.




PLAN OF PIER CAP



SECTION P2



END VIEW



ELEVATION
LOOKING UP SHAFT

PLAN NOTES

THE BAR SPLICES AT THE OPTIONAL KEYED CONSTRUCTION JOINTS MAY BE ELIMINATED WHETHER OR NOT THE JOINT IS UTILIZED. PAYMENT WILL BE FOR THE ACTUAL BARS INSTALLED.

DESIGNER NOTES (CONT.)

- THIS MAXIMUM VERT. BAR SPACING APPLIES ONLY WHEN THE VERTICAL REINFORCEMENT IS 1% OR MORE OF THE GROSS CONCRETE AREA.
- MAXIMUM SPACING BETWEEN UNRESTRAINED VERTICAL BAR AND RESTRAINED (TIED ACROSS MEMBER) VERTICAL BAR IS 24 INCHES

DESIGNER NOTES


ALL BAR SPLICES TO BE BASED ON "CLASS C" TENSION LAP SPLICE UNLESS OTHERWISE SHOWN.

OPTIONAL KEYED CONSTRUCTION JOINTS IN SHAFT, IF PROVIDED, SHALL BE PLACED APPROXIMATELY 2'-0" ABOVE NORMAL WATER ELEVATION. OPTIONAL KEYED CONSTRUCTION JOINTS IN SHAFT SHOULD BE PROVIDED SO THAT THE MAXIMUM HEIGHT OF POUR NEED NOT EXCEED 25'-0". DETAIL BAR SPLICES AT OPTIONAL JOINTS IF THE BAR PROJECTION WOULD BE GREATER THAN 20'-0".


KEYED CONSTRUCTION JOINTS SHALL BE FORMED BY BEVELED KEYWAY 4" DEEP X 1/3 THICKNESS OF SHAFT X 4'-0" LESS THAN LENGTH OF SHAFT. EXPOSED EDGES OF CONSTRUCTION JOINT SHALL BE FLUSH AND NOT BEVELED.

BEARING SEAT AREAS SHALL BE LEVEL EXCEPT FOR THE TWO CASES LISTED BELOW:


1. FOR GIRDER WITH 1/2" ELASTOMERIC BEARING PADS THAN 1% WHEN THE BOTTOM OF THE GIRDERS SLOPE MORE THAN 1%. SEE STANDARD 13.01.
 2. WHEN A CAP IS USED FOR CONCRETE SLAB SUPERSTRUCTURES MAKE THE TOP OF CAP PARALLEL TO GRADE. SEE STANDARD 18.01.
- BEAM SEATS MAY BE ANGLED TO MATCH SKEW AT THE DESIGN ENGINEER'S DISCRETION.
- SEE STANDARD 12.01 FOR ADDITIONAL REINFORCING STEEL IN BEARING AREA FOR BEAM SEATS THAT ARE 4" OR MORE ABOVE LOWEST BEAM SEAT.
- FOR "HAMMERHEAD LENGTH" GREATER THAN 45'-0", CONSIDER A TWO SHAFT PIER FRAME RESEMBLING TWO HAMMERHEAD PIERS PLACED SIDE BY SIDE.
- SEE STANDARD 13.01 FOR MINIMUM OFFSETS FROM BEARINGS TO SIDES OF CAP AND TO ADJACENT BEARING SEAT STEPS.
- EPOXY COAT BAR STEEL DOWN TO TOP OF FOOTINGS IN ALL PIERS UNDER EXPANSION JOINTS AND ON ALL PIERS AT GRADE SEPARATIONS.



DETAIL A



TEXTURING LIMITATIONS OF PIER WALL
(EACH FACE)




TWO SHAFT PIER

HAMMERHEAD PIER - TYPE 2

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva DATE: 1-15



18" RUBBERIZED MEMBRANE WATERPROOFING TO BE PLACED ON THESE SURFACES AT EACH JOINT.

IF THE OPT. CONST. JOINT IS USED, PLACE 18" MEMBRANE WATERPROOFING ALONG THE ENTIRE LONGITUDINAL JOINT. THE MEMBRANE WATERPROOFING SEALING THE OPTIONAL CONST. JOINT IS INCIDENTAL TO THE CONCRETE MASONRY BID ITEM.

RUSTICATION DETAIL
 PROVIDE RUSTICATION IF OPT. CONST. JOINT IS USED.



LIQUID OR OTHER BOND BREAKER BETWEEN CAST-IN-PLACE CONCRETE AND CAST-IN-PLACE WALL PANEL.

CAST-IN-PLACE CONCRETE TRAFFIC BARRIER DETAIL FOR PRECAST WALL PANELS


OPTIONAL CONSTRUCTION JOINTS IN THE PARAPET AND ANCHOR SLAB BETWEEN EXPANSION JOINTS MAY BE USED. RUN BAR REINFORCEMENT THRU THE JOINT. SEE STANDARDS 30.07, 30.12, 30.13 & 30.30-30.32 FOR MINIMUM LAP LENGTHS IN PARAPET BARS. DEFINE CONSTRUCTION JOINT WITH A 3/4" "V" GROOVE.

LAP LONGITUDINAL #4 BARS A MINIMUM OF 1'-0".
 ALL BAR STEEL SHALL BE EPOXY COATED.
 CONCRETE QUANTITY BASED ON 3" PANEL EMBEDMENT.

CAST-IN-PLACE CONCRETE TRAFFIC BARRIER DETAIL FOR CAST-IN-PLACE WALL PANELS


OPTIONAL CONSTRUCTION JOINTS IN THE PARAPET AND ANCHOR SLAB BETWEEN EXPANSION JOINTS MAY BE USED. RUN BAR REINFORCEMENT THRU THE JOINT. SEE STANDARDS 30.07, 30.12, 30.13 & 30.30-30.32 FOR MINIMUM LAP LENGTHS IN PARAPET BARS. DEFINE CONSTRUCTION JOINT WITH A 3/4" "V" GROOVE.

LAP LONGITUDINAL #4 BARS A MINIMUM OF 1'-0".
 ALL BAR STEEL SHALL BE EPOXY COATED.




CAST-IN-PLACE CONCRETE COPING DETAIL

NOTE: CONCRETE COPING REINFORCING STEEL SHALL BE DESIGNED AT LOCATIONS WHERE RAILING, FENCING, OR ANY OTHER ATTACHMENTS ARE MADE.




TRAFFIC BARRIER EXPANSION JOINT DETAIL




ANCHOR SLAB EXPANSION JOINT DETAIL

EXPANSION JOINTS TO BE SPACED AT A MINIMUM OF 20' AND A MAXIMUM OF 30'. LOCATE EXPANSION JOINTS OVER WALL JOINTS. DO NOT RUN BAR STEEL THRU JOINT, EXCEPT FOR DOWEL BARS. JOINT TO EXTEND FULL DEPTH OF PARAPET AND ANCHOR SLAB. PROVIDE THE NUMBER OF BARS AND OVERALL LENGTH FOR QUANTITY PURPOSES, ONLY. DO NOT DETAIL SPECIFIC BAR LENGTHS BETWEEN EXPANSION JOINTS AS THESE LENGTHS ARE BASED ON UNKNOWN MSE PANEL LENGTH AND CONFIGURATION.




C.I.P. TRAFFIC BARRIER OR COPING PARTIAL ELEVATION

NOTE: ALL JOINTS SHALL BE LOCATED AS SHOWN ON WALL ELEVATIONS AND MUST COINCIDE WITH PANEL JOINT ON FRONT FACE.



COPING EXPANSION JOINT

DO NOT RUN BAR STEEL THRU JOINT. MAX. SPACING OF JOINT = 50'




COPING CONTRACTION JOINT

DO NOT RUN BAR STEEL THRU JOINT. MAX. SPACING OF JOINT = 12'


DESIGNER NOTES

MODIFIED ANCHOR SLAB DETAILS SHALL SATISFY AASHTO LRFD STRENGTH AND STABILITY REQUIREMENTS.


MSE RETAINING WALL DETAILS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 1-15



PLAN VIEW OF DECK CONTINUITY REINFORCEMENT FOR PRESTRESSED GIRDER BRIDGES
(SHOWING TYPICAL BAR SPACING FROM CHAPTER 17 TABLES)



PLAN VIEW OF DECK CONTINUITY REINFORCEMENT FOR PRESTRESSED GIRDER BRIDGES SHOWING HALF-SPACES
(SHOWING TYPICAL BAR SPACING FROM CHAPTER 17 TABLES + HALF-SPACE)




LONGITUDINAL CONSTRUCTION JOINT DETAIL


DESIGNER NOTES

DETAIL REQUIRED WHEN WIDTH OF DECK EXCEEDS 90 FEET FOR GIRDER SUPERSTRUCTURES AND 52 FEET FOR SLAB SUPERSTRUCTURES. DETAIL SHOULD BE USED FOR STAGED CONSTRUCTION AND FOR OTHER COLD JOINT APPLICATIONS WITHIN THE DECK. OPTIONAL (CONTRACTOR) JOINTS ARE TO BE APPROVED BY THE ENGINEER.


JOINTS SHOULD BE PLACED AT LEAST 6 INCHES FROM THE EDGE OF THE TOP FLANGE OF THE GIRDER AND PREFERABLY LOCATED BENEATH THE MEDIAN OR PARAPET. AVOID PLACING NEAR WHEEL PATHS (PLACE AT LANE LINES OR IN THE MIDDLE OF THE LANE).




CROSS SECTION THRU DECK
(SHOWING TOP LONGIT. REINF. LOCATION RELATIVE TO BOTTOM LONGIT. REINF.)




CROSS SECTION THRU EDGE OF DECK
(SHOWING DRIP GROOVE FOR ALL PARAPET AND RAILINGS, AND PROTECTIVE SURFACE TREATMENT FOR OPEN RAILINGS)



CROSS SECTION THRU EDGE OF SLAB
(SHOWING DRIP GROOVE FOR ALL PARAPET AND RAILINGS, AND PROTECTIVE SURFACE TREATMENT FOR OPEN RAILINGS)



CROSS SECTION THRU EDGE OF DECK
(SHOWING ADDITIONAL OVERHANG REINFORCEMENT)



CROSS SECTION THRU EDGE OF DECK
(SHOWING ADDITIONAL OVERHANG REINFORCEMENT)

THESE DETAILS ARE MERELY REPRESENTATIVE OF WHAT CAN BE DONE FOR OVERHANG REINFORCEMENT WHEN SUPERELEVATIONS, EXCESSIVE HAUNCHES, M-RAILS, ETC. ARE ENCOUNTERED ON PRESTRESSED AND STEEL GIRDER BRIDGE DECKS. USE GOOD ENGINEERING JUDGEMENT IN DETERMINING THE APPROPRIATE APPLICATION.

DESIGNER NOTES

- 3/4" V-GROOVE. TERMINATE 2'-0" FROM FRONT FACE OF EXPANSION ABUTMENTS, OR FIXED ABUTMENTS ON STEEL BEARINGS.
 - 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM FOR TYPE A1 FIXED AND SEMI-EXPANSION ABUTMENTS.
- V-GROOVES ARE REQUIRED.

NOTES

- 3/4" V-GROOVE. TERMINATE 2'-0" FROM FRONT FACE OF ABUTMENTS.
 - 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM.
- V-GROOVES ARE REQUIRED.

- ☑ FOR OPEN RAILINGS, COAT WITH "PROTECTIVE SURFACE TREATMENT" AS PER THE STANDARD SPECIFICATIONS. PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE TOP AND EXTERIOR EXPOSED FACE OF WINGS, AND THE END 1'-0" OF THE FRONT FACE OF ABUTMENT.


- ☑ COAT WITH "PROTECTIVE SURFACE TREATMENT" AS PER THE STANDARD SPECIFICATIONS.

DECK AND SLAB DETAILS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15



HALF LONGITUDINAL SECTION

NOTES

- TOP TRANSVERSE BARS IN SLAB SHALL BE SUPPORTED BY INDIVIDUAL BAR CHAIRS AT APPROXIMATELY 3'-0" CENTERS EACH WAY. BOTTOM LONGITUDINAL BARS SHALL BE SUPPORTED BY CONTINUOUS BAR CHAIRS AT APPROXIMATELY 4'-0" CENTERS.
- ALL SLAB THICKNESS DIMENSIONS ARE MINIMUM. ANY TOLERANCES NECESSARY TO CORRECT CONSTRUCTION DISCREPANCIES ARE TO BE PLUS (+).
- PARAPETS, SIDEWALKS AND MEDIANS PLACED ON TOP OF THE SLAB SHALL BE POURED AFTER FALSEWORK HAS BEEN RELEASED, EXCEPT FOR STAGED CONSTRUCTION.
- CAMBER SPANS AS SHOWN TO PROVIDE FOR DEAD LOAD DEFLECTION AND FUTURE CREEP. CAMBER DOES NOT INCLUDE ALLOWANCE FOR FORM SETTLEMENT.
- PRIOR TO RELEASING SLAB FALSEWORK, TAKE TOP OF SLAB ELEVATIONS AT THE C.L. OF ABUTMENTS, THE C.L. OF PIERS AND AT 5/10 PTS. TO VERIFY CAMBER. TAKE ELEVATIONS ALONG GUTTER LINES AND CROWN OR C.L.

DESIGNER NOTES


- THE MAXIMUM ALLOWABLE SKEW ANGLE OF STRUCTURE SHALL BE 30°.
- ALL BAR SPLICES TO BE BASED ON "CLASS C" TENSION LAP SPLICE.
- USE OPTIONAL LONGITUDINAL JOINTS WHEN OVERALL SLAB WIDTH IS OVER 52'-0".
- FOR BRIDGES LOCATED IN REMOTE AREAS USE OPTIONAL TRANSVERSE JOINT WHEN POUR EXCEEDS 400 C.Y. PLACE KEVED JOINT NEAR POINT OF DEAD LOAD INFLECTION.
- ALL TRANSVERSE BAR STEEL REINFORCEMENT SHALL BE PLACED ON THE SKEW.
- FLOOR DRAINS ARE TO BE OMITTED FROM SLAB STRUCTURES WHERE POSSIBLE. IF FLOOR DRAINS ARE REQUIRED, PLACE ONLY AT THE 2/10 AND 8/10 PTS. BEND MAIN REBARS PAST DRAINS - DO NOT CUT.

PIER CAP OR WALL TYPE PIERS SHALL BE USED ON MOST STRUCTURES. "COLUMN WITHOUT CAP" TYPE PIERS (SEE STD. 18.01) MAY BE USED WITH THE APPROVAL OF THE STRUCTURES DESIGN SECTION.


ON THE PLANS, PROVIDE CAMBER VALUES AT THE TENTH POINTS OF ALL SPANS. ALSO PROVIDE TOP OF SLAB ELEVATIONS AT THE CENTERLINE (AND/OR CROWN) AND OUTSIDE EDGES OF SLAB AT TENTH POINTS.

▲ PAVING NOTCH IS 1'-0" WIDE BY 1'-4" DEEP IF STRUCTURAL APPROACH SLAB (STD. 12.10) IS USED.


■ REINFORCEMENT IN SLAB MUST MEET TEMPERATURE AND SHRINKAGE REQUIREMENTS.



PIER CAP OR WALL TYPE PIER
SEE STD. 18.01 FOR COLUMN W/O CAP PIER DETAIL.



PLAN OF PIER





OPTIONAL LONGITUDINAL CONSTRUCTION JOINT

TOP TRANSVERSE REINF. FOR RAILINGS/PARAPETS		
SINGLE SLOPE OR SLOPED FACE PARAPETS	MAIN BARS RUN FROM EDGE TO EDGE OF SLAB	SHORT BARS PLACED BETWEEN MAIN BARS AT EDGE OF SLAB
SLAB THICK. ≥ 15"	(#5 @ 1'-0")	(#5 @ 1'-0") 5'-0" LONG NO HOOK REQ'D. AT END
13" ≤ SLAB THICK. < 15"	(#5 @ 10")	(#5 @ 10") 5'-0" LONG STD. HOOK REQ'D. AT END
STEEL RAILINGS TYPE "NY"/"M"/"W"	TOP TRANSVERSE REINF. SPECIFIED IN "LONGIT. SECTION" IS ADEQUATE	

CONTINUOUS FLAT SLAB

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15



SECTION THRU EXTERIOR GIRDER

LEGEND


- ① W6 x 25. SEE STD. 30.1 OR 30.2 FOR RAILING ATTACHMENT. PLACE POSTS NORMAL TO GRADE LINE. PLACE POSTS VERTICAL.
 - ② 1" DIA. STUD WITH NUT & WASHER, FOUR REQ'D. PER POST. A325.*
 - ③ THREADED BAR COUPLER FOR 1" # STUD. ACCEPTABLE PRODUCTS ARE WILLIAMS REBAR FLANGE COUPLERS BY WILLIAMS FORM ENGINEERING CORP. OR DOWEL BAR REPLACEMENTS BY DAYTON SUPERIOR. FOUR REQ'D. PER POST. EXPOSED OPTIONAL FLANGE TO BE GALVANIZED.*
 - ④ ANCHOR BAR 1" DIA. THREADED REINFORCEMENT BAR BENT AS SHOWN IN ANCHOR DETAILS. GRADE 60. TWO REQ'D. PER POST. (TOP)**
 - ⑤ ANCHOR BAR, 1" DIA. THREADED REINFORCEMENT BAR (STRAIGHT), GRADE 60. TWO REQ'D. PER POST. (BOTTOM)**
 - ⑥ 1/4" x 1 3/4" SLOTTED HOLES IN POST FOR STUD NO. 2. LONG DIMENSION OF SLOTTED HOLE TO BE VERTICAL.
- *SHALL BE MECHANICALLY GALVANIZED OR ELECTRO-PLATED.
 **NOT GALVANIZED OR ELECTRO-PLATED.

GENERAL NOTES


FILL BOLT SLOT OPENINGS IN POST SHIMS AND POSTS WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.
 STEEL POST SHIMS MAY BE USED AT POSTS WHERE REQ'D. FOR ALIGNMENT.

THE RAILING ATTACHMENT SHOWN ON THIS STANDARD IS NOT ALLOWED FOR THE TYPE NY OR TYPE M RAILINGS. THE PRESTRESSED BOX SECTIONS SHOULD NOT BE MODIFIED TO FACILITATE USE OF THE TYPE NY OR TYPE M RAILING.

SECTION DEPTH	"D"
12"	7"
17"	12"
21"	16"
27"	22"
33"	28"
42"	37"




SECTION THRU RAILING




ANCHOR DETAILS

ANCHORS MAY BE FABRICATED IN A CAGE IF OPTED BY THE MFG'R.



POST SHIM DETAIL

(14 PER POST)




RAIL POST VERTICAL ADJUSTMENT PLATE
(1 PER POST)

④ SEAL TOP & VERT. EDGES OF SHIMS, VERT. ADJUSTMENT PLATES, AND POST TO GIRDER CONTACT AREAS WITH NON-STAINING GRAY BITUMINOUS JOINT SEALER.

PRESTRESSED SLAB AND BOX GIRDER RAILING POST ATTACHMENT

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva DATE: 1-15




STEEL GIRDER IDEAL POURS - 2 SPANS

② — INDICATES POUR NUMBER AND DIRECTION OF POUR


- S = TOTAL NUMBER OF SPANS
- P = TOTAL NUMBER OF SUPPORTS.
- L = LENGTH OF END SPAN.
- n = $\frac{\text{INTERIOR SPAN}}{\text{END SPAN}}$



STEEL GIRDER IDEAL POURS - 3 SPANS



STEEL GIRDER IDEAL POURS - ANY NUMBER OF SPANS



PLAN VIEW - SHOWING PLACEMENT OF TRANSVERSE CONSTRUCTION JOINTS

NOTES ON PLANS

THE RATE OF PLACING CONCRETE SHALL EQUAL OR EXCEED $\frac{1}{2}$ SPAN LENGTH PER HOUR BUT NEED NOT EXCEED 100 CU. YDS. PER HOUR. (REQUIRED ONLY FOR CONTINUOUS STEEL GIRDERS.)

TWO OR MORE ALTERNATE POURS MAY BE PLACED ON THE SAME DAY. (REQUIRED ONLY WHEN A POURING SEQUENCE IS SHOWN ON PLANS.)

THE CONTRACTOR MAY SUBMIT AN ALTERNATE POURING SEQUENCE SUBJECT TO THE APPROVAL OF THE STRUCTURES DESIGN SECTION. THE CONTRACTOR MAY SUBMIT A POURING SEQUENCE FOR APPROVAL TO THE STRUCTURES DESIGN SECTION IF ONE IS NOT SHOWN ON THE PLANS.

DESIGN NOTES


OPTIONAL TRANSVERSE CONSTRUCTION JOINTS SHALL BE DETAILED ON PLANS TO LIMIT THE VOLUME OF POUR TO < 600 CU. YDS. IN URBAN AREAS AND < 300 CU. YDS. IN OTHER AREAS. GENERALLY FOR STEEL GIRDER SUPERSTRUCTURES LOCATE THE TRANSVERSE JOINTS AT THE 0.6 POINT (CONCRETE IN 60% OF SPAN AND FOR PRESTRESS GIRDER SUPERSTRUCTURES LOCATE JOINTS NEAR THE 0.75 POINT. (CONCRETE IN 75% OF SPAN) CONSIDER CUT-OFF POINTS OF CONTINUITY REINFORCING STEEL WHEN LOCATING JOINTS FOR PRESTRESS GIRDER SUPERSTRUCTURES. LOCATION OF JOINTS IN STEEL GIRDER SUPERSTRUCTURES MAY VARY IF DEFLECTIONS ARE INFLUENCED BY IN SPAN HINGES OR UNUSUAL SPAN LENGTH RATIOS. CHECK WITH THE STRUCTURES DEVELOPMENT SECTION FOR ADDITIONAL INFORMATION.

DETAIL TRANSVERSE CONSTRUCTION JOINTS 5'-0" FROM C. OF IN SPAN HINGES, (ONE ON EACH SIDE OF HINGE) THE CONCRETE BETWEEN THESE JOINTS SHOULD BE THE LAST POUR PLACED.

WHEN THE WIDTH OF SLAB IS GREATER THAN 90 FEET, A LONGITUDINAL CONSTRUCTION JOINT SHALL BE DETAILED. LOCATE LONGITUDINAL CONSTRUCTION JOINT ALONG EDGE OF LANE LINE AND AT LEAST 6 INCHES FROM EDGE OF TOP FLANGE OF GIRDER.


FOR GRADES OVER 3% THE PREFERRED DIRECTION OF POUR IS UPHILL.

AN ALTERNATE POURING SEQUENCE IS TO POUR THE DL POSITIVE MOMENT AREAS AND THEN THE DL NEGATIVE MOMENT AREAS. THE SEQUENCE MAY BE STARTED ANYWHERE ON THE BRIDGE.



SECTION THRU TRANSVERSE OR LONGITUDINAL JOINT

SLAB POURING SEQUENCE	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15



BEARING NOTES

- ALL BEARINGS ARE SYMMETRICAL ABOUT ϕ OF GIRDER AND ϕ OF BEARING.
- ALL MATERIAL IN BEARINGS, BUT EXCLUDING STAINLESS STEEL PLATE, TEFLON SURFACE, PINTLES, ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 50W. STAINLESS STEEL PLATE SHALL CONFORM TO ASTM A240, TYPE 304.
- STEEL PINTLES SHALL CONFORM TO ASTM A449 OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL CONFORM TO ASTM A709 GRADE 36, OR MATERIAL OF EQUIVALENT YIELD STRENGTH AND ELONGATION.
- ALL STRUCTURAL STEEL BEARING PLATES SHALL BE FLAT ROLLED STEEL PLATES WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT, AND VERTICAL.
- ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUTS.
- ALL FINISHED SURFACES SHALL BE MACHINE FINISHED BY AN AUTOMATIC PROCESS.
- ANCHOR BOLTS SHALL BE THREADED 3". PROVIDE ONE STANDARD WROUGHT WASHER AND ONE HEX NUT PER BOLT. PROJECT ANCHOR BOLTS, MASONRY PLATE "D" THICKNESS + 2 $\frac{1}{4}$ " ABOVE TOP OF CONCRETE.
- CHAMFER ANCHOR BOLTS PRIOR TO THREADING.
- MASONRY PLATE "D", ROCKER PLATE "C", ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153, CLASS "C". STEEL PLATE "B" SHALL BE SHOP PAINTED, DO NOT PAINT TEFLON SURFACE.
- ALL MATERIAL IN "STEEL BEARINGS FOR PRESTRESSED CONCRETE GIRDERS", INCLUDING BEARING PADS, SHALL BE PAID FOR AT THE UNIT PRICE BID FOR "BEARING ASSEMBLIES EXPANSION B-1", EACH.
- \ddagger DRILLED HOLES FOR ANCHOR BOLTS IN MASONRY PLATE "D" SHALL HAVE A DIAMETER $\frac{3}{8}$ " LARGER THAN ANCHOR BOLT.
- ▲** TEFLON SURFACE, USE UNFILLED WITH MINIMUM $\frac{1}{16}$ " THICKNESS. PLACE WITH SCRIVE MARKS IN DIRECTION OF MOVEMENT. BOND STEEL PLATE "B" AND TEFLON WITH ADHESIVE MATERIAL MEETING FEDERAL SPECIFICATION MMM-A-134, FEP FILM OR EQUAL.
- PROVIDE A METHOD FOR HANDLING ROCKER PLATE "C" DURING GALVANIZING.
- AT INSTALLATION, ENSURE STAINLESS STEEL SLIDING FACE OF THE UPPER ELEMENT AND THE TFE SLIDING FACE OF THE LOWER ELEMENT HAVE THE SURFACE FINISH SPECIFIED AND ARE CLEAN AND FREE OF ALL DUST, MOISTURE, AND ANY OTHER FOREIGN MATTER.


DESIGNER NOTES

- IF ALL BEARINGS AT A GIVEN SUBSTRUCTURE UNIT ARE FIXED, UTILIZE $\frac{1}{2}$ " THICK ELASTOMERIC BEARING PADS AND FULL-DEPTH CONCRETE DIAPHRAGMS.
- FOR EXPANSION BEARINGS, USE LAMINATED ELASTOMERIC BEARINGS WHENEVER POSSIBLE.
- SEE STANDARD 27.02 AND 19.31 FOR CLEARANCE REQUIREMENTS AND STANDARD 27.02 FOR THE USE OF BEVELED ROCKER PLATE "C" ON GRADES GREATER THAN 3%.
- HEIGHT OF BEARING SHOWN IN "EXPANSION BEARING ASSEMBLY" INCLUDES $\frac{1}{16}$ " BEARING PAD AND $\frac{1}{16}$ " TEFLON SURFACE.
- ▲** ADJUST HEIGHT IF BEVELED ROCKER PLATE "C" IS USED.
- ANCHOR PLATE LENGTH TO BE DESIGNED. MINIMUM LENGTH IS 10"

CALCULATE THE REACTIONS AT THE BEARINGS DUE TO "TOTAL LOADS" AND ALSO "DEAD LOADS" ONLY, USE THE AASHTO LRFD SERVICE I LOAD COMBINATION AND CHECK TO SEE IF THE REACTIONS EXCEED THE BEARING CAPACITIES IN THE TABLE BELOW. CONSIDER ONLY DEAD LOAD (DC + DW) AND HL-93 LIVE LOADS (LL), INCLUDING A 33% DYNAMIC LOAD ALLOWANCE (IM).

IF EITHER REACTION EXCEEDS ITS CORRESPONDING BEARING CAPACITY, THE BEARING DETAILS AS SHOWN ON THIS STANDARD MUST BE MODIFIED TO INCREASE THE BEARING CAPACITY. IF BEARING DETAILS ARE CHANGED AND ANY PLATE HAS A THICKNESS GREATER THAN 2", THEN PROVIDE AN ANSIB FINISH TO TOP AND BOTTOM SURFACE OF THESE PLATES.


GIRDER SIZE	28" & 36"	45"	54" & 70"	36W", 45W", 54W", 72W" & 82W"
TOTAL LOAD (DC+DW+(LL+IM))	180	230	280	330
DEAD LOAD (DC + DW)	110	140	170	200



STEEL BEARINGS FOR PRESTRESSED CONCRETE GIRDERS


STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15




LEGEND
 ○ 5/16" x 3/8" WELDED STUDS
 △ WELD BEAD ON EACH SIDE OF TUBE, GRIND BEADS SO THAT SLEEVE FITS FREELY INSIDE THE 2 1/2" X 2 1/2" TUBE.

RAILING EXPANSION JOINT DETAIL




BASE PLATE



ANCHORAGE DETAIL

5/8" CAST-IN-PLACE ANCHOR BOLTS. MASONRY ANCHORS MAY BE SUBSTITUTED FOR C.I.P. ANCHOR BOLTS. ANCHORAGE PLATE NOT REQUIRED WHEN TYPE S ANCHORS ARE USED.
 MASONRY ANCHOR TYPE S 5/8-INCH. EMBED 7" IN CONCRETE.



SHIM PLATE DETAILS

TWO SHIMS OF EACH SIZE REQUIRED PER POST

NOTES
 POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.

STRUCTURAL TUBING SHALL CONFORM TO ASTM A500, GRADE B. PLATES, ANGLES, BARS AND SHIMS SHALL CONFORM TO ASTM A709, GRADE 36. FENCE FABRIC SHALL CONFORM TO ASTM F668, CLASS 2B.

ANCHORAGES SHALL BE ACCURATELY PLACED TO PROVIDE CORRECT ALIGNMENT OF RAILING. SET POSTS NORMAL TO GRADE.

ALL POST SPACINGS ARE TAKEN HORIZONTAL ALONG CENTERLINE OF RAILING AT BASE OF POST.

STEEL SHIMS SHALL BE PROVIDED & USED UNDER BASE PLATES WHERE REQUIRED FOR ALIGNMENT, AND SHALL BE GALVANIZED.

CAULK AROUND PERIMETER OF BASE PLATES AND FILL PORTION OF SLOTTED HOLES AROUND ANCHOR BOLTS WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.

CUT BOTTOM OF POST TO MAKE VERTICAL IN TRANSVERSE DIRECTION.

ANCHOR BOLTS, NUTS AND WASHERS SHALL BE EITHER STAINLESS STEEL OR ASTM 307. IF 307 IS USED, ANCHOR BOLTS, NUTS, AND WASHERS SHALL BE GALVANIZED.

THE BID ITEM SHALL BE "RAILING TUBULAR SCREENING GALVANIZED B-..." WHICH SHALL INCLUDE ALL ITEMS SHOWN.

RAILING SHALL BE FABRICATED IN LENGTHS THAT INCLUDE NOT MORE THAN 3 POSTS.

VENT HOLES SHALL BE DRILLED IN MEMBERS AS REQUIRED TO FACILITATE GALVANIZING AND DRAINAGE.

ALL RAILING MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING THE STEEL RAILING SHALL BE GIVEN A NO. 6 BLAST CLEANING PER SSPC SPECIFICATIONS. PAINT OVER GALVANIZING WITH AN APPROVED TOP COAT AND TOP COAT AS SPECIFIED IN THE "BRIDGE SPECIAL PROVISIONS". THE RAILING SHALL BE PAINTED FEDERAL COLOR NO. FENCE FABRIC AND TIES TO BE VINYL-COATED, COLOR SHALL BE (SPECIFY: DARK GREEN, BROWN OR BLACK) IN ACCORDANCE WITH ASTM F934.


THE END OF THE FABRIC SHALL BE ATTACHED TO THE POST BY MEANS OF A TENSION BAR THREADED THROUGH THE END LOOPS OF THE FABRIC AND SECURED TO THE POST WITH CLAMPS & BOLT. THE FABRIC SHALL BE STRETCHED TO REMOVE ALL SLACK.

DESIGNER NOTES


TUBULAR SCREENING MAY BE USED ON STRUCTURES WITH A 45 M.P.H. DESIGN SPEED OR LESS, OR WHEN THE SIDEWALK IS SEPARATED FROM THE ROADWAY BY A PARAPET.

THIS RAILING MAY BE MOUNTED DIRECTLY TO A BRIDGE SIDEWALK OR RETAINING WALL PROVIDED THE SIDEWALK IS SEPARATED FROM THE ROADWAY BY A TRAFFIC BARRIER. USE 6" CLEAR SPACING BETWEEN VERTICAL MEMBERS IF CHAIN LINK FENCE IS NOT USED.


FENCE HEIGHT, CURVED OR STRAIGHT, MESH SIZE, COATING AND COLOR SHOULD BE COORDINATED WITH THE REGION. SEE BRIDGE MANUAL 30.3 (8) FOR ADDITIONAL GUIDANCE.




SECTION THRU RAILING




SECTION THRU FENCE SHOWING DETAILS FOR BENT TOP



TOP RAIL CONNECTION FOR FENCE W/ BENT TOP



INSIDE ELEVATION OF RAILING



DETAIL B

SECTION B-B













TUBULAR STEEL RAILING SCREENING

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

WEIGHT = 35 LB/FT (W/O BENT SECTION @ TOP)
 WEIGHT = 45 LB/FT (W/ BENT SECTION @ TOP)

APPROVED: *Bill Oliva*

DATE: 1-15




- LEGEND**
- W6 X 25 WITH 1/8" X 1 1/2" HORIZONTAL SLOTTED HOLES ON EACH SIDE OF POST FOR BOLT NO. 6 AT TOP TWO RAILS, USE 1" DIA. HOLES FOR BOLT NO. 6 AT BOTTOM NO. 5A & FOR BOLT NO. 6A AT NO. 7. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY, PLACE POST VERTICAL, PLACE POSTS NORMAL TO GRADE LINE.
 - PLATE 1 1/2" X 10" X 1'-2" WITH 1/8" X 1 1/2" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3, WELD TO NO. 1 AS SHOWN, SLOTS PARALLEL TO SHORT SIDE OF PLATE.
 - ASTM A449 - 1" DIA. ANCHOR BOLTS WITH HEAVY HEX NUT AND 2" O.D. HARDENED WASHER (ALL GALVANIZED), 4 REQUIRED PER POST, THREAD 3" AND PLACE NORMAL TO PLATE NO. 2, CHAMFER TOP OF BOLTS BEFORE THREADING, USE 1 1/2" LONG BOLT FOR CONCRETE DECKS, ON CONCRETE SLAB SUPERSTRUCTURES, USE 1'-3" LONG BOLT FOR SLAB THICKNESS > 16" AND 1 1/2" LONG FOR THICKNESS < 16", USE 1'-9" LONG IN ABUTMENT WINGS, (AN EQUIVALENT THREADED ROD WITH HEAVY HEX NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQUIRED FOR CONSTRUCTIBILITY.)
 - 3/8" X 10" X 1'-2" ANCHOR PLATE (GALVANIZED) WITH 1/16" DIA. HOLES FOR ANCHOR BOLTS NO. 3.
 - TS 6 X 6 1/2 3/16" STRUCTURAL TUBING, USE 1" DIA. HOLES FOR BOLT NO. 6 (FRONT & BACK) & 7/8" DIA. HOLES FOR BOLT NO. 6A (TOP & BOTTOM).
 - TS 5 X 3 X 1/4" STRUCTURAL TUBING, USE 1" DIA. HOLES FOR BOLT NO. 6 IN TOP RAIL (FRONT & BACK), USE 1/2" X 1 3/8" HORIZONTAL SLOTTED HOLES FOR BOLT NO. 6 IN BOTTOM RAIL (FRONT & BACK) AND A 2" O.D. WASHER UNDER BOLT HEAD.
 - 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH HEX NUT, 3/8" X 1 3/4" X 1 3/4" WASHER, AND SPRING LOCK WASHER (2 REQUIRED AT RAIL TO POST LOCATIONS SHOWN).
 - 7/8" DIA. A325 BOLT WITH HEX NUT AND SPRING LOCK WASHER (1 REQUIRED AT RAIL TO ANGLE AND 2 REQUIRED AT ANGLE TO POST LOCATIONS SHOWN WITH 3/8" X 1 3/4" X 1 3/4" WASHER).
 - L 5 X 5 X 3/8" STRUCTURAL ANGLE, ATTACH TO NO. 1 AND NO. 5 AS SHOWN.
 - TS 5 X 5 X 3/8" X 2'-4" LONG SPLICE TUBE, 1 PER RAIL, USED IN NO. 5.
 - 4/4" X 2/8" X 2'-4" LONG SPLICE BAR, 1 PER RAIL, USED IN NO. 5A.
 - 3/4" DIA. A325 FULLY THREADED BOLTS, 7/2" LONG, WITH 2 WASHERS AND HEAVY HEX NUT ON EACH BOLT, NUT TO BE FINGER TIGHT, (4 REQUIRED PER SPLICE), USE 1" X 4" SLOTTED HOLES IN TOP AND BOTTOM OF NO. 5.
 - 3/4" DIA. A325 FULLY THREADED BOLTS, 4/2" LONG, WITH 2 WASHERS AND HEAVY HEX NUT ON EACH BOLT, NUT TO BE FINGER TIGHT, (4 REQUIRED PER SPLICE), USE 1" X 4" SLOTTED HOLES IN TOP AND BOTTOM OF NO. 5A.
 - SPLICE SLEEVE FABRICATED FROM 1/4" PLATE, PROVIDE "SLD. FIT".
 - ROADWAY OPENING OR 2 1/2" MIN. FOR STRIP SEAL EXP. JOINT & 1/2" OPENING FOR AT ABUTMENT, 1/2" AT FIXED JOINTS, SPLICES ARE REQUIRED IN ANY RAILING SPAN BETWEEN POSTS THAT CONTAINS A SUPERSTRUCTURE EXPANSION JOINT.
 - PROTRUSIONS CAUSED BY WELDING OR GALVANIZING ARE NOT PERMITTED ON THE ADJOINING SURFACES OF THE RAILS, SPLICE TUBES AND FILL PLATES.
 - #6 BARS X 12'-0" LONG, BEND AS SHOWN, TIE TO TOP MAT OF STEEL (DESIGNER TO PLACE THESE BARS IN BILL OF BARS FOR SUPERSTRUCTURE.)

- NOTES**
- BID ITEM SHALL BE "RAILING TUBULAR TYPE NY4 GALVANIZED B-...", WHICH INCLUDES ALL ITEMS SHOWN.
- RAILING SHALL BE CONTINUOUS OVER A MINIMUM OF THREE (3) POSTS WITHOUT SPLICES WHERE POSSIBLE.
- POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT, AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUT.
- ALL MATERIAL SHALL BE GALVANIZED AFTER FABRICATION. PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS, ANGLES, SPLICE TUBES, SPLICE BARS AND STEEL TUBING SHALL BE GIVEN A NO. 6 BLAST CLEANING PER SSPC SPECIFICATIONS.
- WHEN PAINTING IS REQUIRED, ALL MATERIAL EXCEPT ANCHORAGE DETAIL (NO. 3 & NO. 4) SHALL BE PAINTED OVER GALVANIZING WITH AN APPROVED THE COAT AND TOP COAT AS SPECIFIED IN THE "BRIDGE SPECIAL PROVISIONS". THE RAILING SHALL BE PAINTED FEDERAL COLOR NO. 1.
- RAIL POST, BASE PLATES, SPLICE BAR, ANGLES AND SPLICE PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 50. STRUCTURAL TUBING SHALL CONFORM TO THE REQUIREMENTS OF ASTM A500 GRADE B OR C WITH A CERTIFIED 150 KSI ANCHOR PLATES & SHIMS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A709 GRADE 36.
- THE NUT SECURING THE POST BASE PLATE TO THE CONCRETE SHALL BE TIGHTENED TO A SNUG FIT AND GIVEN AN ADDITIONAL 1/8" TURN.
- FILL BOLT SLOT OPENINGS IN POST SHIMS AND PLATE NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER, CAULK AROUND PERIMETER OF NO. 2 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.
- STEEL SHIMS SHALL BE PROVIDED & USED UNDER PLATE NO. 2 WHERE REQUIRED FOR ALIGNMENT, AND SHALL BE GALVANIZED.
- PLACE FIRST BOTTOM LONGITUDINAL REINFORCING BAR CLEAR OF DRIP GROOVE.
- THIS RAILING MEETS NCHRP REPORT 350 EVALUATION CRITERIA FOR TEST LEVEL 4 (TL-4).
- SEE BRIDGE MANUAL 30.2 FOR ALLOWED USE.
- RAILING WEIGHT = 75 LB/LF (BASED ON 8'-0" POST SPACING)


TUBULAR STEEL RAILING TYPE NY4

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: *Bill Oliva* DATE: 1-15



SECTION THRU RAILING ON SIDEWALK



SECTION THRU RAILING ON SIDEWALK

LEGEND

- ① #6 X 25 WITH 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES ON EACH SIDE OF POST FOR BOLT NO. 6 AT TOP TWO RAILS. USE 1" DIA. HOLES FOR BOLT NO. 6 AT BOTTOM NO. 5A & FOR BOLT NO. 6A AT NO. 7. CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POST VERTICAL. PLACE POSTS NORMAL TO GRADE LINE.
- ② PLATE 1 1/2" X 10" X 1/2" WITH 1/8" X 1 1/8" SLOTTED HOLES FOR ANCHOR BOLTS NO. 3. WELD TO NO. 1 AS SHOWN. SLOTS PARALLEL TO SHORT SIDE OF PLATE.
- ③ ASTM A449 - 1" DIA. ANCHOR BOLTS WITH HEAVY HEX NUT AND 2" O.D. HARDENED WASHER (ALL GALVANIZED). 4 REQUIRED PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 2. CHAMFER TOP OF BOLTS BEFORE THREADING. USE 1 1/2" LONG BOLT FOR CONCRETE SIDEWALKS ≥ 11'-0" WIDE AND SEE TABLE TO THE LEFT FOR CONCRETE SIDEWALKS ≥ 6'-0" AND < 11'-0" WIDE FOR PROPER BOLT LENGTHS. USE 1'-9" LONG IN ABUTMENT WINGS. (AN EQUIVALENT THREADED ROD WITH HEAVY HEX NUTS AND HARDENED WASHERS MAY BE SUBSTITUTED FOR ANCHOR BOLTS IN WINGS IF REQUIRED FOR CONSTRUCTABILITY.)
- ④ 3/8" X 10" X 1'-2" ANCHOR PLATE (GALVANIZED) WITH 1/8" DIA. HOLES FOR ANCHOR BOLTS NO. 3.
- ⑤ TS 6 X 6 X 3/8" STRUCTURAL TUBING. USE 1" DIA. HOLES FOR BOLT NO. 6 (FRONT & BACK) & 3/8" DIA. HOLES FOR BOLT NO. 6A (TOP & BOTTOM).
- ⑥A TS 5 X 3 X 1/4" STRUCTURAL TUBING. USE 1" DIA. HOLES FOR BOLT NO. 6 IN TOP RAIL (FRONT & BACK). USE 1/8" X 1 3/8" HORIZONTAL SLOTTED HOLES FOR BOLT NO. 6 IN BOTTOM RAIL (FRONT & BACK) AND A 2" O.D. WASHER UNDER BOLT HEAD.
- ⑥ 7/8" DIA. A325 SLOTTED ROUND HEAD BOLT WITH HEX NUT, 3/8" X 1 3/4" X 1 3/4" WASHER, AND SPRING LOCK WASHER (2 REQUIRED AT RAIL TO POST LOCATIONS SHOWN).
- ⑥A 3/4" DIA. A325 BOLT WITH HEX NUT AND SPRING LOCK WASHER (1 REQUIRED AT RAIL TO ANGLE AND 2 REQUIRED AT ANGLE TO POST LOCATIONS SHOWN WITH 3/8" X 1 3/4" X 1 3/4" WASHER).
- ⑦ L 5 X 5 X 5/8" STRUCTURAL ANGLE. ATTACH TO NO. 1 AND NO. 5 AS SHOWN.
- ⑧ *6 BARS X 12'-0" LONG. BEND AS SHOWN. TIE TO TOP MAT OF STEEL. (DESIGNER TO PLACE THESE BARS IN BILL OF BARS FOR SUPERSTRUCTURE.)


FOR ALL TUBULAR STEEL RAILING TYPE NY4 DETAILS SEE STD. 30.27.

SIDEWALK DETAILS FOR TUBULAR STEEL RAILING TYPE NY4

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
1-15



PLAN
LOOKING UP STATION

*GIVE WING ANGLES ON PLANS IN INCREMENTS OF 5°. SEE BRIDGE MANUAL.



SECTION C1

DESIGN DATA

LIVE LOAD:
 DESIGN LOADING: HL-93
 INVENTORY RATING FACTOR: RF=LOS
 OPERATING RATING FACTOR: RF=L35
 WISCONSIN STANDARD PERMIT VEHICLE (WIS.-SPV): 255 (KIPS)

**** EARTH LOAD:** DESIGNED FOR FILL HEIGHT RANGE OF ___ TO ___ FEET

MATERIAL PROPERTIES:
 CONCRETE MASONRY ————— $f'c = 3.5$ K.S.I.
 BAR STEEL REINFORCEMENT ————— $f_y = 60.0$ K.S.I.

BOX CULVERT LAYOUT





STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15

**SEE SECTION 36.5 FOR DESIGN RANGE OF FILL HEIGHTS.
 HEIGHT TO BE TO THE NEAREST 0.5 FEET ON FILLS UNDER 4 FEET AND TO THE NEAREST FOOT ON FILLS OVER 4 FEET.

□ 18" MIN. WIDTH RUBBERIZED MEMBRANE WATERPROOFING UP WALLS & ACROSS TOP SLAB



FABRICATOR MAY MAKE TRUSSES ANY LENGTH KEEPING A SECTION A MINIMUM OF 20'-0" & A MULTIPLE OF 5'-0". CHORD FIELD SPLICES SHALL BE MADE WITH COUPLINGS. CHORD SHOP SPLICE SHALL BE THE WELDED SPLICE SHOWN ABOVE.





GENERAL NOTES

- DRAWINGS SHALL NOT BE SCALED.
- STEEL COLUMN AND CHORD PIPE SHALL BE APISPEC. 5L GRADE X42 Fy = 42,000 PSI**
- PLATES, BARS, & STRUCTURAL ANGLES SHALL BE ASTM A709 GRADE 36 Fy = 36,000 PSI
- ALL STRUCTURAL STEEL MEMBERS SHALL BE GALVANIZED.
- ALL BOLTED CONNECTIONS SHALL BE MADE WITH 3/4" A325 BOLTS, GALVANIZED ASTM A53, CLASS C, AND MADE WITH DTI WASHERS.
- WELDED CONNECTIONS CAN BE USED IN LIEU OF BOLTED CONNECTIONS, IF UNIT CAN BE GALVANIZED IN ONE PIECE.
- STEEL ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM F1554 GRADE 55, Fy = 55,000 PSI
- THE UPPER 12" OF ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH THE AASHTO SPECIFICATION AS STATED IN SECTION 64L OF THE WISDOT STANDARD SPECIFICATIONS.
- WELD TEST AS PER AWS D11.
- ** ALTERNATE MATERIAL FOR COLUMN AND CHORD LESS THAN 10" DIAMETER MAY BE ASTM A500 GRADE B Fy = 42,000 PSI, GRADE C Fy = 46,000 PSI, OR ASTM A53 GRADE B Fy = 35,000 PSI.

DESIGN DATA

DEAD LOAD - 3 PSF OF SIGN, WT. OF SUPPORTING STRUCTURE, CATWALK, LIGHTS AND RAILINGS.
 ICE LOAD - 3 PSF TO 1FACE OF SIGN & AROUND SURFACE OF MEMBERS.
 WIND PRESSURE - 90 MPH (3-SECOND GUST SPEED) TO SIGN AREA & EXPOSED MEMBERS.
 DESIGNED ACCORDING TO THE LATEST EDITION OF AASHTO "STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND TRAFFIC SIGNALS."

STRUCTURE	DESIGN SIGN AREA	MAX. SIGN DEPTH



STANDARDS 39.03, 39.09, AND 39.13 DETAILS ARE USED WITH THIS STANDARD TO DETAIL A "4-CHORD GALVANIZED STEEL SIGN BRIDGE" FOR TYPE I AND II SIGNS ONLY.

DIMENSIONS, MEMBER SIZES, CAMBER & ELEVATIONS


STRUCTURE	"A"	"B"	"C"	CHORDS O.D. X THK.	TOP & BOTTOM WEB	FRONT & REAR WEB	COUPLING PLATE "D1" & "T"	COUPLING BOLT CIRCLE DIA. "D2"	NO. OF BOLTS IN COUPLING	CAMBER	STEEL COLUMN O.D. X THK.	TOWER WEBS	"L"	ELEV "P"	ELEV "R"	ELEV "T"

TABLE ENTRIES TO BE DESIGNED

4-CHORD GALVANIZED STEEL SIGN BRIDGE

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15




ALTERNATE ANCHOR PLATE/TOP TEMPLATE

PLAN VIEW

ANCHOR PLATE/TOP TEMPLATE


PLAN VIEW

CAP FABRICATED FROM STEEL PLATES (MIN. THICKNESS = 3/16") WILL BE ACCEPTABLE, SUBJECT TO APPROVAL BY THE ENGINEER.




TOWER CAP DETAIL

HOLE FOR 3/4" ϕ BOLT (ASTM A325) TYP.



TYPICAL TRUSS CONNECTION DETAILS




TYPICAL WELDED ALTERNATE

WEB MEMBERS & BOXED ENDS

ANGLE SIZE	*WELD LENGTH	NO. OF BOLTS
2 1/2" x 2 1/2" x 1/4"	11"	3
3" x 3" x 3/16"	10"	3
3" x 3" x 1/4"	13"	4
3" x 3" x 3/16"	16 1/2"	5
3" x 3" x 3/8"	19 1/2"	6
4" x 4" x 1/4"	18"	5
4" x 4" x 3/16"	22"	6
4" x 4" x 3/8"	26"	8
4" x 4" x 1/2"	30"	9
4" x 4" x 1/2"	34"	10


● ONLY USED FOR BOXED ENDS AND TRANSVERSE WEBS.



PLAN VIEW (BASE PLATE)

3/4" ϕ BOLT MAY BE ASTM A449. SNUG-TIGHT ONLY, DO NOT OVER TIGHTEN.

OVERSIZED, OR PLATE WASHER. (TYP.)



TOWER CONNECTION DETAIL


⊖ BOLT PLATE DETAILS SHOWN ARE MIN.

BASE PLATE, ANCHOR BOLTS & COLUMN STIFFENER DETAILS

STRUCTURE	STEEL COLUMN O.D. X THK.	ANCHOR BOLT		BASE PLATE THICKNESS (IN.)	STIFFENER PLATE THICKNESS (IN.)	STIFFENER PLATE HEIGHT (IN.)	t _w (IN.)
		SIZE	L _e				


TABLE ENTRIES TO BE DESIGNED

NOTE: PRIOR TO INSTALLATION, ANCHOR BOLTS SHALL BE RIGIDLY HELD IN POSITION DURING CONCRETE PLACEMENT USING STEEL ANCHOR PLATE AND TOP TEMPLATE. REMOVE TOP TEMPLATE (NOT SHOWN) AFTER CONCRETE SETS.



SECTION A-A

L_e FOR 1/4" ANCHOR BOLTS
L_e FOR 1/2" ANCHOR BOLTS
L_e FOR 3/4" ANCHOR BOLTS




COUPLING DETAIL

4-CHORD SIGN BRIDGE DETAILS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 1-15



GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

STEEL COLUMN AND CHORD PIPE SHALL BE APISPEC. 5L GRADE X42 Fy = 42,000 PSI **

PLATES, BARS, & STRUCTURAL ANGLES SHALL BE ASTM A709 GRADE 36 Fy = 36,000 PSI

ALL STRUCTURAL STEEL MEMBERS SHALL BE GALVANIZED.

ALL BOLTED CONNECTIONS SHALL BE MADE WITH 3/4" ϕ A325 BOLTS, GALVANIZED ASTM A153, CLASS C, AND MADE WITH DTI WASHERS.

WELDED CONNECTIONS CAN BE USED IN LIEU OF BOLTED CONNECTIONS, IF UNIT CAN BE GALVANIZED IN ONE PIECE.

STEEL ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM F1554 GRADE 55, Fy = 55,000 PSI

THE UPPER 12" OF ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH THE AASHTO SPECIFICATION AS STATED IN SECTION 64L OF THE WISDOT STANDARD SPECIFICATIONS.

WELD TEST AS PER AWS D11.

PREFABRICATE CAMBER INTO THE HORIZONTAL SUPPORT PROVIDING AN AMOUNT "Y" AT END OF TRUSS SHOWN IN "CAMBER DIAGRAM". DO NOT MAKE VERTICAL UPRIGHT BY ADJUSTMENT OF LEVELING NUTS.

** ALTERNATE MATERIAL FOR CHORD LESS THAN 10" DIAMETER MAY BE ASTM A500 GRADE B Fy = 42,000 PSI, GRADE C Fy = 46,000 PSI, OR ASTM A53 GRADE B Fy = 35,000 PSI.

DESIGN DATA

DEAD LOAD - 3 PSF OF SIGN, WT. OF SUPPORTING STRUCTURE, CATWALK, LIGHTS AND RAILINGS.

ICE LOAD - 3 PSF TO 1FACE OF SIGN & AROUND SURFACE OF MEMBERS.

WIND PRESSURE - 90 MPH (3-SECOND GUST SPEED) TO SIGN AREA & EXPOSED MEMBERS.

FATIGUE CATEGORY 1 WITHOUT GALLOPING.

DESIGNED ACCORDING TO THE LATEST EDITION OF AASHTO "STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES, AND TRAFFIC SIGNALS."

STRUCTURE	DESIGN SIGN AREA	MAX. SIGN DEPTH

DIMENSIONS, CAMBER & ELEVATIONS

TABLE ENTRIES TO BE DESIGNED

STRUCTURE	"A"	"L"	"B"	"D"	"Y"	ELEV "R"	ELEV "T"






DESIGNER NOTES

		CAMBER VALUES				
		"Y" (IN.)				
"L"	"A"	32	30	28	26	24
30	4 1/4	3 1/2	2 3/4	2 3/8	2 1/4	1 3/4
28	3 3/4	3 1/4	2 3/4	2 1/4	1 3/4	1 1/4
26	3 3/8	3	2 1/2	2 1/8	1 3/4	1 1/4
24	3 3/8	2 7/8	2 3/8	2	1 3/4	1 1/4
22	3 3/8	2 5/8	2 1/4	1 7/8	1 3/4	1 1/4

"A" & "L" IN FT.

INTERPOLATE FOR VALUES NOT SHOWN

TABLES REFLECT CATWALK LOADING. FOR CAMBER VALUES WITHOUT CATWALK LOADING, MULTIPLY TABLE VALUES ABOVE AS FOLLOWS: MULTIPLY "Y" BY .72




STANDARDS 39.9, 39.11, 39.12 AND 39.13 DETAILS ARE USED WITH THIS STANDARD TO DETAIL A "GALVANIZED STEEL CANTILEVER SIGN TRUSS" FOR TYPE I AND II SIGNS ONLY.

GALVANIZED STEEL CANTILEVER SIGN TRUSS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15


TOP DIAGONAL
L 3" X 3" X 1/4"

* ANGLE
L 2 1/2" X 2 1/2" X 1/4"
L 3" X 3" X 1/4"


WELD LENGTH (MIN.)
7"
8"



SECTION B-B



SECTION H-H




SECTION G-G


(LOOKING DOWN @ BOT. HORIZ. PLANE @ FRONT CHORD)

BOLTED OR OPTIONAL WELDED CONNECTION


BOLTED CONNECTION




PLAN TRUSS TO UPRIGHT





ELEVATION TRUSS TO UPRIGHT



END VIEW TRUSS TO UPRIGHT



BASE PLATE DETAILS










DETAIL 'A'

GALVANIZED STEEL CANTILEVER SIGN TRUSS DETAILS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15






NOTE:
THE FIRST OR FIRST TWO DIGITS OF A
BAR MARK SIGNIFIES THE BAR SIZE.

BILL OF BARS

980 LB

BAR MARK	COAT	NO. REQ'D	LENGTH	SEVY	CUT. DIA.	BUN-DLE	LOCATION
A701	X	12	15'-6"				FOOTING - COLUMN/TOP
A402	X	16	10'-6"	X			FOOTING - COLUMN/TOP
A703	X	12	15'-0"				FOOTING - WINGS
A404	X	12	7'-6"	X			FOOTING - WINGS
A405	X	10	7'-11"	X			FOOTING - TOP
A406	X	4	3'-6"				FOOTING - TOP - COLUMNS



GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.
BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 3" CLEAR UNLESS DETAILED OTHERWISE.

ALLOWABLE DESIGN STRESSES

CONCRETE MASONRY $f'_c=3,500$ PSI
HIGH STRENGTH BAR STEEL REINFORCEMENT, $f_y=60,000$ PSI
ANCHOR BOLTS ASTM F1554 GRADE 60 $f_y=55,000$ PSI


FOUNDATION DATA

ALLOWABLE SOIL BEARING PRESSURE = 2T/5F

TOTAL ESTIMATED QUANTITIES (1 FTG.)

SIGN SUPPORTS CONCRETE MASONRY 8 CY
SIGN SUPPORTS STEEL REINFORCEMENT HS 980 LB

CANTILEVER TRUSS FOOTING	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15




SECTION O-O

HANDHOLE DETAILS

HANDHOLE NOTES


HANDHOLES SHALL BE LOCATED IN ONE COLUMN OF THE SIGN BRIDGE STRUCTURE IF ELECTRICALLY OPERATED DEVICES ARE INSTALLED ON/IN THE STRUCTURE. COLUMNS WITH HANDHOLES SHALL BE NEAR THE ELECTRICAL SERVICE. THE CONTRACTOR SHALL VERIFY THE LOCATION OF THE ELECTRICAL SERVICE ENTRANCE WITH THE REGION TRAFFIC SECTION PRIOR TO FABRICATION OF THE SIGN BRIDGE COLUMNS AND MEMBERS. CONDUIT (AS REQ'D) SHALL BE LOCATED, PLACED AND SIZED AS SHOWN ON THE ELECTRICAL PLAN DETAIL SHEETS.

* COLUMN SIZE O.D. X THK.	HANDHOLE PIPE O.D. X MIN. THK.
UP TO AND INCLUDING 16" X .375"	5.562" X .500"
GREATER THAN 16" X .375" TO AND INCLUDING 24" X .562"	6.625" X .562"




TYPICAL "J" HOOK LOCATION

THE "J" HOOK SHALL BE FACTORY WELDED TO THE INSIDE OF ALL COLUMNS CONTAINING ELECTRICAL WIRING. THE "J" HOOK SHALL BE ATTACHED ABOVE THE CENTERLINE OF THE UPPER HANDHOLE AND MOUNTED DIRECTLY OPPOSITE THE HANDHOLE AS SHOWN IN THE DRAWING.



GROUNDING LUG DETAIL


NUT, BOLT AND WASHERS SHALL BE STAINLESS STEEL.



RODENT SCREEN
(ONLY REQ'D WHEN ELECTRICAL DEVICES ARE INSTALLED)

HANDHOLE DETAILS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15

- ☐ "CLEANING PARAPETS" LIMITS
- ⚠ "PIGMENTED SURFACE SEALER" LIMITS
- Ⓞ "PROTECTIVE SURFACE TREATMENT" LIMITS




PARAPET REPAIR DETAIL

502.3200	PROTECTIVE SURFACE TREATMENT	SY
502.3210	PIGMENTED SURFACE SEALER	SY
509.1500	CONCRETE SURFACE REPAIR	SF
509.9050,5	CLEANING PARAPETS	LF


DESIGNER NOTES

DETAILS MAY BE SHOWN ON PLANS IF NECESSARY FOR CLARITY.
INCLUDE APPLICABLE CONCRETE MASONRY BID ITEM TO FILL REPAIRS.



CURB REPAIR DETAIL

502.3200	PROTECTIVE SURFACE TREATMENT	SY
509.1200	CURB REPAIR	LF



★ MASONRY ANCHORS TYPE S X-INCH. EMBED X" IN CONCRETE

ANCHOR DETAIL (EXAMPLE)

502.50..	MASONRY ANCHORS TYPE L NO. X BARS	EACH
502.61..	MASONRY ANCHORS TYPE S X-INCH	EACH
505.0605	BAR STEEL REINFORCEMENT HS COATED BRIDGES	LB


DESIGNER NOTES

FOR DESIGNER INFORMATION ONLY, THE DESIGN ENGINEER SHALL PROVIDE ANCHOR DETAILS AS NEEDED. PLANS SHALL INCLUDE ANCHOR "TYPICAL NOTES" WHEN MASONRY ANCHORS ARE USED.

ANCHOR DETAIL EXAMPLE APPLICABLE FOR ADHESIVE "TYPE S" ANCHORS LOCATED IN UNCRACKED CONCRETE. SEE CHAPTER 40.16 FOR ADDITIONAL GUIDANCE.

TYPICAL NOTES:


- MECHANICAL "TYPE S" MASONRY ANCHORS TYPE S X/X-INCH. MIN. PULLOUT CAPACITY OF XX KIPS. EMBED XX" IN CONCRETE.
- ADHESIVE "TYPE S" MASONRY ANCHORS TYPE S X/X-INCH. EMBED XX" IN CONCRETE. ANCHORS SHALL BE APPROVED FOR USE IN CRACKED CONCRETE.
- ADHESIVE "TYPE L" MASONRY ANCHORS TYPE L NO. X BARS. EMBED XX" IN CONCRETE. ANCHORS SHALL BE APPROVED FOR USE IN CRACKED CONCRETE.



DECK REPAIR DETAIL - PLAN


FOR DESIGNER INFORMATION ONLY (DO NOT PLACE ON PLANS)

509.0301	PREPARATION DECKS TYPE 1	SY
509.0302	PREPARATION DECKS TYPE 2	SY
509.2000	FULL-DEPTH DECK REPAIR	SY
▲509.2500	CONCRETE MASONRY OVERLAY DECKS	CY
*SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF



DECK REPAIR DETAIL - SECTION

FOR DESIGNER INFORMATION ONLY (DO NOT PLACE ON PLANS)



FULL-DEPTH DECK REPAIR DETAIL

FOR DESIGNER INFORMATION ONLY (DO NOT PLACE ON PLANS)

509.2000	FULL-DEPTH DECK REPAIR	SY
▲509.2500	CONCRETE MASONRY OVERLAY DECKS	CY
*SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF

DESIGNER NOTES


- DETAILS APPLICABLE TO ALL OVERLAY METHODS AND DECK REPAIRS WITHOUT OVERLAYS.
- * "SAWING PAVEMENT DECK PREPARATION AREAS" NOT REQUIRED FOR CONCRETE OVERLAYS.
- ▲ USE "CONCRETE MASONRY DECK PATCHING" (SPV.0035) FOR DECK REPAIRS UNDER POLYMER, ASPHALTIC, OR POLYMER MOD. ASPHALTIC OVERLAYS. USE "CONCRETE MASONRY DECK PATCHING" FOR DECK REPAIRS WITHOUT OVERLAYS.
- RESTRICTIONS ON REMOVAL ITEMS SHALL BE PLACED ON THE PLANS TO PREVENT DAMAGE TO REINFORCING STEEL.

CONCRETE REPAIR DETAILS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva


DATE:
1-15



**TYPICAL INSTALLATION AT
BAR STEEL INTERSECTION**




**TYPICAL INSTALLATION
FOR BAR STEEL**



PLACE GALVANIC ANODES AT INTERIOR OF REPAIR WHEN REINFORCING STEEL IS IN CONTACT WITH THE EXISTING CONCRETE AT THE BOTTOM OF THE REPAIR

NOTE:
EXISTING REINFORCING STEEL TO BE COMPLETELY CLEANED OF CORRODED MATERIAL PRIOR TO INSTALLATION OF GALVANIC ANODES.



PART. PLAN TYPICAL REPAIR DETAIL

509.1500 CONCRETE SURFACE REPAIR SF
SPV.0060 EMBEDDED GALVANIC ANODES EACH

DESIGNER NOTES

CATHODIC PROTECTION SHALL BE USED ONLY AT THE REQUEST OF THE REGIONAL BRIDGE MAINTENANCE ENGINEER.
INCLUDE APPLICABLE CONCRETE MASONRY BID ITEM TO FILL REPAIRS.

NOTES

SEE SPECIAL PROVISION "EMBEDDED GALVANIC ANODES" FOR DESCRIPTION, MATERIALS, CONSTRUCTION, MEASUREMENT, AND PAYMENT INFORMATION.

ANODES NEAREST TO EDGE OF REPAIR TO BE WITHIN 6" OF EDGE.


AFTER PLACEMENT, GALVANIC ANODES SHOULD MAINTAIN A MINIMUM TOP COVER OF 1/2" AND A MINIMUM BOTTOM COVER OF 3/4".

CATHODIC PROTECTION


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva


DATE:
1-15



RUPTURED VOID REPAIR



SECTION THRU PARAPET ON WING




SECTION AT END OF SLAB

509.0301	PREPARATION DECKS TYPE 1	SY
509.0302	PREPARATION DECKS TYPE 2	SY
509.2000	FULL-DEPTH DECK REPAIR	SY
▲509.2500	CONCRETE MASONRY OVERLAY DECKS	CY
*SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF

DESIGNER NOTES

- * "SAWING PAVEMENT DECK PREPARATION AREAS" NOT REQUIRED FOR CONCRETE OVERLAYS.
- ▲ USE "CONCRETE MASONRY DECK PATCHING" (SPV.0035) FOR DECK REPAIRS UNDER POLYMER, ASPHALTIC, OR POLYMER MOD. ASPHALTIC OVERLAYS. USE "CONCRETE MASONRY DECK PATCHING" FOR DECK REPAIRS WITHOUT OVERLAYS.




SECTION THRU RAILING


ATTACHING PARAPETS OR RAILINGS TO BRIDGE DECKS WITH EPOXY ANCHORS IS NOT ALLOWED BY FHWA.

OVERLAY DETAILS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 1-15


☆ MIN. LAP, TOP. ⊗ LAP TO EXIST. TRANS. BARS.
 □ MIN. LAP, BOT.



CROSS SECT. THRU RDWY.




DIAPHRAGM CONNECTION TO EXISTING STEEL GIRDER




PLAN

SLAB WIDENING	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 1-15



CROSS SECTION THRU ROADWAY
LOOKING NORTH



† SURVEY TYPE:
SURVEY COMPLETED DATE: ___/___/___

PLAN
TOP OF DECK SHOWN

DESIGNER NOTES

- PLAN VIEW APPLICABLE TO ALL OVERLAY METHODS AND DECK REPAIRS WITHOUT OVERLAYS.
- FOR CROSS SECTIONS NOT IN SUPERELEVATION TRANSITIONS, THE PREFERRED MINIMUM SLOPE IS 2%.
- PROVIDE AN AVERAGE OVERLAY THICKNESS ON THE PLANS, THE AVERAGE OVERLAY THICKNESS IS THE THE MINIMUM OVERLAY THICKNESS PLUS 1/2" TO ACCOUNT FOR VARIATIONS IN THE DECK SURFACE. CHANGES IN CROSS-SLOPE INCREASE THE AVERAGE OVERLAY THICKNESS. QUANTITIES ARE BASED ON THE AVERAGE OVERLAY THICKNESS.
- DO NOT PROVIDE A PROFILE GRADE LINE ON THE PLANS.
- * REMOVAL OF 1" OF EXISTING DECK UNDER BID ITEM "CLEANING DECKS" IS NOT INTENDED FOR PREVIOUSLY OVERLAID DECKS. EXISTING CONCRETE COVER (1" MIN.) SHALL BE MAINTAINED AND CONSIDERED WHEN DETERMINING CONCRETE REMOVALS. DO NOT INCLUDE BID ITEM "CLEANING DECKS" WHEN REMOVING EXISTING OVERLAY.
- † PROVIDE (IF AVAILABLE) DECK CONDITION ASSESSMENT SURVEY ON PLANS, INCLUDE SURVEY TYPE AND DATE COMPLETED.
- JOINT REPAIR AREAS SHOULD NOT BE INCLUDED IN DECK REPAIR AREAS OR OVERLAY QUANTITIES. SEE STANDARD 40.04.
- INCLUDE THE BID ITEM "ADJUSTING FLOOR DRAINS" WHEN DRAINS ARE TO BE RAISED.
- RESTRICTIONS ON REMOVAL ITEMS SHALL BE PLACED ON THE PLANS TO PREVENT DAMAGE TO REINFORCING STEEL.

DESIGN DATA

LIVE LOAD:
INVENTORY RATING: HS-
OPERATING RATING: HS-
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... KIPS

MATERIAL PROPERTIES:
CONCRETE MASONRY OVERLAY DECKS $f_c = 4,000$ P.S.I.

NOTES

- DRAWINGS SHALL NOT BE SCALED.
- DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.
- PROTECTIVE SURFACE TREATMENT SHALL BE APPLIED TO THE ENTIRE TOP SURFACE OF THE NEW CONCRETE OVERLAY.
- A MINIMUM OF 1-INCH OF CONCRETE SHALL BE REMOVED FROM THE ENTIRE BRIDGE DECK UNDER THE BID ITEM "CLEANING DECKS".
- PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2, AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION AND FULL-DEPTH DECK REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY OVERLAY DECKS".
- ANY EXCAVATION REQUIRED TO COMPLETE THE OVERLAY OR JOINT REPAIRS AT THE ABUTMENTS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "CONCRETE MASONRY OVERLAY DECKS".
- PROFILE GRADE LINE SHALL BE DETERMINED IN THE FIELD BASED ON A MINIMUM OVERLAY THICKNESS OF 1/2" PLACED ABOVE THE DECK SURFACE AFTER SURFACE PREPARATION. EXPECTED AVERAGE OVERLAY THICKNESS IS 2" (OR AS GIVEN ON THE PLANS). IF EXPECTED AVERAGE OVERLAY THICKNESS IS EXCEEDED BY MORE THAN 1/2", CONTACT THE STRUCTURES DESIGN SECTION.
- DRAINS REMOVED OR CLOSED IS INCIDENTAL TO THE BID ITEM "CONCRETE MASONRY OVERLAY DECKS".

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
502.3200	PROTECTIVE SURFACE TREATMENT	SY	
509.0301	PREPARATION DECKS TYPE 1	SY	
509.0302	PREPARATION DECKS TYPE 2	SY	
509.0500	CLEANING DECKS	SY	
509.2000	FULL-DEPTH DECK REPAIR	SY	
509.2500	CONCRETE MASONRY OVERLAY DECKS	CY	
POSSIBLE ADDITIONAL BID ITEMS			
* 509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY	SY	
514.0900	ADJUSTING FLOOR DRAINS	EACH	


THIS IS A PARTIAL LIST OF POSSIBLE BID ITEMS. BID ITEMS MAY NEED TO BE ADDED OR REMOVED TO FIT EACH INDIVIDUAL CASE.

CONCRETE OVERLAY

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15



CROSS SECTION THRU ROADWAY
LOOKING NORTH

DESIGNER NOTES

REPAIRS USING CONCRETE REQUIRE A MINIMUM CURE TIME OF 28 DAYS BEFORE PLACING OVERLAY. ALTERNATIVES TO CONCRETE DECK PATCHES MAY BE USED TO SHORTEN TIME REQUIRED FOR PLACING OVERLAY.
DO NOT PROVIDE A PROFILE GRADE LINE ON THE PLANS.

DESIGN DATA

LIVE LOAD:
INVENTORY RATING: HS-...
OPERATING RATING: HS-...
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... KIPS

MATERIAL PROPERTIES:
CONCRETE MASONRY - DECK PATCHING f'c = 4,000 P.S.I.

NOTES


DRAWINGS SHALL NOT BE SCALED.
DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.
DECK SURFACE PREPARATION IS INCLUDED IN THE BID ITEM "POLYMER OVERLAY".
AREAS OF "PREPARATION DECKS TYPE 1" SHALL BE DEFINED BY A SAW CUT.
PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2, AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION AND FULL-DEPTH DECK REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY DECK PATCHING".

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
509.0301	PREPARATION DECKS TYPE 1	SY	
509.0302	PREPARATION DECKS TYPE 2	SY	
509.2000	FULL-DEPTH DECK REPAIR	SY	
509.5100.S	POLYMER OVERLAY	SY	
SPV.0035	CONCRETE MASONRY DECK PATCHING	CY	
SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF	

THIS IS A PARTIAL LIST OF POSSIBLE BID ITEMS. BID ITEMS MAY NEED TO BE ADDED OR REMOVED TO FIT EACH INDIVIDUAL CASE.

REHABILITATION OVERLAY



CROSS SECTION THRU ROADWAY
LOOKING NORTH

DESIGNER NOTES

PREVENTATIVE OVERLAY INTENDED FOR USE ON DECKS WITH A MINIMUM AGE OF 28 DAYS AND A SERVICE LIFE LESS THAN 2 YEARS. AN ADDITIONAL CONTRACT MAY BE REQUIRED FOR APPLYING THE OVERLAY DUE TO SCHEDULE AND DECK AGE CONSIDERATIONS.
WHEN BID ITEM "POLYMER OVERLAY" IS USED RATING SHOULD INCLUDE THE 5 PSF OVERLAY.

DESIGN DATA

LIVE LOAD:
DESIGN LOADING: HL-93
INVENTORY RATING FACTOR: RF=1...
OPERATING RATING FACTOR: RF=1...
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... KIPS

STRUCTURE IS DESIGNED FOR A FUTURE WEARING SURFACE OF 20 POUNDS PER SQUARE FOOT.

NOTES

DRAWINGS SHALL NOT BE SCALED.
DECK SURFACE PREPARATION IS INCLUDED IN THE BID ITEM "POLYMER OVERLAY".

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
509.5100.S	POLYMER OVERLAY	SY	


PREVENTATIVE OVERLAY

POLYMER OVERLAY

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15



CROSS SECTION THRU ROADWAY

LOOKING NORTH

DESIGNER NOTES

CONCRETE OVERLAYS ARE THE CURRENT PREFERRED METHOD TO OVERLAY A BRIDGE.

REPAIRED AREAS REQUIRE A MINIMUM CURE TIME OF 7 DAYS BEFORE PLACING OVERLAY. ALTERNATIVES TO CONCRETE DECK PATCHES MAY BE USED TO SHORTEN TIME REQUIRED FOR PLACING OVERLAY.

PROVIDE AN AVERAGE OVERLAY THICKNESS ON THE PLANS. THE AVERAGE OVERLAY THICKNESS IS THE MINIMUM OVERLAY THICKNESS PLUS 1/2" TO ACCOUNT FOR VARIATIONS IN THE DECK SURFACE. CHANGES IN CROSS-SLOPE INCREASE THE AVERAGE OVERLAY THICKNESS. QUANTITIES ARE BASED ON THE AVERAGE OVERLAY THICKNESS.

DO NOT PROVIDE A PROFILE GRADE LINE ON THE PLANS.

OVERLAYS NOT REQUIRING SHEET MEMBRANE WATERPROOFING ARE PREFERRED.

DESIGNER TO CONTACT THE REGIONAL BRIDGE MAINTENANCE ENGINEER TO DETERMINE IF POLYMER MODIFIED ASPHALTIC MATERIAL IS AVAILABLE.

RESTRICTIONS ON REMOVAL ITEMS SHALL BE PLACED ON THE PLANS TO PREVENT DAMAGE TO REINFORCING STEEL.

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
509.0301	PREPARATION DECKS TYPE 1	SY	
509.0302	PREPARATION DECKS TYPE 2	SY	
509.2000	FULL-DEPTH DECK REPAIR	SY	
SPV.0035	CONCRETE MASONRY DECK PATCHING	CY	
SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF	
509.3500.S	HMA OVERLAY POLYMER-MODIFIED	TON	
POSSIBLE ADDITIONAL BID ITEMS			
509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY	SY	
509.9010.S	REMOVING ASPHALTIC CONCRETE DECK OVERLAY (STRUCTURE)	SY	

THIS IS A PARTIAL LIST OF POSSIBLE BID ITEMS. BID ITEMS MAY NEED TO BE ADDED OR REMOVED TO FIT EACH INDIVIDUAL CASE.

DESIGN DATA

LIVE LOAD:
INVENTORY RATING: HS-...
OPERATING RATING: HS-...
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... KIPS

MATERIAL PROPERTIES:
CONCRETE MASONRY - DECK PATCHING f'c = 4,000 P.S.I.

NOTES

DRAWINGS SHALL NOT BE SCALED.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.

AREAS OF "PREPARATION DECKS TYPE 1" SHALL BE DEFINED BY A SAW CUT.


PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2, AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION AND FULL-DEPTH DECK REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY DECK PATCHING".

ANY EXCAVATION REQUIRED TO COMPLETE THE OVERLAY OR JOINT REPAIR AT THE ABUTMENTS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "HMA OVERLAY POLYMER-MODIFIED".

THE PLAN QUANTITY FOR THE BID ITEM "HMA OVERLAY POLYMER-MODIFIED" IS BASED ON THE AVERAGE OVERLAY THICKNESS.

PROFILE GRADE LINE SHALL BE DETERMINED IN THE FIELD BASED ON A MINIMUM OVERLAY THICKNESS OF 2" PLACED ABOVE THE DECK SURFACE. EXPECTED AVERAGE OVERLAY THICKNESS IS 2 1/2" (OR AS GIVEN ON THE PLANS). IF EXPECTED AVERAGE OVERLAY THICKNESS IS EXCEEDED BY MORE THAN 1/2", CONTACT THE STRUCTURES DESIGN SECTION.

POLYMER MODIFIED ASPHALTIC OVERLAY



CROSS SECTION THRU ROADWAY

LOOKING NORTH

DESIGNER NOTES

CONCRETE OVERLAYS ARE THE CURRENT PREFERRED METHOD TO OVERLAY A BRIDGE.

REPAIRS USING CONCRETE REQUIRE A MINIMUM CURE TIME OF 7 DAYS BEFORE PLACING OVERLAY. ALTERNATIVES TO CONCRETE DECK PATCHES MAY BE USED TO SHORTEN TIME REQUIRED FOR PLACING OVERLAY.

PROVIDE AN AVERAGE OVERLAY THICKNESS ON THE PLANS. THE AVERAGE OVERLAY THICKNESS IS THE MINIMUM OVERLAY THICKNESS PLUS 1/2" TO ACCOUNT FOR VARIATIONS IN THE DECK SURFACE. CHANGES IN CROSS-SLOPE INCREASE THE AVERAGE OVERLAY THICKNESS. QUANTITIES ARE BASED ON THE AVERAGE OVERLAY THICKNESS.

DO NOT PROVIDE A PROFILE GRADE LINE ON THE PLANS.

OVERLAYS NOT REQUIRING SHEET MEMBRANE WATERPROOFING ARE PREFERRED.

COORDINATE ASPHALTIC DESIGN WITH REGION BRIDGE MAINTENANCE AND ROADWAY ENGINEERS.

THE PLAN QUANTITY FOR THE BID ITEM "HMA PAVEMENT TYPE E-X" IS BASED ON (INSERT VALUE) LBS/CF X (AVERAGE OVERLAY THICKNESS) X (OVERLAY AREA). ASSUME 112 LBS/(SY-IN) IF NO ADDITIONAL INFORMATION IS PROVIDED.

THE PLAN QUANTITY FOR THE BID ITEM "ASPHALTIC MATERIAL PGXX-XX" IS BASED ON (INSERT VALUE) % OF BID ITEM "HMA PAVEMENT TYPE E-X". ASSUME 6% IF NO ADDITIONAL INFORMATION IS PROVIDED.

THE PLAN QUANTITY FOR THE BID ITEM "TACK COAT" IS BASED ON A APPLICATION RATE OF 0.025 GALLONS/SY.

RESTRICTIONS ON REMOVAL ITEMS SHALL BE PLACED ON THE PLANS TO PREVENT DAMAGE TO REINFORCING STEEL.

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
455.0XXX	ASPHALTIC MATERIAL PGXX-XX	TON	
455.0605	TACK COAT	GAL	
460.IXXX	HMA PAVEMENT TYPE E-X	TON	
509.0301	PREPARATION DECKS TYPE 1	SY	
509.0302	PREPARATION DECKS TYPE 2	SY	
509.2000	FULL-DEPTH DECK REPAIR	SY	
SPV.0035	CONCRETE MASONRY DECK PATCHING	CY	
SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF	
POSSIBLE ADDITIONAL BID ITEMS			
509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY	SY	
509.9010.S	REMOVING ASPHALTIC CONCRETE DECK OVERLAY (STRUCTURE)	SY	

THIS IS A PARTIAL LIST OF POSSIBLE BID ITEMS. BID ITEMS MAY NEED TO BE ADDED OR REMOVED TO FIT EACH INDIVIDUAL CASE.

DESIGN DATA

LIVE LOAD:
INVENTORY RATING: HS-...
OPERATING RATING: HS-...
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... KIPS

MATERIAL PROPERTIES:
CONCRETE MASONRY - DECK PATCHING f'c = 4,000 P.S.I.

NOTES

DRAWINGS SHALL NOT BE SCALED.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.

AREAS OF "PREPARATION DECKS TYPE 1" SHALL BE DEFINED BY A SAW CUT.

PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2, AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION AND FULL-DEPTH DECK REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY DECK PATCHING".

ANY EXCAVATION REQUIRED TO COMPLETE THE OVERLAY OR JOINT REPAIR AT THE ABUTMENTS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "HMA PAVEMENT TYPE E-X".

THE PLAN QUANTITY FOR THE BID ITEM "HMA PAVEMENT TYPE E-X" IS BASED ON THE AVERAGE OVERLAY THICKNESS.

PROFILE GRADE LINE SHALL BE DETERMINED IN THE FIELD BASED ON A MINIMUM OVERLAY THICKNESS OF 2" PLACED ABOVE THE DECK SURFACE. EXPECTED AVERAGE OVERLAY THICKNESS IS 2 1/2" (OR AS GIVEN ON THE PLANS). IF EXPECTED AVERAGE OVERLAY THICKNESS IS EXCEEDED BY MORE THAN 1/2", CONTACT THE STRUCTURES DESIGN SECTION.

ASPHALTIC OVERLAY

POLYMER MODIFIED ASPHALTIC AND ASPHALTIC OVERLAYS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-15