



PRECAST PIER CAP AND COLUMNS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 7-14




TYPE A1 WITH FIXED SEAT



TYPE A1 WITH SEMI-EXPANSION SEAT

LEGEND

- ◆ #5 BARS (COATED) AT 1'-0" (2'-0" LONG). THESE BARS MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE.
- ◇ WHEN THIS DIMENSION ≥ 4" THIS ADDITIONAL REINFORCEMENT SHALL BE ADDED. MAX. SPA. OF HORIZ. #4 BARS = 1'-0".
- USE 1'-3" FOR SLAB SPANS AND FOR GIRDER SPANS WITH NO PAVING NOTCH. USE 1'-6" FOR GIRDER SPANS WITH NO PAVING NOTCH, BUT WHERE 36W", 45W", 54", 54W", 70", 72W" OR 82W" GIRDERS ARE USED, AND SKEW > 25°. USE 1'-3" FOR SLAB SPANS WITH A PAVING NOTCH, BUT NO STRUCTURAL APPROACH SLAB. USE 1'-11" FOR GIRDER SPANS WITH A PAVING NOTCH, BUT NO STRUCTURAL APPROACH SLAB. USE 1'-7" FOR SLAB SPANS WITH A STRUCTURAL APPROACH SLAB. (STD. 12.10) USE 2'-3" FOR GIRDER SPANS WITH A STRUCTURAL APPROACH SLAB. (STD. 12.10)
- DIMENSION IS FROM BOTTOM OF ABUTMENT TO LOW BEAM SEAT OR LOW SIDE OF SLAB TYPE SUPERSTRUCTURE.
- ▽ 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZONTAL AND VERTICAL JOINTS ON BACKFACE.
- ▲ KEYED CONST. JOINT FORMED BY BEVELED 2" x 6".
- ** WINGWALL WIDTH SHALL BE 1'-6" WHEN "M" RAILING, VERTICAL FACE PARAPET "TX", OR SINGLE SLOPE PARAPET "565S" IS USED. WINGWALL WIDTH SHALL BE 1'-9" WHEN TYPE "NY3" OR "NY4" RAILING IS USED.
- USE #5 BARS AT 6" SPA. IN OUTSIDE THIRDS OF BODY LENGTH WHEN THE WING LENGTH > 20'-0" AND WING HEIGHT > 10'-0".
- ☆ WHEN BODY SECTION IS > 50'-0"± LONG PROVIDE VERTICAL CONSTRUCTION JOINT. RUN BAR STEEL THRU JOINT AND SEAL JOINT WITH 18" RUBBERIZED MEMBRANE WATERPROOFING. SEE STD. 12.09 FOR ALTERNATE CONSTRUCTION JOINT.
- ⊙ SHOW ALL BARS FOR CLARITY.



SECTION B-B

RODENT SHIELD DETAIL

* DIMENSIONS ARE APPROXIMATE, THE GRATE IS SIZED TO FIT INTO A PIPE COUPLING. ORIENT SO SLOTS ARE VERTICAL.

THE RODENT SHIELD, PIPE COUPLING AND SCREWS SHALL BE CONSIDERED INCIDENTAL TO THE BID ITEM "PIPE UNDERDRAIN WRAPPED 6-INCH".

THE RODENT SHIELD SHALL BE A PVC GRATE SIMILAR TO THIS DETAIL. THE GRATE IS COMMERCIALY AVAILABLE AS A FLOOR STRAINER. A PIPE COUPLING IS REQUIRED FOR THE ATTACHMENT OF THIS SHIELD TO THE EXPOSED END OF THE PIPE UNDERDRAIN. THE SHIELD SHALL BE FASTENED TO THE PIPE COUPLING WITH TWO OR MORE NO. 10 X 1-INCH STAINLESS STEEL SHEET METAL SCREWS.

DESIGNER NOTES


LAP LENGTHS FOR HORIZONTAL BARS SHALL BE BASED ON A "CLASS C" TOP TENSION LAP SPLICE.

PILING SPACING IN ABUTMENT BODY SHALL BE 8'-0" MAX. FOR ALL TYPES OF PILING. THE MAX. PILE SPACING FROM THE END OF THE ABUT. BODY TO THE FIRST PILE SHALL BE THE MINIMUM OF ONE-HALF PILE SPACE OR 2'-6".

CONCRETE POURED UNDER WATER WILL BE ALLOWED AND SHALL BE DONE IN ACCORDANCE WITH SECTION 502.3.5.3 STANDARD SPECIFICATIONS.


THE SEMI-EXPANSION SEAT SHALL BE USED WHEN REQUIRED AS STATED IN CHAPTER 12, FIGURE 12.7-1 OF THE BRIDGE MANUAL OR WHENEVER A WING PILE IS REQUIRED.

THE FIXED SEAT CANNOT BE USED WHEN A WING PILE IS REQUIRED (SEE STD 12.02 FOR CRITERIA)




WING WITHOUT PILE

DISTANCE OR EQUIVALENT STD. HOOK)	BAR SIZE
1'-9"	5
2'-1"	6
2'-9"	7
3'-8"	8
4'-7"	9
5'-10"	10



WING WITH PILE




SLAB SPAN WITH FIXED SEAT

GIRDER SPAN WITH FIXED SEAT

SLAB SPAN WITH SEMI-EXPANSION SEAT

GIRDER SPAN WITH SEMI-EXPANSION SEAT

ABUTMENT TYPE A1 (INTEGRAL ABUTMENT)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 7-14



DESIGNER NOTES

LENGTH OF A1 BARS SHALL BE \geq TO WING LENGTH.

WING WITH PILE & WING WITHOUT PILE CAN BE USED FOR EITHER SIDEWALK OR SLOPED FACE PARAPETS. THE TYPE OF WING TO USE IS BASED ONLY ON THE WING HEIGHT AND WING LENGTH LIMITATIONS SHOWN.

LAP LENGTH FOR HORIZONTAL BARS SHALL BE BASED ON A "CLASS C" TOP TENSION LAP SPlice.

WING BARS AND DOWEL BARS SHALL BE EPOXY COATED.

NAME PLATE (ONLY FOR TYPE "F", "W" AND "M" OR TIMBER RAIL AS SHOWN ON STANDARD 30.24), LOCATE NAME PLATE ON FIRST RIGHT WING TRAVELING UP STATION.

SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.







LRFD DESIGN LOADS

LIVE LOAD = 2'-0" SURCHARGE
LOAD FACTORS:
 $\gamma_{DC} = 1.25$
 $\gamma_{DW} = 1.50$
 $\gamma_{EV} = 1.35$
 $\gamma_{LS} = 1.75$

EXPOSURE CLASS 2, $\gamma_E = 0.75$
 $f_y = 60,000$ P.S.I.
 $f'_c = 3,500$ P.S.I.
 HORIZ. EARTH LOAD BASED ON:
 35 P.C.F. EQUIV. FLUID UNIT
 WEIGHT OF SOIL

WING LENGTH	WING HEIGHT			BARS	
	8'-6"	10'-0"	11'-6"		
10'-0"	#6-#6's	#6-#6's	6-#5's	W	
10'-0"	#7-#8's	#7-#8's	6-#5's	A1	
12'-0"	#6-#6's	#7-#6's	7-#5's	W	
12'-0"	#7-#8's	#7-#8's	6-#7's	A1	
16'-0"	7-#6's	8-#6's	7-#7's	8-#7's	W
16'-0"	5-#8's	6-#8's	7-#8's	8-#8's	A1
20'-0"	7-#7's	7-#8's	8-#8's	8-#9's	W
20'-0"	6-#9's	7-#9's	7-#10's	8-#10's	A1
24'-0"	8-#8's	9-#8's	9-#9's	9-#10's	W
24'-0"	7-#9's	8-#9's	8-#10's	9-#10's	A1

* WING WITHOUT PILE VALUES SHOWN. (FOR WING WITH PILE THAT HAS WING LENGTH IN THIS REGION, USE VALUES FOR 11'-6" WING HEIGHT.)



TOP OF WING DETAILS
(TYP. FOR A3 ABUTMENT WINGS ALSO)

- CONSTRUCTION JOINT, LEAVE ROUGH. REQUIRED FOR PRESTRESSED CONCRETE SUPERSTRUCTURES. OPTIONAL FOR OTHERS. POUR CONCRETE ABOVE THIS JOINT AFTER DECK IS IN PLACE. IF JOINT IS USED, UTILIZE RUBBERIZED MEMBRANE WATERPROOFING (COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY BRIDGES").
- USE #4 BARS @ 1'-6" FOR WINGWALL WIDTH = 1'-3". USE #4 BARS @ 1'-4" FOR WINGWALL WIDTH = 1'-6".
- ** BARS TO BE SAME SIZE AS "W" BARS.
- OPTIONAL CONST. JOINT FORMED BY BEVELED 2" x 6" KEYWAY WITH MEMBRANE ON BACKFACE.


ABUTMENT TYPE A1

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: *Bill Oliva* DATE: 7-14

WING WITHOUT PILE SECTION

WING WITH PILE SECTION



FRONT ELEVATION



VERT. CONST. JOINT

$$P = \gamma D C (P_{DC} + \gamma D W + P_{DW}) + \gamma L L (P_{LL})$$


P ¹ K/FT	'A' BAR SIZE	FOOTING STEEL SIZE	FOOTING DEPTH 'D'
16	#6	#6	3'-0"
24	#7	#6	3'-0"
27	#7	#7	3'-0"
38	#8	#6	3'-3"
41	#8	#7	3'-3"
48	#9	#6	3'-3"
54	#9	#7	3'-3"

ABUTMENT BODY DEPTH	'B' BARS
< 7'	9- #11
≥ 7'	10- #10


h = WING HEIGHT

PILE REACTIONS PER FOOT IN KIPS	
BACK ROW =	$P(0.56 - X/5.5) - h^2/915 + 17.2$
FRONT ROW =	$P(0.44 + X/5.5) + h^2/425 + 7.9$

(PILES MUST ALSO BE DESIGNED TO ACCOUNT FOR LATERAL LOADS)



PLAN



SECTION AA

DESIGNER NOTES

- PIILING SPACING IN ABUTMENT FOOTING SHALL BE 8'-0" MAXIMUM.
- WHEN BODY SECTION IS MORE THAN 50'-0"± LONG, PROVIDE VERTICAL CONSTRUCTION JOINT. RUN BAR STEEL THRU JOINT, SEAL JOINT WITH 18" RUBBERIZED MEMBRANE WATERPROOFING. SEE STD. 12.09 FOR ALTERNATE CONSTRUCTION JOINT.

DESIGNER NOTES CONT'D

- IN "FRONT ELEVATION" VIEW, GIVE ELEVATION OF ALL BEARING AREAS AND ELEVATION AT BOTTOM OF PARAPETS AT EACH END OF WINGS. ALL ELEVATIONS ARE TAKEN AT FRONT FACE OF BACKWALL.
- LAP LENGTHS FOR HORIZONTAL BARS SHALL BE BASED ON A "CLASS C" TOP TENSION LAP SPLICE.
- PARAPET NOT SHOWN IN PLAN VIEW FOR CLARITY. SEE STD. 12.03 FOR ADDITIONAL DETAILS.

LEGEND

- 18" RUBBERIZED MEMBRANE WATERPROOFING. SEAL ALL HORIZ. AND VERT. JOINTS ON BACKFACE ABOVE FOOTING.
- ▲ KEYPED CONSTRUCTION JOINT FORMED BY BEVELED 2" X 6".
- #4 AT 9" BEAM SEAT. SPACE AT 1'-6" BETWEEN SEATS. THIS STEEL IS REQUIRED ONLY IF DIMENSION "A" EXCEEDS 4'.
- † OPTIONAL KEYPED CONSTRUCTION JOINT FORMED BY BEVELED 2" X 6". USE 3/4" 1" GROOVE ON F.F. OF WING WALL ONLY. IF JOINT IS NOT USED, WATERPROOFING IS NOT REQUIRED.
- ** WINGWALL WIDTH SHALL BE 1'-6" WHEN TYPE "M" RAILING, VERTICAL FACE PARAPET "TX" OR SINGLE SLOPE PARAPET "56SS" IS USED. "56SS" SHOULD NOT BE USED ON A SIDEWALK.
- ☆ PAVING NOTCH IS 1'-0" WIDE BY 1'-4" DEEP IF STRUCTURAL APPROACH SLAB (STD. 12.12) IS USED.
- ★ SIDE WALL IS 1'-3" WIDE IF STRUCTURAL APPROACH SLAB (STD. 12.12) IS USED.
- ⊙ SHOW ALL BARS FOR CLARITY.

ABUTMENT A4 PILE FOOTING

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
7-14

DESIGNER NOTES

THIS TYPE OF WING SHOULD BE USED WHEN POSSIBLE IN LIEU OF WINGS PARALLEL TO THE ROADWAY. DO NOT USE FOR STREAM CROSSINGS WHERE HIGH WATER MAY BE A PROBLEM.

*USE 2/2:1 FOR THE UNSTABLE CLAYS WHICH ARE SOMETIMES ENCOUNTERED IN NORTHWEST WISC. (SUPERIOR AREA)

1 WHEN TIMBER RAILING IS USED AS PER STANDARD 30.24, AND THE SKEW IS > 0°, THIS CONSTRUCTION JOINT SHALL BE MANDATORY. THE WING CONCRETE SHALL BE PLACED ABOVE CONSTR. JT. AFTER THE TIMBER END POSTS ARE IN PLACE.

ALL WING BARS SHALL BE EPOXY COATED.

2 SHOW ALL LONGITUDINAL BARS FOR CLARITY.

LRFD DESIGN LOADS (WINGS)

LIVE LOAD = 1'-0" SURCHARGE

LOAD FACTORS:

$\gamma_{DC} = 1.25$

$\gamma_{EH} = 1.50$

$\gamma_{LS} = 1.75$

EXPOSURE CLASS 2, $X_c = 0.75$

HORIZ. EARTH LOAD BASED ON: 35 P.C.F. EQUIV. FLUID UNIT

WT OF SOIL


FC = 60,000 P.S.I.

FC = 3,500 P.S.I.

TABLE A


WING LENGTH	WING HEIGHT				BARS
	8'-6"	10'-0"	11'-6"	13'-0"	
10'-0"	5-#5's	5-#5's	6-#5's		W
	4-#6's	2-#5's	2-#5's		WT
12'-0"		5-#6's	5-#7's	6-#7's	W
		2-#7's	2-#7's	2-#8's	WT
		5-#6's	6-#6's	6-#7's	AI
16'-0"		5-#8's	6-#8's	5-#9's	W
		2-#8's	2-#8's	2-#9's	WT
		5-#8's	6-#8's	7-#8's	AI
20'-0"			8-#8's	8-#9's	W
			2-#8's	2-#9's	WT
			7-#9's	8-#9's	AI

▲ WING PILE REQUIRED



PLAN FOR TYPE A1 ABUTMENT


(SEE STD. 12.01 FOR ABUTMENT BODY DETAILS)



WING ELEVATION

(A1 ABUTMENT)

DISTANCE	BAR SIZE
1'-9"	5
2'-1"	6
2'-9"	7
3'-8"	8
4'-7"	9



SECTION A-A

SECTION B-B

SEE STD. 12.01 & 12.02 FOR NOTES & DETAILS


DETAILS FOR WINGS PARALLEL TO A1 ABUTMENT CENTERLINE

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
7-14

STANDARD 12.07



DESIGNER NOTES

STRUCTURAL APPROACH SLABS AND PARAPETS SHALL BE USED ON ALL LH BRIDGES AND U.S.H. BRIDGES. OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER.

STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED BRIDGES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.

QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.

CONSTRUCTION JOINT REQUIRED WHEN WIDTH OF SUPERSTRUCTURE EXCEEDS 90'. RUN REINFORCEMENT THROUGH THE JOINT.

LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).

STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.), WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).

THE BID ITEM FOR S5901 BARS SHALL BE SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS BRIDGES".

DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND FDM SDD 802 OR 803.

LEGEND

SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

SEE PARAPET STANDARD DETAILS FOR LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET.

DESIGN DATA

CONCRETE STRENGTH, f'c: 4,000 P.S.I.
 BAR STEEL REINFORCEMENT, GRADE 60, fy: 60,000 P.S.I.
 ALLOWABLE SOIL BEARING PRESSURE: 2,000 P.S.F.


NOTE: FOR NEW STRUCTURES ON NEW ALIGNMENTS, BASE AGGREGATE DENSE 1-1/4 INCH AS PER FDM 14-5 AND BRIDGE MANUAL FIGURE 12.6-2 SHALL BE UTILIZED. FOR REPLACEMENT STRUCTURES ON EXISTING ALIGNMENTS, THE EXISTING SOIL MAY REMAIN IN PLACE IF THE REGION SOILS ENGINEER DETERMINES THAT THE EXISTING SOIL BEARING PRESSURE MEETS THE REQUIREMENT ABOVE.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENDS	BAR SERIES	LOCATION
S5901			5'-0"	X		CONC. ABUT. DIAPH. TO APPROACH SLAB

BAR MARK	COAT	NO. REQ'D.	LENGTH	BENDS	BAR SERIES	LOCATION
T501	X			X		APPROACH SLAB FTG. - STIRRUP
T802	X					APPROACH SLAB FTG. - TRANS.
T803	X			X		APPROACH SLAB - LONG. - BOT.
T804	X					APPROACH SLAB - LONG. - BOT. - WALL
T505	X					APPROACH SLAB - LONG. - TOP.
T506	X					APPROACH SLAB - LONG. - WALL
T507	X					APPROACH SLAB - TRANS. - BOT.
T508	X					APPROACH SLAB - TRANS. - TOP.
T509	X		4'-3"	X		APPROACH SLAB - TRANS. - TOP - WALL
T510	X		4'-1"	X		APPROACH SLAB - TRANS. - TOP - WING
T411	X		3'-0"	X		APPROACH SLAB - TRANS. - WALL




STRUCTURAL APPROACH SLAB FOR TYPE A1 ABUTMENTS

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 7-14

SECTIONS A-A THRU E-E ARE SHOWN ON STANDARD 12.11



APPROACH SLAB PLAN

APPROACH SLAB FTG. = XX'-XX"

APPROACH SLAB WIDTH = XX'-X"

EXTEND ABUTMENT LENGTH BY THICKNESS OF THE WING

DESIGNER NOTES

STRUCTURAL APPROACH SLABS AND PARAPETS SHALL BE USED ON ALL I.H. BRIDGES AND U.S.H. BRIDGES. OTHER LOCATIONS CAN BE CONSIDERED WITH THE APPROVAL OF THE CHIEF STRUCTURAL DESIGN ENGINEER.

STRUCTURAL APPROACH SLABS TO BE PART OF THE BRIDGE PLAN. BID ITEMS ARE CONCRETE MASONRY BRIDGES, BAR STEEL REINFORCEMENT HS COATED BRIDGES, ETC. POLYETHYLENE SHEETS SHALL BE INCIDENTAL TO CONCRETE MASONRY BRIDGES.

QUANTITIES FOR APPROACH SLABS SHALL BE SHOWN IN A SEPARATE COLUMN WITHIN THE TOTAL ESTIMATED QUANTITIES TABLE IN THE FINAL PLANS.

CONSTRUCTION JOINT REQUIRED WHEN WIDTH OF SUPERSTRUCTURE EXCEEDS 90'. RUN REINFORCEMENT THROUGH THE JOINT.

LONGITUDINAL APPROACH SLAB REINFORCEMENT SHALL BE PLACED PARALLEL TO THE APPROACH (I.E., NOT NORMAL TO THE ABUTMENT WITH SKEWED STRUCTURES).

STRUCTURE APPROACH SLABS TO BE DETAILED TO MATCH THE BRIDGE DECK (I.E., PROTECTIVE SURFACE TREATMENT, STAINLESS STEEL REINFORCEMENT, LONGITUDINAL GROOVING, ETC.). WHERE HIGH PERFORMANCE CONCRETE IS USED AT THE BRIDGE DECK, HPC SHALL BE USED FOR THE APPROACH SLAB ONLY (I.E., HPC IS NOT REQUIRED FOR APPROACH SLAB FOOTING).

THE BID ITEM FOR SS901 BARS SHALL BE SPECIAL PROVISION "BAR STEEL REINFORCEMENT HS STAINLESS BRIDGES".

DESIGNER TO COORDINATE LOCATION OF SURFACE DRAINS, INLETS, AND/OR FLUMES WITH ROADWAY DESIGNER AND FDM SDD 802 OR 803.

LEGEND

SEAL ALL EXPOSED HORIZONTAL AND VERTICAL SURFACES OF 1/2" FILLER WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER. (1" DEEP AND HOLD 1/8" BELOW SURFACE OF CONCRETE). EXTEND SEALER 3" BELOW GUTTER LINE AT INSIDE FACE.

SEE PARAPET STANDARD DETAILS FOR LOCATION OF NAME PLATE AND BENCH MARK WITH RESPECT TO THE END OF PARAPET.

DESIGN DATA

CONCRETE STRENGTH, f'_c: 4,000 P.S.I.
 BAR STEEL REINFORCEMENT, GRADE 60, f_y: 60,000 P.S.I.
 ALLOWABLE SOIL BEARING PRESSURE: 2,000 P.S.F.


NOTE:
 FOR NEW STRUCTURES ON NEW ALIGNMENTS, BASE AGGREGATE DENSE 1-1/4 INCH AS PER FDM 14-5 AND BRIDGE MANUAL FIGURE 12.6-2 SHALL BE UTILIZED.
 FOR REPLACEMENT STRUCTURES ON EXISTING ALIGNMENTS, THE EXISTING SOIL MAY REMAIN IN PLACE IF THE REGION SOILS ENGINEER DETERMINES THAT THE EXISTING SOIL BEARING PRESSURE MEETS THE REQUIREMENT ABOVE.

BILL OF BARS

NOTE: THE FIRST OR FIRST TWO DIGITS OF THE BAR MARK SIGNIFIES THE BAR SIZE.

BAR MARK	COAT	NO. REOD.	LENGTH	BENT	BAR SERIES	LOCATION
SS901			5'-0"	X		CONC. BACKWALL TO APPROACH SLAB

BAR MARK	COAT	NO. REOD.	LENGTH	BENT	BAR SERIES	LOCATION
T501	X			X		APPROACH SLAB FTG. - STIRRUP
T802	X					APPROACH SLAB FTG. - TRANS.
T803	X			X		APPROACH SLAB - LONG. - BOT.
T804	X					APPROACH SLAB - LONG. - BOT. - WALL
T505	X					APPROACH SLAB - LONG. - TOP.
T506	X					APPROACH SLAB - LONG. - WALL
T507	X					APPROACH SLAB - TRANS. - BOT.
T508	X					APPROACH SLAB - TRANS. - TOP.
T509	X		4'-3"	X		APPROACH SLAB - TRANS. - TOP - WALL
T510	X		4'-1"	X		APPROACH SLAB - TRANS. - TOP - WING
T411	X		3'-0"	X		APPROACH SLAB - TRANS. - WALL



STRUCTURAL APPROACH SLAB FOR TYPE A3 & A4 ABUTMENTS

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE: 7-14


SECTIONS A-A THRU F-F ARE DETAILED ON STANDARD 12.13

GIRDER STRUCTURES


CONCRETE SLAB STRUCTURES




ELEVATION
LOOKING UP STATION




PLAN



END VIEW



CONST. JT. DETAIL



SECTION P1

ALTERNATE SECTION P1

DESIGNER NOTES

ALL BAR SPLICES TO BE BASED ON "CLASS C" TENSION LAP SPLICE UNLESS OTHERWISE SHOWN.

OPTIONAL KEYED CONSTRUCTION JOINTS IN SHAFT, IF PROVIDED, SHALL BE PLACED APPROXIMATELY 2'-0" ABOVE NORMAL WATER ELEVATION. OPTIONAL KEYED CONSTRUCTION JOINT IN SHAFT SHALL BE PROVIDED SO THAT MAXIMUM HEIGHT OF POUR NEED NOT EXCEED 20 FEET. RUSTICATIONS SHOWN IN "CONST. JT. DETAIL" MAY BE OMITTED AT THE OPTION OF THE DESIGNER.

KEYED CONSTRUCTION JOINTS SHALL BE FORMED BY BEVELED KEYWAY 4" DEEP X 1/3 THICKNESS OF SHAFT X 4'-0" LESS THAN LENGTH OF SHAFT.

A STANDARD SHAFT TAPER OF 1% MAY BE USED AT THE OPTION OF THE DESIGNER. (LATERAL DIRECTION ONLY)

SHAFT MAY BE TAPERED IN ONE OR TWO DIRECTIONS WHEN REQUIRED FOR STRUCTURAL REASONS.

A NON-STANDARD SHAFT CROSS-SECTION, SHAPE, OR TAPER, NOT REQUIRED FOR STRUCTURAL REASONS, MAY BE USED ONLY WITH THE APPROVAL OF THE STRUCTURES DESIGN SECTION.

BEARING SEAT AREAS SHALL BE LEVEL EXCEPT FOR THE TWO CASES LISTED BELOW:

1. FOR GIRDERS WITH 1/2" ELASTOMERIC BEARING PADS WHEN THE BOTTOM OF THE GIRDERS SLOPE MORE THAN 1%. SEE STANDARD 13.01.

2. FOR CONCRETE SLAB SUPERSTRUCTURES MAKE THE TOP OF CAP PARALLEL TO GRADE. SEE STANDARD 18.01.

BEAM SEATS MAY BE ANGLED TO MATCH SKEW AT THE DESIGN ENGINEER'S DISCRETION.

SEE STANDARD 12.01 FOR ADDITIONAL REINFORCING STEEL IN BEARING AREA FOR BEAM SEATS OF NON-SLOPED CAPS THAT ARE 4 INCHES OR MORE ABOVE THE LOWEST BEARING SEAT.

THIS MAXIMUM VERT. BAR SPACING APPLIES ONLY WHEN THE VERTICAL REINFORCEMENT IS 1% OR MORE OF THE GROSS CONCRETE AREA.

SEE STANDARD 13.01 FOR MINIMUM OFFSETS FROM BEARINGS TO SIDES OF CAP AND TO ADJACENT BEARING SEAT STEPS.

EPOXY COAT BAR STEEL DOWN TO TOP OF FOOTINGS IN ALL PIERS UNDER EXPANSION JOINTS AND ON ALL PIERS AT GRADE SEPARATIONS.

INCREASE THIS DIMENSION IF NECESSARY TO PREVENT BATTERED PILES FROM DRIVING INTO SHEET PILING. ALSO INCREASE DIMENSION TO FACILITATE OVERHEAD SHEETING CLEARANCE IF THE TOP OF PIER IS BEYOND NORMAL SEAL SIZE AND NO CONSTRUCTION JOINT IS PROVIDED IN THE SHAFT/CAP REGION (E.G. TAPERED WALL PIERS OR SHORTER HAMMERHEADS WITH RADIUS TRANSITION FROM SHAFT TO CAP).

MAXIMUM SPACING BETWEEN UNRESTRAINED VERTICAL BAR AND RESTRAINED (TIED ACROSS MEMBER) VERTICAL BAR IS 24 INCHES.


HAMMERHEAD PIER

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: *Bill Oliva*

DATE:
7-14

R N.E. RAMP



EXAMPLE PLAN



EXAMPLE ELEVATION
(LOOKING @ F.F. OF WALL)

GEOMETRY TABLE

STATION	OFFSET TO F.F. WALL	COORDINATES	ELEV. A	ELEV. B

SOIL PARAMETERS

STRATUM LOCATIONS & SOIL DESCRIPTIONS	UNIT WEIGHT (pcf)	FRICTION ANGLE (DEGREES)	COHESION (psf)
EL. - EL. (SOIL TYPE)			
EL. - EL. (SOIL TYPE)			
EL. & BELOW (SOIL TYPE)			
RETAINED SOIL EL. - EL. *			

* DESIGN WALL FOR THESE VALUES

SAFETY FACTORS

MINIMUM DOT STANDARD	(INSERT WALL SYSTEM)
SLIDING (FS>1.5)	
OVERTURNING (FS>2.0)	
GLOBAL STABILITY (FS>1.3)	
ULTIMATE BEARING CAPACITY (FS>2) BASED ON WALL WIDTHS & IMBEDMENT DEPTHS SHOWN IN TABLE	

DESIGN DATA

THE CONTRACTOR SHALL PROVIDE COMPLETE DESIGN, PLANS, DETAILS, SPECIFICATIONS, AND SHOP DRAWINGS FOR THE RETAINING WALLS IN ACCORDANCE WITH THE SPECIAL PROVISIONS. THE RETAINING WALL MANUFACTURER SHALL PROVIDE TECHNICAL ASSISTANCE TO THE CONTRACTOR DURING CONSTRUCTION. THE COST OF FURNISHING THESE ITEMS SHALL BE INCLUDED IN THE BID ITEM "INSERT WALL SYSTEM OR SYSTEMS".

PLANS, ELEVATIONS AND DETAILS SHOWN ON THESE DRAWINGS ARE INTENDED TO INDICATE WALL LOCATIONS, LENGTHS, HEIGHTS, AND DETAILS COMMON TO THE WALL SYSTEM SELECTED. THE CONTRACTOR SHALL VERIFY THAT THE WALL SYSTEM SELECTED WILL CONFORM TO THE REQUIRED ALIGNMENTS AND DETAILS.

THE RETAINING WALL IS TO BE DESIGNED USING THE ELEVATIONS GIVEN ON THIS SHEET.

DESIGN FOR RETAINING WALL TO PROVIDE FOR FINISHED GRADE SLOPED BEHIND WALL AS SHOWN.

SEE SPECIAL PROVISIONS FOR AESTHETIC TREATMENT TO WALL.

DESIGN RETAINING WALL FOR A LIVE LOAD SURCHARGE OF INSERT VALUE).

THE MAXIMUM VALUE OF THE ANGLE OF INTERNAL FRICTION OF THE WALL BACKFILL MATERIAL IN THE REINFORCED ZONE SHALL BE ASSUMED TO BE 30° WITHOUT CERTIFIED TEST VALUES.

ALLOWABLE WALL SYSTEMS


- 1.
- 2.

TOTAL ESTIMATED QUANTITIES

(INSERT WALL SYSTEM) S.F.

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.



TYP. CROSS SECT. OF RETAINING WALL

LIST OF DRAWINGS

1. INSERT WALL SYSTEM
2. SUBSURFACE EXPLORATION

PROPRIETARY RETAINING WALLS (GENERAL PLAN)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
7-14

GENERAL NOTES

DRAWINGS SHALL NOT BE SCALED.

THE PLAN QUANTITY FOR THE BID ITEM (INSERT WALL SYSTEM) IS BASED ON A WALL HEIGHT MEASURED FROM THE TOP OF WALL TO A CONSTANT DEPTH OF (INSERT VALUE) BELOW FINISHED GRADE.

DESIGN DATA

THE CONTRACTOR SHALL PROVIDE COMPLETE DESIGN, PLANS, DETAILS, SPECIFICATIONS, AND SHOP DRAWINGS FOR THE RETAINING WALLS IN ACCORDANCE WITH THE SPECIAL PROVISIONS. THE RETAINING WALL MANUFACTURER SHALL PROVIDE TECHNICAL ASSISTANCE TO THE CONTRACTOR DURING CONSTRUCTION. THE COST OF FURNISHING THESE ITEMS SHALL BE INCLUDED IN THE BID ITEM "INSERT WALL SYSTEM OR SYSTEMS".

PLANS, ELEVATIONS AND DETAILS SHOWN ON THESE DRAWINGS ARE INTENDED TO INDICATE WALL LOCATIONS, LENGTHS, HEIGHTS, AND DETAILS COMMON TO THE WALL SYSTEM SELECTED. THE CONTRACTOR SHALL VERIFY THAT THE WALL SYSTEM SELECTED WILL CONFORM TO THE REQUIRED ALIGNMENTS AND DETAILS.

THE RETAINING WALL IS TO BE DESIGNED USING THE ELEVATIONS GIVEN ON THIS SHEET.

DESIGN FOR RETAINING WALL TO PROVIDE FOR FINISHED GRADE SLOPED BEHIND WALL AS SHOWN.

SEE SPECIAL PROVISIONS FOR AESTHETIC TREATMENT TO WALL.

DESIGN RETAINING WALL FOR A LIVE LOAD SURCHARGE OF (INSERT VALUE).

THE MAXIMUM VALUE OF THE ANGLE OF INTERNAL FRICTION OF THE WALL BACKFILL MATERIAL IN THE REINFORCED ZONE SHALL BE ASSUMED TO BE 30° WITHOUT CERTIFIED TEST VALUES.

DESIGNER NOTES

☐ THE LENGTHS PROVIDED IN THE TABLE ARE THE MINIMUM REQUIRED REINFORCEMENT LENGTHS BASED UPON THE MINIMUM DESCRIBED IN THE WALL SYSTEM SPECIAL PROVISIONS OR EXTERNAL AND OVERALL STABILITY AT THE DESIGNATED LOCATIONS. THESE DESIGNATED LOCATIONS REPRESENT TYPICAL AND CRITICAL WALL LOCATIONS, BUT SHALL NOT BE CONSIDERED ALL INCLUSIVE. THE CONTRACTOR DESIGN LENGTHS SHALL MEET OR EXCEED THE MINIMUM VALUES REPRESENTED IN THE TABLE AT THESE DESIGNATED LOCATIONS.

★ THE LENGTHS PROVIDED IN THE TABLE ARE THE MINIMUM REQUIRED REINFORCEMENT LENGTHS BASED ON OVERALL STABILITY PERFORMED BY THE WALL DESIGNER. COMPOUND STABILITY IS THE CONTRACTOR'S RESPONSIBILITY.

▲ MINIMUM EMBEDMENT BASED ON SITE SPECIFIC PARAMETERS (1'-6" MINIMUM FOR ALL WALLS ON LEVEL GROUND). FIELD EMBEDMENTS BELOW MINIMUM EMBEDMENT SHALL NOT BE INCLUDED IN THE PAY LIMITS.

● STRATUM LOCATIONS & SOIL DESCRIPTIONS AT EACH BORING LOCATION.

NOMINAL MSE PANEL DIMENSIONS ARE 5-FOOT HIGH AND 5-10 FOOT WIDE. THE WALL DESIGNER SHALL PROVIDE DETAILS BASED ON NOMINAL PANEL DIMENSIONS AND CONFIGURATION. DETAILS SHALL BE ABLE TO ACCOMMODATE VARIOUS PANEL DIMENSIONS. THE CONTRACTOR AND WALL SUPPLIER SHALL COORDINATE DETAILS BASED ON THE ACTUAL PANEL DIMENSIONS.

R N.E. RAMP

BEGIN WALL
STA. 185+75 N.E. RAMP
39.59' LT. =
STA. 0+00 WALL


PC STA. 1+11.51 WALL
= STA. 184+63.76 N.E. RAMP
31.54' LT.

EXAMPLE PLAN

CC STA. 184+60.53 N.E. RAMP
76.42' LT.

PT STA. 1+63.69 WALL
= STA. 184+21.45 N.E. RAMP
55.56' LT

END WALL
STA. 184+13 N.E. RAMP
74.49' LT. =
STA. 1+84.84 WALL



EXAMPLE ELEVATION

(LOOKING @ F.F. OF WALL)

GEOMETRY TABLE

WALL STATION	ROADWAY STATION	OFFSET TO F.F. WALL	TOP OF WALL ELEV.	FINISHED GRADE ELEV.


SOIL PARAMETERS

STRATUM LOCATIONS & SOIL DESCRIPTIONS	TOTAL UNIT WEIGHT (PCF)	FRICTION ANGLE (DEGREES)	COHESION (PCF)
GRANULAR BACKFILL (REINFORCING ZONE OR BACKFILL)			
(INSERT SOIL TYPE) RETAINED SOIL *			
(INSERT SOIL TYPE) FILL			
(INSERT SOIL TYPE)			
(INSERT SOIL TYPE)			

* DESIGN WALL FOR THESE VALUES

WALL EXTERNAL & OVERALL STABILITY EVALUATION

DIMENSIONS	EVALUATED LOCATIONS
WALL HEIGHT (FEET)	
EXPOSED WALL HEIGHT (FEET)	
MINIMUM LENGTH OF REINFORCEMENT (FEET) ☐	
WALL STATION	
BORING USED	
CAPACITY TO DEMAND RATIO (CDR)	
SLIDING (CDR>1.0)	
ECCENTRICITY (CDR>1.0)	
OVERALL STABILITY (CDR>1.0) ★	
BEARING RESISTANCE (CDR>1.0)	
FACTORED BEARING RESISTANCE (PSF)	



LIST OF DRAWINGS


- (INSERT WALL SYSTEM)
- SUBSURFACE EXPLORATION

LRFD PROPRIETARY RETAINING WALLS (GENERAL PLAN)


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva


DATE:
7-14




**TYPICAL SECTION
HIGHWAY GRADE SEPARATION**




**ALT. SECTION @ SHOULDER
(RURAL ROADWAY)**




SECTION @ SIDEWALK



SECTION A-A




0° - 15° SKEW



> 15° SKEW

**PLAN
(TYPICAL SECTION SHOWN)**



CONSTRUCTION JOINT DETAIL


GENERAL NOTES
 DETAILS OF CONSTRUCTION NOT SHOWN HEREIN SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS

**SLOPE PAVING - STRUCTURES
(CONCRETE CAST-IN-PLACE)**

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
 7-14



**PART TRANSVERSE SECTION AT ABUTMENT
TYPE A1 DIAPHRAGM WITH A RAISED SIDEWALK**

(HORIZ. BARS SHOWN ARE THE FF BARS.
DECK REINFORCEMENT NOT SHOWN FOR CLARITY.)




SECTION A-A

** 3" X 3" BEVEL ENDS AT EDGE OF BRIDGE DECK

SECTION B-B


- SEE STANDARDS 19.33, 19.34, 19.35 FOR REINFORCEMENT DETAILS
- DETAILS SHOWN ARE FOR GIRDER STRUCTURES. SIMILAR REINFORCEMENT FOR SLAB STRUCTURES SHALL BE USED WITH A REMINDER THAT THE TRANSVERSE AND LONGITUDINAL REINFORCEMENT LAYERS ARE REVERSED.



CROSS SECTION THRU UNANCHORED MEDIAN


* (ANCHORAGE TO DECK NOT REQUIRED FOR WIDTHS > 3'-0", EXCEPT ALL MEDIAN SECTIONS ON TOP OF PAVING BLOCK MUST BE ANCHORED)

NOTE: CLEAN ALL LOOSE MATERIAL ON THE DECK AT THE MEDIAN LOCATION PRIOR TO MEDIAN PLACEMENT USING HIGH PRESSURE WATER OR AIR, ENSURING ALL FREE-STANDING WATER IS REMOVED PRIOR TO MEDIAN PLACEMENT. NEAT CEMENT IS REQUIRED AS PER 509.3.9.2 OF THE STANDARD SPECIFICATIONS UNLESS THE MEDIAN IS POURED WITHIN 45 DAYS OF COMPLETING THE DECK POUR.




CROSS SECTION THRU ANCHORED MEDIAN

SEE STD. 24.11 FOR DECK JOINT DETAIL FOR LONGITUDINAL AND TRANSVERSE JOINTS.



SECTION THRU SIDEWALK



DEFLECTION JOINT DETAIL

SHOWING DEFLECTION JOINT IN PARAPET OR SIDEWALK USING THE FOLLOWING CRITERIA:

1. GIRDER STRUCTURES AND SLAB STRUCTURES WITH A SIDEWALK SHOULD HAVE A DEFLECTION JOINT IN THE SIDEWALK AND PARAPET OVER THE PIER.
2. GIRDER STRUCTURES AND SLAB STRUCTURES WITHOUT SIDEWALKS SHOULD HAVE NO DEFLECTION JOINTS IN THE PARAPETS.

NOTES

WHEN PARAPETS ARE POURED CONTINUOUSLY FROM END TO END, THEY SHALL BE SEPARATED AT THE DEFLECTION JOINTS BY A PIECE OF 1/4" ZINC OR PLASTIC PLATE CUT AS SHOWN IN THE "DEFLECTION JOINT DETAIL". IF CONSTRUCTION JOINTS IN PARAPETS ARE USED AT THE DEFLECTION JOINTS, ONE SIDE OF JOINT SHALL BE COATED WITH AN APPROVED LIQUID BOND BREAKER AND PLATE SEPARATORS MAY BE OMITTED.

- ☑ CONST. JOINT-STRIKE OFF AS SHOWN AND LEAVE ROUGH FOR DECK POUR, MATCH BRIDGE X-SLOPE.
- ⊕ 8" MIN. SIDEWALK THICKNESS ALSO REQ'D AT EDGE OF DECK/SLAB.
- ▲ ±0.5% CONSTRUCTION TOLERANCE IN SIDEWALK CROSS SLOPE. THE SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2% WITHOUT PRIOR APPROVAL FROM THE ENGINEER.

DESIGNER NOTES

FOR EXTREME SIDEWALK WIDTHS AND/OR SUPERELEVATIONS THE DECK MAY BE LEVEL BENEATH THE SIDEWALK (MAINTAIN CONSTANT DECK THICKNESS) TO REDUCE EXCESSIVE SIDEWALK THICKNESS.


THE DESIGN ENGINEER SHALL DESIGN THE SUPERSTRUCTURE TO ACCOUNT FOR THE MAXIMUM 2% SIDEWALK CROSS SLOPE.

MEDIAN AND RAISED SIDEWALK DETAILS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva


DATE:
7-14




PLAN VIEW OF DECK CONTINUITY REINFORCEMENT FOR PRESTRESSED GIRDER BRIDGES
(SHOWING TYPICAL BAR SPACING FROM CHAPTER 17 TABLES)



PLAN VIEW OF DECK CONTINUITY REINFORCEMENT FOR PRESTRESSED GIRDER BRIDGES SHOWING HALF-SPACES
(SHOWING TYPICAL BAR SPACING FROM CHAPTER 17 TABLES + HALF-SPACE)




CROSS SECTION THRU EDGE OF DECK
(SHOWING DRIP GROOVE FOR ALL PARAPET AND RAILINGS, AND PROTECTIVE SURFACE TREATMENT FOR OPEN RAILINGS)




CROSS SECTION THRU EDGE OF SLAB
(SHOWING DRIP GROOVE FOR ALL PARAPET AND RAILINGS, AND PROTECTIVE SURFACE TREATMENT FOR OPEN RAILINGS)


- NOTES:
- LONGITUDINAL CONSTRUCTION JOINT DETAIL IS OPTIONAL AND IS TO BE USED FOR STAGED CONSTRUCTION JOINT LOCATIONS ONLY. DESIGNER TO DETERMINE PROJECT SPECIFIC APPLICABILITY.
 - AVOID PLACING JOINTS NEAR WHEEL PATHS. IF POSSIBLE, PLACE JOINTS AT LINE LINES.




LONGITUDINAL CONSTRUCTION JOINT DETAIL



CROSS SECTION THRU DECK
(SHOWING TOP LONGIT. REINF. LOCATION RELATIVE TO BOTTOM LONGIT. REINF.)



CROSS SECTION THRU EDGE OF DECK
(SHOWING ADDITIONAL OVERHANG REINFORCEMENT)



CROSS SECTION THRU EDGE OF DECK
(SHOWING ADDITIONAL OVERHANG REINFORCEMENT)

DESIGNER NOTES

- 3/4" V-GROOVE. TERMINATE 2'-0" FROM FRONT FACE OF EXPANSION ABUTMENTS, OR FIXED ABUTMENTS ON STEEL BEARINGS.
- 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM FOR TYPE A1 FIXED AND SEMI-EXPANSION ABUTMENTS.
- V-GROOVES ARE REQUIRED.

NOTES

- 3/4" V-GROOVE. TERMINATE 2'-0" FROM FRONT FACE OF ABUTMENTS.
- 3/4" V-GROOVE. EXTEND V-GROOVE TO 6" FROM FRONT FACE OF ABUTMENT DIAPHRAGM.
- V-GROOVES ARE REQUIRED.

- FOR OPEN RAILINGS, COAT WITH "PROTECTIVE SURFACE TREATMENT" AS PER THE STANDARD SPECIFICATIONS. PROTECTIVE SURFACE TREATMENT TO BE APPLIED TO THE TOP AND EXTERIOR EXPOSED FACE OF WINGS, AND THE END 1'-0" OF THE FRONT FACE OF ABUTMENT.



- COAT WITH "PROTECTIVE SURFACE TREATMENT" AS PER THE STANDARD SPECIFICATIONS.

DECK AND SLAB DETAILS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
7-14



PART PLAN



SECTION AT HOLD DOWN BOLT

GENERAL NOTES

ALL DRAIN MATERIAL INCLUDING GRATE, EXCLUDING PIPE & GRATE HOLD DOWN BOLTS, SHALL BE ASTM A36 STEEL.

MATERIAL FOR BRACKETS SHALL CONFORM TO ASTM A36.

THE CONTRACTOR MAY PROPOSE AN ALTERNATE TYPE OF BRACKET. THE PROPOSED ALTERNATE DETAILS SHALL BE SUBMITTED AND SUBJECT TO THE APPROVAL OF THE ENGINEER.

ALL STEEL SHALL BE GALVANIZED. WELDS SHALL BE MADE WITH LOW HYDROGEN ELECTRODES.

SEAL WELD INSIDE OF DRAIN.

PRIOR TO GALVANIZING A NO. 6 BLAST CLEANING IS REQUIRED.


FLANGED 6" DIA. FIBERGLASS PIPE CONFORMING TO ASTM D2996, GRADE 1, CLASS A, MAY BE USED AS AN ALTERNATE TO GALVANIZED STANDARD PIPE CONFORMING TO ASTM A53.

DESIGNER NOTES

ALL MATERIAL FOR FLOOR DRAINS AS SHOWN ON THIS SHEET SHALL BE INCLUDED IN THE BID ITEM "FLOOR DRAINS TYPE 'H'".


ALL MATERIAL FOR DOWNSPOUTS AND BRACKETS AS SHOWN ON THIS SHEET SHALL BE INCLUDED IN THE BID ITEM "DOWNSPOUT 6-INCH".

ON THE PRESTRESSED GIRDER SHEET, SHOW LOCATION OF HOLES FOR BRACKET ANCHORAGE FROM TOP/BOTTOM AND END OF GIRDER.




GRATE DETAIL


ATTACH GRATE TO FRAME FOR SHIPMENT



BRACKET DETAIL



SECTION A1



SECTION A2

FLOOR DRAIN TYPE 'H'	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 7-14

GENERAL NOTES

ALL MATERIAL FOR TYPE "WF" CASTING AND 8" DIA. CONNECTION PIPE, EXCLUDING GRATE HOLD DOWN SCREWS, SHALL BE GRAY IRON CONFORMING TO ASTM A48, CLASS 50.

MATERIAL FOR BRACKETS SHALL CONFORM TO ASTM A36.

THE CONTRACTOR MAY PROPOSE AN ALTERNATE TYPE OF BRACKET. THE PROPOSED ALTERNATE DETAILS SHALL BE SUBMITTED AND SUBJECT TO THE APPROVAL OF THE ENGINEER.

8" DIA. DOWNSPOUTS SHALL BE REINFORCED THERMOSETTING RESIN PIPE CONFORMING TO SECTION 514 OF THE STANDARD SPECIFICATIONS.






TRANSVERSE & LONGITUDINAL SLAB BAR REINFORCEMENT TO BE CUT A MAXIMUM OF 1" CLEAR FROM DRAIN FRAME. DISPLACE BARS WHERE POSSIBLE.

DESIGNER NOTES

ALL MATERIAL FOR FLOOR DRAINS AS SHOWN ON THIS SHEET SHALL BE INCLUDED IN THE BID ITEM "FLOOR DRAINS TYPE WF".


ALL MATERIAL FOR DOWNSPOUTS, CONNECTORS, AND BRACKETS AS SHOWN ON THIS SHEET SHALL BE INCLUDED IN THE BID ITEM "DOWNSPOUT 8-INCH".

ON THE PRESTRESSED GIRDER SHEET, SHOW LOCATION OF HOLES FOR BRACKET ANCHORAGE FROM TOP/BOTTOM AND END OF GIRDER.



FLOOR DRAIN TYPE 'WF'	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 7-14

AT END POSTS, RAIL MEMBER SHALL HAVE PROVISIONS FOR A THREE BEAM CONNECTION AS SHOWN ON SDD 14 B 20 STANDARDS.



ELEVATION OF RAILING

LEGEND

- ① #6x25 WITH 2 - 3/4" x 2 1/2" VERT. SLOTS IN FLG. (SLOT ON OTHER SIDE OF WEB IS OPTIONAL) FOR NO. 7, CUT BOTTOM OF POST TO MATCH CROSS SLOPE OF ROADWAY. PLACE POSTS VERTICAL AND NORMAL TO GRADE LINE.
- ② C8x11.5 WITH 1/16" DIA. HOLES FOR NO. 8.
- ③ BASE PLATE 1" x 9 1/2" x 10" WITH 1/16" x 1/2" SLOTTED HOLES FOR ANCHOR BOLTS NO. 4. WELD TO NO. 1 AS SHOWN.
- ④ A325 - 3/8" HEX BOLTS (GALVANIZED) WITH A325 NUT AND WASHER, 1/4" LONG AT END POSTS AND AT POSTS ON CONCRETE SLAB SUPERSTRUCTURES WHERE THE SLAB THICKNESS IS > 15". USE 8" LONG AT ALL OTHER LOCATIONS. 4 REOD. PER POST. THREAD 3" AND PLACE NORMAL TO PLATE NO. 3. CHAMFER TOP OF BOLTS BEFORE THREADING.
- ⑤ 1/4" x 8" x 8" FLAT BAR WITH 1/16" DIA. HOLES FOR ANCHOR BOLTS NO. 4.
- ⑥ 1 3/4" x 3" MOUNTING BOLT WASHER (GALVANIZED).
- ⑦ 3/8" DIA. BUTTON HEAD POST MOUNTING BOLT WITH ROUND WASHER AND NUT.
- ⑧ 3/8" DIA. x 2" HEX BOLTS WITH NUT AND TWO WASHERS EACH.
- ⑨ PLATE 1/2" x 5 3/4" x 6" AT BASIC POST CONNECTION. 1/4" DIA. HOLES IN CHANNEL. 1/16" DIA. HOLES IN PLATE.
- ⑩ PLATE 1/2" x 5 3/4" x 11 1/2". 1/4" DIA. HOLES IN PLATE. 1/16" DIA. HOLES IN CHANNEL. EXPANSION SLOTS ON JOINT SIDE OF POST. 1/4" x 2 1/2" IN PLATE. 3/16" x 2 1/4" IN CHANNEL. (AT EXPANSION SPLICE.)
- ⑪ PLATE 1/2" x 5 3/4" x 11 1/2". 1/4" DIA. HOLES IN PLATE. 1/16" DIA. HOLES IN CHANNEL. (AT TYPICAL SPLICE.)

GENERAL NOTES

BID ITEM SHALL BE "RAILING STEEL TYPE W B--" WHICH INCLUDES ALL ITEMS SHOWN.

POST BASE PLATES SHALL BE FLAT WITH ALL SURFACES SMOOTH AND FREE FROM WARP AND ALL EDGES SMOOTH, STRAIGHT AND VERTICAL. ALL PLATE CUTS SHALL BE MACHINE OR MACHINE FLAME CUTS.

ALL MATERIAL EXCEPT ANCHORAGE DETAIL NO. 5 SHALL BE GALVANIZED AFTER FABRICATION.

PRIOR TO GALVANIZING, ALL STEEL RAILING POSTS AND CHANNELS SHALL BE GIVEN A NO. 6 COMMERCIAL BLAST CLEANING BY SSPC SPEC.

ALL MATERIAL USED IN FABRICATION SHALL BE MADE FROM MATERIALS CONFORMING TO ASTM DESIGNATION A709 GRADE 36 UNLESS NOTED OTHERWISE.

FILL BOLT SLOT OPENINGS IN POST SHIMS & PLATE NO. 3 WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.


SEE STANDARD SPECIFICATIONS FOR RAIL TYPE.

CHANNEL MEMBER SHALL BE ATTACHED CONTINUOUSLY TO A MINIMUM OF FOUR POSTS AND A MAXIMUM OF EIGHT (EXCEPT AT ABUTMENTS).


AT EXPANSION SLOTS IN RAIL AND CHANNEL MEMBERS, TIGHTEN BOLTS, BACK OFF ONE HALF TURN AND BURR THREADS. RAIL MEMBERS SHALL BE LAPPED IN THE DIRECTION OF TRAFFIC AND THE UPPER RAIL SHALL LAP THE LOWER RAIL.

STEEL POST SHIMS MAY BE USED UNDER POSTS WHERE REOD. FOR ALIGNMENT.


SEE BRIDGE MANUAL 30.2 FOR ALLOWED USE.




SECTION THRU RAILING




SECTION B-B



RAIL MEMBER SPLICE




POST SHIM DETAIL
4 PER POST




BASIC POST CONNECTION

OPTIONAL SHOP SPLICE



ANCHORAGE DETAIL




EXPANSION SPLICE


TYPICAL SPLICE

CHANNEL MEMBER DETAILS
SHIM PLATES 6" x 1/16" x 6" MAY BE USED BETWEEN TOP OF POST AND CHANNEL MEMBER TO ACHIEVE VERT. ALIGNMENT.


STEEL RAILING TYPE 'W'	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 7-14




ALUMINUM POST CASTING




RAIL SPLICE DETAIL



SECTION R1




SLEEVE DETAIL AT ABUTMENT




DETAIL AT RAIL OPENINGS

ALL SLEEVE DETAILS SAME AS "RAIL SPLICE DETAIL" UNLESS SHOWN OTHERWISE




DETAIL OF ATTACHMENT TO POST


NOTES: MAX. REDUCTION IN DIAMETER OF BENT SECTION SHALL BE 3%. WALL THICKNESS OF TUBING SHOWN ABOVE SHALL BE MIN. NOMINAL AVERAGE WALL THICKNESS. MAX. REDUCTION IN SLOT WIDTH IN BENT TUBING SHALL BE 1/8%.




DETAIL OF RAIL BEND AT ABUTMENTS




END PLATE




ANCHOR BOLTS AT END PLATE



END PLATE SHIM DETAILS



ANCHOR BOLTS AT POSTS




POST SHIM DETAILS

GENERAL NOTES






- BID ITEM SHALL BE "RAILING TUBULAR TYPE H B - ..." WHICH INCLUDES ALL ITEMS SHOWN.
- SHIMS SHALL CONFORM TO SAME MATERIAL AS POSTS.
- ANCHOR BOLTS, NUTS AND WASHERS SHALL BE STAINLESS STEEL.
- RAILINGS SHALL BE FABRICATED IN 2 AND 3 PANEL LENGTHS.
- RAILING POSTS SHALL BE SET NORMAL TO GRADE LINE.
- ALL POST SPACINGS ARE MEASURED HORIZONTALLY ALONG CENTERLINE OF THE POST BASE.
- SHIMS SHALL BE USED UNDER POSTS AND END PLATES WHERE RECD. FOR ALIGNMENT.
- FILL ALL EXPOSED OPENINGS BETWEEN SHIMS AND POST ANCHOR BOLT HOLES WITH NON-STAINING GRAY NON-BITUMINOUS JOINT SEALER.
- RAILS SHALL BE BUILT STRAIGHT AND SPRUNG INTO PLACE FOR STRUCTURES CURVED UP TO 3°. FOR STRUCTURES CURVED GREATER THAN 3°, RAILS SHALL BE CURVED TO FIT.

RAILING WEIGHT = 20 LB/FT



RAIL CLOSURE CAP DETAIL

TUBULAR RAILING TYPE 'H' (ALUM.)	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <i>Bill Oliva</i>	DATE: 7-14



DESIGNER NOTES


'325S' PARAPET SHOWN IN THIS STANDARD. FOR DETAILS, INCLUDING REINFORCING, SEE STANDARD 30.30. SEE STANDARDS 30.31, 30.32, AND 30.33 FOR SIMILAR DETAILS USED WITH OTHER PARAPET TYPES.

ALL PARAPET FOOTING BARS SHALL BE EPOXY COATED.

DO NOT SHOW THE ADHESIVE ANCHOR CONNECTION DETAIL ON THE PLAN. THE CONTRACTOR MAY REQUEST THIS DETAIL IF DESIRED.


- STEEL TROWEL HORIZONTAL SURFACE OF PAVING NOTCH. PLACE MULTIPLE LAYERS OF POLYETHYLENE SHEETS BETWEEN PARAPET FOOTING AND HORIZONTAL SURFACE OF PAVING NOTCH. TOTAL THICKNESS OF SHEETS SHALL BE AT LEAST 0.03".

PARAPET FOOTING	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION STRUCTURES DEVELOPMENT SECTION	
APPROVED: <u>Bill Oliva</u>	DATE: 7-14




INSIDE ELEVATION


AVOID PLACING A BENCH MARK CAP BELOW A RAIL OR FENCE SYSTEM THAT IS ATTACHED TO THE TOP OF THE PARAPET.



SECTION A



SECTION B



SECTION C

LENGTH SHOWN FOR BAR IS AN AVERAGE LENGTH AND SHOULD ONLY BE USED FOR BAR WEIGHT CALCULATIONS. SEE BAR SERIES TABLE FOR ACTUAL LENGTHS.


BILL OF BARS FOR ABUTMENT PARAPETS

BAR MARK	Qty	ABUT.	ABUT.	LENGTH	BEV.	BAR SERIES	LOCATION
R501	X			4'-7"	X		PARAPET VERT.
R502	X			2'-4"	X		PARAPET VERT.
R503	X			4'-7"	X		PARAPET VERT.
R804	X						PARAPET HORIZ.
R505	X			6'-6"	X		PARAPET VERT.
R506	X				X		PARAPET HORIZ.
R507	X			5'-8"	X		PARAPET VERT.
R808	X				X		PARAPET HORIZ.
S501	X			4'-5"	X		PARAPET VERT.
S502	X			2'-4"	X		PARAPET VERT.
S503	X			4'-2"	X		PARAPET VERT.

BAR SERIES TABLE

MARK	NO. REOD.	LENGTH
R507	4 SERIES OF 6	4'-10" TO 6'-6"

ROADWAY OPENING OR 2 1/2" MIN. FOR EXPANSION JOINT. USE 1/2" OPENING WITH FILLER FOR A1 ABUTMENTS





PLAN


EXPANSION JOINT @ ABUT. 0° SKEW SHOWN. MATCH EXP. JT. OPENING.

FOR TYPE A1 ABUT., USE 1/2" FILLER TO TOP OF PARAPET. SEE STD. 12.01.


OPTIONAL CONSTRUCTION JOINTS IN THE PARAPETS MAY BE USED. RUN BAR REINF. THRU THE JOINT. LAP LONGIT. BARS A MIN. OF 3'-5". MIN. JOINT SPACING OF 80'-0". DEFINE CONST. JOINT WITH A 3/4" - 1" GROOVE.



BARS FOR TRANSITION ON BRIDGE



OUTSIDE ELEVATION



SECTION THRU PARAPET ON BRIDGE

AREA = 3.16 SF
WEIGHT = 474 LB/FT

CONST. JOINT - STRIKE OFF AS SHOWN.

R502 BARS MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. USE CARE TO PLACE R502 OR S502 BARS CORRECTLY ALONG TRANSITION OF PARAPET.

R501 AND R503 BARS TO BE TIED TO WING STEEL BEFORE WING IS POURED.

A R503 BAR MAY BE USED IN LIEU OF A S503 BAR ADJACENT TO THE PAVING NOTCH ON TYPE A1 ABUTMENTS.


SLOPED FACE PARAPET 'HF'

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: *Bill Oliva*


DATE:
7-14

AVOID PLACING A BENCH MARK CAP BELOW A RAIL OR FENCE SYSTEM THAT IS ATTACHED TO THE TOP OF THE PARAPET.



INSIDE ELEVATION


ROADWAY OPENING OR 2 1/2" MIN. FOR EXPANSION JOINT. USE 1/2" OPENING WITH FILLER FOR A1 ABUTMENTS



SECTION A

BILL OF BARS FOR ABUTMENT PARAPETS


BAR MARK	CO ₂ S	ABUT.	ABUT.	LENGTH	REIN.	LOCATION
R501	X			4'-6"	X	PARAPET VERT.
R502	X			7'-11"	X	PARAPET VERT.
R803	X					PARAPET HORIZ.
S5	X			4'-2"	X	PARAPET VERT.
S5	X			7'-11"	X	PARAPET VERT.
S8	X					PARAPET HORIZ.



R501


R502/S5

S5




PLAN


EXPANSION JOINT @ ABUT. 0° SKEW SHOWN. MATCH EXP. JT. OPENING.
 FOR TYPE A1 ABUT., USE 1/2" FILLER TO TOP OF PARAPET. SEE STD. 12.01.
 OPTIONAL CONSTRUCTION JOINTS IN THE PARAPETS MAY BE USED. RUN BAR REINF. THRU THE JOINT. LAP LONGIT. BARS A MIN. OF 3'-5". MIN. JOINT SPACING OF 80'-0". DEFINE CONST. JOINT WITH A 1/4" - V GROOVE.



OUTSIDE ELEVATION



SECTION THRU PARAPET ON BRIDGE




SLOPED FACE PARAPET "51F" MAY BE USED IN MEDIAN AREA OF ADJACENT STRUCTURES WHEN HIGHWAY MEDIAN APPROACH CONCRETE BARRIER IS 51" HIGH

- CONST. JOINT - STRIKE OFF AS SHOWN.
- A R501 BAR MAY BE USED IN LIEU OF A TYPICAL S5... BAR ADJACENT TO THE PAVING NOTCH ON TYPE A1 ABUTMENTS.
- AREA = 3.41 FT²
- WEIGHT = 512 LBS./FT.

SLOPED FACE PARAPET '51F'

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 7-14




INSIDE ELEVATION

◆ ROADWAY OPENING OR 2 1/2" MIN. FOR EXPANSION JOINT. USE 1/2" OPENING WITH FILLER FOR AI ABUTMENTS

■ BENCH MARK CAP (WHEN SUPPLIED). AVOID PLACING A BENCH MARK CAP BELOW A RAIL OR FENCE SYSTEM THAT IS ATTACHED TO THE TOP OF THE PARAPET.

NOTE: FOR SECTIONS A, B & C ONLY THE PARAPET TERMINATING ON A WING IS SHOWN. TERMINATION ON A DECK IS SIMILAR.




SECTION A SECTION B SECTION C


BILL OF BARS

FOR ABUTMENT PARAPETS


BAR MARK	Qty	ABUT.	ABUT.	LENGTH	BENT	LOCATION
R501	X			5-10	X	PARAPET-VERT.
R502	X			5-0	X	PARAPET-VERT.
R503	X			3-0	X	PARAPET-VERT.
R504	X			5-7	X	PARAPET-VERT.
R505	X			4-9	X	PARAPET-VERT.
R506	X			4-10	X	PARAPET-VERT.
R507	X				X	PARAPET-HORIZ.
R508	X					PARAPET-HORIZ.
S501	X			4-5	X	PARAPET-VERT.
S503	X			2-9	X	PARAPET-VERT.
S504	X			4-4	X	PARAPET-VERT.




PLAN




R501 R502 R503 R504 R505 R506 R507



OUTSIDE ELEVATION



SECTION THRU PARAPET ON BRIDGE



BARS FOR TRANSITION ON BRIDGE

AREA = 3.09 SF
WEIGHT = 464 LB/FT

● CONST. JOINT - STRIKE OFF AS SHOWN.


■ R503 BARS MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. USE CARE TO PLACE R503 OR S503 BARS CORRECTLY ALONG TRANSITION OF PARAPET.

▽ R501 AND R504 BARS TO BE TIED TO WING STEEL BEFORE WING IS POURED. DESIGNER MAY ELECT TO USE A R501 BAR IN LIEU OF A S501 BAR ADJACENT TO THE PAVING NOTCH ON TYPE AI ABUTMENTS.

SINGLE SLOPE PARAPET 32SS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva DATE: 7-14




INSIDE ELEVATION

◆ ROADWAY OPENING OR 2 1/2" MIN. FOR EXPANSION JOINT. USE 1/2" OPENING WITH FILLER FOR A1 ABUTMENTS




PLAN



OUTSIDE ELEVATION

■ BENCH MARK CAP (WHEN SUPPLIED). AVOID PLACING A BENCH MARK CAP BELOW A RAIL OR FENCE SYSTEM THAT IS ATTACHED TO THE TOP OF THE PARAPET.

NOTE: FOR SECTIONS A, B & C ONLY THE PARAPET TERMINATING ON A WING IS SHOWN. TERMINATION ON A DECK IS SIMILAR.



SECTION A

SECTION B


SECTION C

BILL OF BARS

FOR ABUTMENT PARAPETS

BAR MARK	COUPLER	ABUT.	ABUT.	LENGTH	BENT	LOCATION
R501	X			5-10	X	PARAPET-VERT.
R502	X			5-8	X	PARAPET-VERT.
R503	X			3-0	X	PARAPET-VERT.
R504	X			5-7	X	PARAPET-VERT.
R505	X			5-5	X	PARAPET-VERT.
R506	X			5-6	X	PARAPET-VERT.
R507	X				X	PARAPET-HORIZ.
R508	X				X	PARAPET-HORIZ.
R509	X			4-9	X	PARAPET-VERT.
R510	X				X	PARAPET-HORIZ.
S501	X			4-5	X	PARAPET-VERT.
S503	X			2-9	X	PARAPET-VERT.
S504	X			4-4	X	PARAPET-VERT.

OPTIONAL CONSTRUCTION JOINTS IN THE PARAPETS MAY BE USED. RUN BAR REINF. THRU THE JOINT. LAP LONGIT. BARS A MIN. OF 1'-9". MIN. JOINT SPACING OF 80'-0". DEFINE CONST. JOINT WITH A 3/4" V-GROOVE.



R501

R502

R503

R504


R505

R506


R507

R510

R509



SECTION THRU PARAPET ON BRIDGE



AREA = 3.36 SF
WEIGHT = 504 LB/FT

● CONST. JOINT - STRIKE OFF AS SHOWN.

■ R503 BARS MAY BE PLACED AFTER CONCRETE IS POURED BUT BEFORE INITIAL SET HAS TAKEN PLACE. USE CARE TO PLACE R503 OR S503 BARS CORRECTLY ALONG TRANSITION OF PARAPET.


▽ R501 AND R504 BARS TO BE TIED TO WING STEEL BEFORE WING IS POURED. DESIGNER MAY ELECT TO USE A R501 BAR IN LIEU OF A S501 BAR ADJACENT TO THE PAVING NOTCH ON TYPE A1 ABUTMENTS.

SINGLE SLOPE PARAPET 36SS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: *Bill Oliva*

DATE:
7-14



APRON DETAIL



SECTION C6


"H" (FT.)	"L" (FT.)
≤ 5'-0"	3'-8"
> 5'-0" - 7'-0"	5'-2"
> 7'-0" - 8'-0"	6'-1"
> 8'-0" - 9'-0"	6'-9"
> 9'-0" - 10'-0"	7'-4"
> 10'-0" - 11'-0"	7'-8"
> 11'-0" - 12'-0"	8'-0"
> 12'-0" - 13'-0"	8'-4"
> 13'-0" - 14'-0"	8'-6"

"H" IS MAX. WING WALL HEIGHT

THE AREA OF REINFORCING STEEL NOT IDENTIFIED IN SECTIONS SHALL CONFORM TO THE FOLLOWING TEMPERATURE AND SHRINKAGE REQUIREMENTS:


THICKNESS	T&S REINF.
≤ 12"	#4 @ 18"
> 12" - 18"	#4 @ 12"

▲ IN LIEU OF CONSTRUCTION JOINTS IN THE BOTTOM SLAB, THE CONTRACTOR MAY USE 2" DEEP SAW CUTS WITHIN 12 HOURS AFTER POURING.




CORNER "A"


* DIMENSION "T" TO BE DETERMINED FROM BARREL DESIGN



CORNER "B"




VERTICAL CONSTRUCTION JOINT



ALTERNATE SECTION C6

SHEET PILING (MIN. WEB THICKNESS 5/16")
PAYMENT BASED ON CONCRETE CUT OFF WALL.

ALTERNATE CUTOFF WALL



SECTION THRU WINGWALLS

□ 18" MIN. WIDTH RUBBERIZED MEMBRANE WATERPROOFING ALONG HORIZ. CONST. JT. IN WING.

NOTES

BAR STEEL REINFORCEMENT SHALL BE EMBEDDED 2" CLEAR UNLESS OTHERWISE SHOWN OR NOTED.

THE UPPER LIMITS OF "EXCAVATION FOR STRUCTURES CULVERTS C-..." SHALL BE THE EXISTING GROUND LINE.

STRUCTURE BACKFILL IS REQUIRED BEHIND ALL WINGWALLS.

WHEN STRUCTURE BACKFILL IS REQUIRED: ALL SPACES EXCAVATED AND NOT OCCUPIED BY THE NEW STRUCTURE SHALL BE BACKFILLED WITH STRUCTURE BACKFILL TO THE ELEVATION AND SECTION EXISTING PRIOR TO EXCAVATION WITHIN THE LENGTH OF THE BOX.

THE CONCRETE IN THE CUT OFF WALL MAY BE PLACED UNDERWATER IF THE EXCAVATION CANNOT BE DEWATERED.

THE ALTERNATE CUT OFF WALL MAY BE USED IN LIEU OF THE CAST-IN-PLACE CONCRETE CUT OFF WALLS. PAYMENT SHALL BE BASED ON CONCRETE CUT OFF WALLS.

LOCATE NAME PLATE ON NEAREST RIGHT WING TRAVELING UP STATION, FACE NAME PLATE UP STATION.

THE CONTRACTOR MAY FURNISH A PRECAST CONCRETE BOX CULVERT IN LIEU OF THE CAST-IN-PLACE BOX CULVERT WITH THE ACCEPTANCE OF THE SHOP DRAWINGS BY THE STRUCTURES DESIGN SECTION. THE PRECAST CONCRETE BOX CULVERT SHALL CONFORM TO PRECAST DETAILS IN CHAPTER 36 STANDARDS OF THE CURRENT WISCONSIN DOT BRIDGE MANUAL. PAYMENT FOR THE PRECAST CULVERT SHALL BE BASED ON THE QUANTITIES AND PRICES BID FOR THE ITEMS LISTED IN THE "TOTAL ESTIMATED QUANTITIES".

IN LIEU OF USING BREAKER RUN FOR THE BOX CONSTRUCTION PLATFORM, THE CONTRACTOR MAY ELECT TO SUBSTITUTE #1 OR #2 CONCRETE COARSE AGGREGATE. SELECT CRUSHED MATERIAL OR OTHER GRANULAR MATERIAL AS APPROVED BY THE ENGINEER. THE CONTRACTOR IS RESPONSIBLE FOR BASE STABILITY WITH ANY SUBSTITUTED MATERIAL. THE REGION GEOTECHNICAL ENGINEER MAY BE CONTACTED TO DETERMINE IF "OTHER GRANULAR MATERIAL" IS ACCEPTABLE.

DESIGNER NOTES

THE ABOVE NOTE REGARDING POTENTIAL SUBSTITUTION OF BREAKER RUN SHOULD ONLY BE INCLUDED ON THE PLANS IF ALLOWED BY THE REGION GEOTECHNICAL ENGINEER.

ALL BAR STEEL FOR CAST-IN-PLACE CONCRETE BOX CULVERTS SHALL BE UNCOATED, EXCEPT WHEN THERE IS NO FILL OVER THE CULVERT. EPOXY COATED BARS SHALL BE USED FOR THE TOP AND BOTTOM BARS IN THE TOP SLAB.


FOR "B" DESIGNATED CONCRETE BOX CULVERTS HAVING THEIR TOP SURFACE AT GRADE, HAND HELD FINISHING MACHINES MAY BE USED. NOTE THIS ON PLANS WHEN APPLICABLE.

BOX CULVERT APRON DETAILS


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: *Bill Oliva*

DATE:
7-14




PLAN




SECTION C2 FOR SKEW OF 20° AND UNDER

OUTLET HEADERS SHOWN



SECTION C2 FOR SKEW OVER 20°

† IF RAILING POSTS ARE ATTACHED TO HEADER THIS DIMENSION MAY BE INCREASED IF NECESSARY TO KEEP RAILING PARALLEL TO ROADWAY. INCREASE WING HEIGHT IF NECESSARY.




SECTION C3

TYPICAL ALL INLETS


* HEADER LENGTH	"A" BARS
TO 11'-0"	6 - #7
OVER 11'-0" - 14'-0"	6 - #8
OVER 14'-0" - 17'-0"	6 - #9
OVER 17'-0" - 20'-0"	6 - #10

* HEADER LENGTH EQUALS THE DISTANCE BETWEEN C. OF WALLS IN ONE CELL MEASURED ALONG THE SKEW.




ELEVATION

INLET NOSE CENTERWALL DETAILS




SECTION C4



SECTION C5

NOTE:
FOR MULTI-CELL CULVERTS, IN THE TOP OF THE TOP SLAB USE A MINIMUM OF #4 BARS AT 1'-0" IN THE LONGITUDINAL DIRECTION AND A MIN. OF #4 BARS AT 1'-0" IN THE TRANSVERSE DIRECTION WHEN THE TOP SLAB HAS NO FILL PLACED ON IT.




SECTION THRU BOX

**BOX CULVERT
DETAILS**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
7-14




14'-0" SPAN

RISE = 10'-0" **SEE NOTE



20'-0" SPAN

RISE = 10'-0" **SEE NOTE



24'-0" SPAN

RISE = 10'-0" **SEE NOTE

NOTES:

** SEE ARCH UNIT PRIMARY REINFORCING CHART ON STANDARD 36.15 FOR MORE INFORMATION.

ALL REINFORCING DIMENSIONS SHOWN ARE FOR 10'-0" RISE. A2 AND A3 STEEL LENGTHS SHALL BE REVISED ACCORDINGLY FOR RISES OTHER THAN 10'-0".

THESE STEEL AREAS, STEEL LENGTHS AND ARCH THICKNESS ARE SHOWN FOR COVER OF 12'-0" OR LESS.

THREE-SIDED PRECAST CONCRETE STRUCTURES SHALL BE DESIGNED FOR COVER GREATER THAN 12'-0", AND CAN BE DESIGNED FOR UP TO THE LIMITS OF COVER SHOWN IN THE TABLE BELOW.

THE COVER OF CONCRETE OVER THE OUTSIDE CIRCUMFERENTIAL REINFORCEMENT SHALL BE 2 INCHES MINIMUM.

THE COVER OF CONCRETE OVER THE INSIDE CIRCUMFERENTIAL REINFORCEMENT SHALL BE 1/2 INCHES MINIMUM.

THE CLEAR DISTANCE OF THE END CIRCUMFERENTIAL WIRES SHALL NOT BE LESS THAN 1" NOR MORE THAN 2" FROM THE ENDS OF EACH SECTION.


AN ALTERNATE EQUIVALENT OF WELDED WIRE FABRIC (WWF) ASTM A497 MAY BE SUBSTITUTED FOR THE REINFORCEMENT SHOWN, UPON APPROVAL OF THE STRUCTURES DEVELOPMENT SECTION.

MINIMUM COVER FOR WILDED WIRE FABRIC: 1-INCH

DESIGN DATA:


f'c = 5000 PSI MINIMUM FOR CONCRETE
 fy = 60,000 PSI FOR STEEL REINFORCING BARS
 fy = 65,000 PSI FOR WELDED WIRE FABRIC (IN FLAT SHEET)

SPAN FT	APPROX. MAX. COVER
14'	50"
20' - 24'	30"
28' - 36'	20"
42'	15"




28'-0" SPAN

RISE = 10'-0"



36'-0" SPAN

RISE = 10'-0"



42'-0" SPAN

RISE = 12'-0"

ARCH UNIT LONGITUDINAL REINFORCEMENT (MINIMUM)							
14'-0" SPAN			20'-0" SPAN			24'-0" SPAN	
CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT	LENGTH FT	CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT	LENGTH FT	CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT
A1 = **	0.13	10'-6"	A1 = **	0.13	15'-0"	A1 = **	0.13
A2 = 0.24	0.13	12'-3"	A2 = 0.24	0.13	12'-5"	A2 = 0.24	0.13
A3 = **	0.13	15'-4"	A3 = **	0.13	16'-3"	A3 = **	0.13
A4 = 0.24	0.13	5'-9"	A4 = 0.24	0.13	9'-3"	A4 = 0.24	0.13


28'-0" SPAN			36'-0" SPAN			42'-0" SPAN		
CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT	LENGTH FT	CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT	LENGTH FT	CIRCUMF. AREA REQ'D SQ. IN./FT	LONGITUDINAL AREA REQ'D SQ. IN./FT	LENGTH FT
A1A = **	0.13	22'-0"	A1A = **	0.13	26'-0"	A1A = **	0.13	31'-0"
A1B = **	NOT REQ'D	16'-0"	A1B = **	NOT REQ'D	18'-0"	A1B = **	NOT REQ'D	23'-0"
A2 = 0.36	0.13	12'-6"	A2 = 0.36	0.13	13'-2"	A2 = 0.48	0.13	14'-4"
A3A = **	0.13	17'-6"	A3A = **	0.13	19'-8"	A3A = **	0.13	21'-9"
A3B = **	NOT REQ'D	13'-6"	A3B = **	NOT REQ'D	15'-8"	A3B = **	NOT REQ'D	17'-9"
A4 = 0.36	0.13	14'-3"	A4 = 0.36	0.13	16'-0"	A4 = 0.48	0.13	20'-0"
A5 = 0.24	0.13	7'-10"	A5 = 0.24	0.13	7'-10"	A5 = 0.24	0.13	7'-10"

PRECAST THREE-SIDED BOX CULVERT REINFORCEMENT

STATE OF WISCONSIN
 DEPARTMENT OF TRANSPORTATION
 STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
7-14



CROSS SECT. THRU RDWY.

LOOKING -----



PLAN

DESIGNER NOTES

FOR CROSS SECTIONS NOT IN SUPERELEVATION TRANSITIONS THE PREFERRED MINIMUM SLOPE IS 2%.

PROVIDE AN AVERAGE OVERLAY THICKNESS ON THE PLANS. THIS OVERLAY THICKNESS SHOULD BE BASED ON 2" MIN. ABOVE THE DECK SURFACE AFTER ALL PREPARATION (3/8" FOR THIN BONDED POLYMER OVERLAYS), DIFFERENCES IN PROPOSED CROSS SLOPE VS. EXISTING CROSS SLOPE, ETC. BASED ON ORIGINAL STRUCTURE PLANS.

DO NOT PROVIDE A PROFILE GRADE LINE ON THE PLANS.

☆ POLYMER MODIFIED ASPHALTIC OVERLAYS NOT REQUIRING SHEET MEMBRANE WATERPROOFING ARE THE PREFERRED ASPHALTIC OVERLAY TYPE. WHERE POLYMER MODIFIED ASPHALTIC MATERIAL IS NOT AVAILABLE, DESIGNER TO UTILIZE ASPHALTIC OVERLAY WITH SHEET MEMBRANE WATERPROOFING. DESIGNER TO CONTACT THE BUREAU OF STRUCTURES DEVELOPMENT SECTION TO DETERMINE IF POLYMER MODIFIED ASPHALTIC MATERIAL IS AVAILABLE.

NOTE:
CONCRETE OVERLAYS ARE THE CURRENT PREFERRED METHOD TO OVERLAY A BRIDGE.

NOTES

DRAWINGS SHALL NOT BE SCALED.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.

UNDER THE BID ITEM "MASONRY ANCHORS TYPE S -INCH", ANCHORED REINFORCING STEEL SHALL BE PAID FOR SEPARATELY AS PROVIDED IN SECTION 505 OF THE STANDARD SPECIFICATIONS FOR BAR STEEL REINFORCEMENT.

A MIN. OF 1-INCH OF CONCRETE SHALL BE REMOVED FROM THE ENTIRE BRIDGE DECK UNDER THE BID ITEM "CLEANING DECKS".

ANY EXCAVATION REQ'D TO COMPLETE THE OVERLAY OR THE PAVING BLOCK AT ABUTS. IS INCIDENTAL TO THE BID ITEM " (OVERLAY TYPE) ".

PROFILE GRADE LINE SHALL BE DETERMINED IN THE FIELD BASED ON A MINIMUM OVERLAY THICKNESS OF 1/2" PLACED ABOVE THE FINAL DECK SURFACE AFTER ALL PREPARATION. EXPECTED AVERAGE OVERLAY THICKNESS IS 2" (OR AS GIVEN ON THE PLANS). IF EXPECTED AVERAGE OVERLAY THICKNESS IS EXCEEDED BY MORE THAN 1/2", CONTACT THE STRUCTURES DESIGN SECTION.

DESIGN DATA

LIVE LOAD:

INVENTORY RATING: HS-
OPERATIONAL RATING: HS -
MAXIMUM STANDARD PERMIT VEHICLE LOAD = ... Kips

ULTIMATE DESIGN STRESSES:

CONCRETE MASONRY SUPERSTRUCTURE f'c = 4,000 P.S.I.

TOTAL ESTIMATED QUANTITIES

BID ITEM NUMBER	BID ITEMS	UNIT	TOTAL
☆ 455.0105	ASPHALTIC MATERIAL ..	TON	
☆ 460.1100	HMA PAVEMENT TYPE ..	TON	
509.5100.S	POLYMER OVERLAY	SY	
☆ 516.0600.S	SHEET MEMBRANE WATERPROOFING	SY	
SPV.0195	POLYMER MODIFIED ASPHALT OVERLAY	TON	
	POSSIBLE ADDITIONAL BID ITEMS		
502.3100	EXPANSION DEVICE B- -.	LS	
502.50..	MASONRY ANCHORS TYPE L NO. . BARS	EACH	
502.61..	MASONRY ANCHORS TYPE S -INCH	EACH	
505.0405	BAR STEEL REINFORCEMENT HS COATED BRIDGES	LB	
509.0301	PREPARATION DECKS TYPE 1	SY	
509.0302	PREPARATION DECKS TYPE 2	SY	
509.1000	JOINT REPAIR	SY	
509.1200	CURB REPAIR	LF	
509.2000	FULL-DEPTH DECK REPAIR	SY	
509.2500	CONCRETE MASONRY OVERLAY DECKS	CY	
509.9005.S	REMOVING CONCRETE MASONRY DECK OVERLAY	SY	
509.9020.S	EPOXY CRACK SEALING	LF	
514.0900	ADJUSTING FLOOR DRAINS	EACH	
SPV.0090	SAWING PAVEMENT DECK PREPARATION AREAS	LF	
SPV.0035	CONCRETE MASONRY DECK PATCHING	CY	


THIS IS A PARTIAL LIST OF POSSIBLE BID ITEMS. BID ITEMS MAY NEED TO BE ADDED OR REMOVED TO FIT EACH INDIVIDUAL CASE.

ASPHALTIC & POLYMER OVERLAYS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION


APPROVED: Bill Oliva

DATE:
7-14



CONCRETE BEARING BLOCK DETAILS

(MAY BE USED IN LIEU OF PLATE 'E' AS SHOWN ON STD. 40.08)



PRECAST CONCRETE BLOCK DETAIL

DEPTH = MIN. 5", MAX. 1'-0" *


ANCHOR IN AT LEAST 4 LOCATIONS (ANCHORS INCLUDE EPOXY ANCHORS, ANCHOR BOLTS OR COMBINATION).

GROUT 1/4" BENEATH PRECAST ELEMENT - ELIMINATE STRESS CONCENTRATION AND REDUCE CRACKING.

PRECAST BLOCK (OR ANY CONCRETE BLOCK) MUST EXTEND BEYOND BEARING A DISTANCE EQUAL TO, OR GREATER THAN, THE HEIGHT OF THE CONCRETE BLOCK *. THIS IS TO ACCOUNT FOR 45-DEGREE DOWNWARD AND OUTWARD STRESS DISTRIBUTION. THIS PROVISION CAN BE DISREGARDED IF A FULL-DEPTH CONCRETE DIAPHRAGM IS USED IN CONJUNCTION WITH A 1/2" THICK ELASTOMERIC PAD (FIXED SEAT).

REINFORCEMENT SHOULD BE IN BOTH DIRECTIONS UTILIZING #4 @ 1'-0" MAXIMUM SPACING.

BURN EXISTING ANCHOR BOLTS OFF FLUSH WITH BEAM SEAT.



*** ALTERNATE DETAIL**

TO BE USED FOR CASES WHERE HEIGHT EXCEEDS 1'-0" OR INSUFFICIENT EDGE DISTANCE (PRECAST OPTION SHOWN)

CONCRETE BEARING BLOCK DETAILS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION
STRUCTURES DEVELOPMENT SECTION

APPROVED: Bill Oliva

DATE:
1-14