


WKE

NOVEMBER 2021
ORDER OF SHEETS

Section No.	1	Title
Section No.	2	Typical Sections and Details
Section No.	3	Estimate of Quantities
Section No.	3	Miscellaneous Quantities
Section No.	4	Right-of-Way Plat
Section No.	5	Plan and Profile
Section No.	6	Standard Detail Drawings
Section No.	7	Sign Plates
Section No.	8	Structure Plans
Section No.	9	Computer Earthwork Data
Section No.	9	Cross Sections

TOTAL SHEETS = 26



12

DESIGN DESIGNATION

A.A.D.T.	2018	=	7,000
A.A.D.T.		=	N/A
D.H.V.		=	N/A
D.D.		=	N/A
T.		=	N/A
DESIGN SPEED		=	30 MPH
ESALS		=	N/A

CONVENTIONAL SYMBOLS

PLAN	
CORPORATE LIMITS	
PROPERTY LINE	
LOT LINE	
LIMITED HIGHWAY EASEMENT	
EXISTING RIGHT OF WAY	
PROPOSED OR NEW R/W LINE	
SLOPE INTERCEPT	
REFERENCE LINE	
EXISTING CULVERT	
PROPOSED CULVERT (Box or Pipe)	
COMBUSTIBLE FLUIDS	
MARSH AREA	
WOODED OR SHRUB AREA	

PROFILE	
GRADE LINE	
ORIGINAL GROUND	
MARSH OR ROCK PROFILE (To be noted as such)	
SPECIAL DITCH	
GRADE ELEVATION	
CULVERT (Profile View)	
UTILITIES	
ELECTRIC	
FIBER OPTIC	
GAS	
SANITARY SEWER	
STORM SEWER	
TELEPHONE	
WATER	
UTILITY PEDESTAL	
POWER POLE	
TELEPHONE POLE	

STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION

PLAN OF PROPOSED IMPROVEMENT


MADISON STREET

BRIDGE OVER FOX RIVER B-67-0099

LOCAL STREET

WAUKESHA COUNTY


STATE PROJECT NUMBER
2718-19-70



BEGIN PROJECT
STA 17+24.60
Y = 373880.203
X = 2472458.634

END PROJECT
STA 17+90.15

STRUCTURE B-67-99



TOTAL NET LENGTH OF CENTERLINE = 0.017 MI

HORIZONTAL POSITIONS SHOWN ON THIS PLAN ARE WISCONSIN COORDINATE REFERENCE SYSTEM (WISCRS), WAUKESHA COUNTY NAD83 (1991), IN U.S. SURVEY FEET. POSITIONS SHOWN ARE GRID COORDINATES, GRID BEARINGS, AND GRID DISTANCES. GRID DISTANCES ARE THE SAME AS GROUND DISTANCES.

ELEVATIONS ARE REFERENCED TO NAVD 88 (1991). GPS DERIVED ELEVATIONS ARE BASED ON GEOID 12A.

STATE PROJECT	FEDERAL PROJECT	
	PROJECT	CONTRACT
2718-19-70	WISC 2022039	1

ACCEPTED FOR
CITY OF WAUKESHA

Date: 7/30/21 *Alto Tanni*
Director of Public Works

Date: _____
City Engineer

ORIGINAL PLANS PREPARED BY
AECOM 1555 N Rivercenter Drive
Suite 214
Milwaukee, WI 53212

WISCONSIN PROFESSIONAL ENGINEER
WILLIAM R SCHILLING
E-35841-008
WAUKESHA, WI

DATE: 7/28/2021 *W R Schilling*
(Professional Engineer Signature)

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

PREPARED BY

Surveyor: CITY OF WAUKESHA
Designer: AECOM
Regional Project Manager: KATHLEEN KRAMER
Regional Supervisor: JEFF BOHEN

APPROVED FOR THE DEPARTMENT

DATE: 7/30/21 *K Kramer*
(Signature)

E

PROJECT ID: 2718-19-70

COUNTY: WAUKESHA

GENERAL NOTES

1. THE CITY OF WAUKESHA IS RECONSTRUCTING MADISON STREET AND ST. PAUL AVENUE UNDER WISDOT PROJECT ID 2718-04-01 CONCURRENTLY WITH THIS PROJECT. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH THE CITY OF WAUKESHA.
2. THERE ARE UTILITY FACILITIES WITHIN THE PROJECT AREA THAT ARE NOT SHOWN ON THE PLANS. THE CONTRACTOR SHALL COORDINATE HIS CONSTRUCTION ACTIVITIES WITH A CALL TO DIGGERS HOTLINE AND/OR A DIRECT CALL TO THE UTILITIES THAT HAVE FACILITIES IN THE AREA. NOT ALL UTILITIES ARE MEMBERS OF DIGGERS HOTLINE.
3. RADII, ELEVATIONS, AND DIMENSIONS ARE GIVEN AT THE FACE OF CURB/FLOW LINE UNLESS OTHERWISE NOTED IN THE PLANS.
4. ADJUST TRAFFIC CONTROL DEVICE LOCATIONS TO FIT FIELD CONDITIONS AS DIRECTED BY THE ENGINEER.
5. EROSION CONTROL ITEMS ARE AT SUGGESTED LOCATIONS. THE ENGINEER MAY MODIFY LOCATIONS TO FIT FIELD CONDITIONS.
6. WATERWAYS AND OTHER ENVIRONMENTALLY SENSITIVE AREAS SHALL BE PROTECTED AT ALL TIMES. DO NOT STORE EQUIPMENT OR MATERIALS NEAR THESE SITES UNLESS APPROVED BY THE ENGINEER.



UTILITY CONTACTS

TELEPHONE - AT&T WISCONSIN
 TOM CROWLEY
 2005 PEWAUKEE ROAD
 WAUKESHA, WI 53188
 PHONE: (262) 501-3499
 EMAIL: TC1657@ATT.COM

FIBER OPTIC - CHARTER
 NEAL LONG
 1320 NORTH MARTIN LUTHER KIND JR DRIVE
 MILWAUKEE, WI 53212
 PHONE: (414) 277-4271
 EMAIL: NEAL.LONG@CHARTER.COM

STORM WATER/SANITARY SEWER - CITY OF WAUKESHA DEPARTMENT OF PUBLIC WORKS
 CHRISTOPHER LANGEMAK
 130 DELAFIELD STREET
 WAUKESHA, WI 53188
 PHONE: (262) 524-3598
 EMAIL: CLANGEMAK@WAUKESHA-WI.GOV

WATER - WAUKESHA WATER UTILITY
 CHRISTOPHER WALTER
 PO BOX 1648
 WAUKESHA, WI 53187
 PHONE: (262) 521-5272
 EMAIL: CWALTER@WAUKESHA-WATER.COM

ELECTRICITY - WE ENERGIES
 ERIC KICKHAVER
 500 SOUTH 116TH STREET
 WEST ALLIS, WI 53214
 PHONE: (414) 944-5917
 EMAIL: ERIC.KICKHAVER@WE-ENERGIES.COM

GAS - WE ENERGIES
 JACOB SPENCER
 S13 W33800 STH 18
 DELAFIELD, WI 53018
 PHONE: (262) 968-7009
 EMAIL: JACOB.SPENCER@WE-ENERGIES.COM

OTHER CONTACTS

WISCONSIN DNR
 CRAIG WEBSTER
 141 NW BARSTOW STREET, ROOM 180
 WAUKESHA, WI 53188
 PHONE: (262) 574-2141
 EMAIL: CRAIG.WEBSTER@WI.GOV

CITY OF WAUKESHA - ENGINEERING DIVISION
 CRAIG AUSEN
 130 DELAFIELD STREET
 WAUKESHA, WI 53188
 PHONE: (262) 524-3589
 CAUSEN@WAUKESHA-WI.GOV


WAUKESHA METRO
 BRIAN ENGELKING
 2311 BADGER DRIVE
 WAUKESHA, WI 53188
 PHONE: (262) 524-3634
 BENGELKI@CI.WAUKESHA.WI.US


STREET LIGHTING - CITY OF WAUKESHA DEPARTMENT OF PUBLIC WORKS
 JEFF HERNKE
 201 DELAFIELD STREET
 WAUKESHA, WI 53188
 PHONE: (262) 524-3592
 EMAIL: JHERNKE@WAUKESHA-WI.GOV

ORDER OF SECTION 2 SHEETS

- GENERAL NOTES/ALIGNMENT DIAGRAM
- PROJECT OVERVIEW
- CONSTRUCTION DETAILS
- EROSION CONTROL
- TRAFFIC CONTROL

CURVE 1
 PI STA = 15+79.92
 Y = 373933.965
 X = 2472324.119
 DELTA = 11°08'15"
 D = 19°05'55"
 T = 29.25'
 L = 58.32'
 R = 300.00'
 PC STA = 15+50.67
 PT STA = 16+08.99





PROJECT NO: 2718-19-70


HWY: LOCAL

COUNTY: WAUKESHA

PROJECT OVERVIEW


SHEET

E




LEGEND

- REMOVING ASPHALT PAVEMENT (PAID FOR AS EXCAVATION COMMON)
- REMOVING CURB & GUTTER
- AAA** SAWING ASPHALT
- XXX** SAWING CONCRETE






LEGEND

 INLET PROTECTION TYPE C

- NOTES:
1. TRAFFIC CONTROL DEVICES FOR MADISON STREET MAINLINE CLOSURES AND PEDESTRIAN DETOURS WEST OF BRIDGE, BY OTHERS.
 2. TRAFFIC CONTROL FOR ADVANCED WARNING ALONG CLINTON STREET AND BANK STREET SHALL FOLLOW STANDARD DETAIL DRAWING "BARRICADES AND SIGNS FOR SIDEROAD CLOSURES, DETAIL 2".
 3. TRAFFIC CONTROL FOR ADVANCED WARNING ALONG WEST BROADWAY AND RIVERFRONT STREET SHALL FOLLOW STANDARD DETAIL DRAWING "BARRICADES AND SIGNS FOR MAINLINE CLOSURES, DETAIL C."
 4. TRAFFIC CONTROL FOR THE PEDESTRIAN DETOUR ROUTE SHALL FOLLOW STANDARD DETAIL DRAWING "TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION".

1 ROAD CLOSED AHEAD W20-5A	2 ROAD CLOSED 500 FT W20-5D	3 ROAD WORK AHEAD W20-1A	4 ROAD CLOSED R11-2 48"x30"	5 END ROAD WORK G20-2A 48"x24"
6 SIDEWALK CLOSED R9-9 24"x12"	7 DETOUR M4-9BR 30"x24"	8 DETOUR M4-9BL 30"x24"	9 DETOUR AHEAD M4-9BA 30"x24"	10 R9-11 24"x12"



LEGEND

↑	TYPE III BARRICADE WITH ONE TYPE "A" WARNING LIGHT (FLASHING)
↑↓	TYPE III BARRICADE WITH ATTACHED SIGN WITH TWO TYPE "A" WARNING LIGHTS (FLASHING)
↑↓	TYPE II BARRICADE WITH ATTACHED SIGN WITH ONE TYPE "A" WARNING LIGHT (FLASHING)
↑↓	SIGN ON PERMANENT SUPPORT
●	TRAFFIC CONTROL DRUM
▨	WORK AREA
---	PEDESTRIAN DETOUR ROUTE

Estimate Of Quantities

2718-19-70

Line	Item	Item Description	Unit	Total	Qty
0002	204.0150	Removing Curb & Gutter	LF	50.000	50.000
0004	205.0100	Excavation Common	CY	70.000	70.000
0006	213.0100	Finishing Roadway (project) 01. 2718-19-70	EACH	1.000	1.000
0008	305.0120	Base Aggregate Dense 1 1/4-Inch	TON	60.000	60.000
0010	415.0410	Concrete Pavement Approach Slab	SY	125.000	125.000
0012	502.3200	Protective Surface Treatment	SY	364.000	364.000
0014	502.3215	Protective Surface Treatment Reseal	SY	121.000	121.000
0016	509.0301	Preparation Decks Type 1	SY	45.000	45.000
0018	509.0302	Preparation Decks Type 2	SY	7.000	7.000
0020	509.0500	Cleaning Decks	SY	364.000	364.000
0022	509.1200	Curb Repair	LF	27.000	27.000
0024	509.1500	Concrete Surface Repair	SF	30.000	30.000
0026	509.2000	Full-Depth Deck Repair	SY	2.000	2.000
0028	509.2500	Concrete Masonry Overlay Decks	CY	23.000	23.000
0030	601.0409	Concrete Curb & Gutter 30-Inch Type A	LF	50.000	50.000
0032	611.8115	Adjusting Inlet Covers	EACH	1.000	1.000
0034	619.1000	Mobilization	EACH	1.000	1.000
0036	624.0100	Water	MGAL	0.900	0.900
0038	628.1905	Mobilizations Erosion Control	EACH	2.000	2.000
0040	628.1910	Mobilizations Emergency Erosion Control	EACH	1.000	1.000
0042	628.7015	Inlet Protection Type C	EACH	2.000	2.000
0044	643.0300	Traffic Control Drums	DAY	600.000	600.000
0046	643.0410	Traffic Control Barricades Type II	DAY	60.000	60.000
0048	643.0420	Traffic Control Barricades Type III	DAY	630.000	630.000
0050	643.0705	Traffic Control Warning Lights Type A	DAY	1,140.000	1,140.000
0052	643.0900	Traffic Control Signs	DAY	780.000	780.000
0054	643.1050	Traffic Control Signs PCMS	DAY	7.000	7.000
0056	643.5000	Traffic Control	EACH	1.000	1.000
0058	652.0225	Conduit Rigid Nonmetallic Schedule 40 2-Inch	LF	66.000	66.000
0060	690.0150	Sawing Asphalt	LF	45.000	45.000
0062	690.0250	Sawing Concrete	LF	55.000	55.000
0064	715.0720	Incentive Compressive Strength Concrete Pavement	DOL	500.000	500.000
0066	ASP.1T0A	On-the-Job Training Apprentice at \$5.00/HR	HRS	200.000	200.000
0068	ASP.1T0G	On-the-Job Training Graduate at \$5.00/HR	HRS	300.000	300.000

3

REMOVALS				
	204.0150 REMOVING CURB & GUTTER LF	205.0100 EXCAVATION COMMON CY	690.0150 SAWING ASPHALT LF	690.0250 SAWING CONCRETE LF
LOCATION				
PROJECT 2718-19-70	50	70	45	55
TOTALS	50	70	45	55

EROSION CONTROL			
	628.1905 MOBILIZATION EROSION CONTROL EACH	628.1910 MOBILIZATION EMERGENCY EROSION CONTROL EACH	628.7015 INLET PROTECTION TYPE C EACH
LOCATION			
PROJECT 2718-19-70	2	1	2
TOTALS	2	1	2

3

APPROACH WORK

	305.0120 BASE AGGREGATE DENSE 1 1/4-INCH TON	415.0410 CONCRETE PAVEMENT APPROACH SLAB SY	601.0409 CONCRETE CURB & GUTTER 30-INCH TYPE A (1) LF	611.8115 ADJUSTING INLET COVERS EACH	624.01 WATER MGAL
LOCATION					
PROJECT 2718-19-70	60	125	50	1	0.9
TOTALS	60	125	50	1	0.9

NOTES:

(1) VARIED CURB HEIGHT TO MATCH EXISTING ELEVATION AT BACK OF CURB

TRAFFIC CONTROL

	643.0300 TRAFFIC CONTROL DRUMS	643.0410 TRAFFIC CONTROL BARRICADES TYPE II	643.0420 TRAFFIC CONTROL BARRICADES TYPE III	643.0705 TRAFFIC CONTROL WARNING LIGHTS TYPE A	643.0900 TRAFFIC CONTROL SIGNS	643.1050 TRAFFIC CONTROL SIGNS PCMS	643.5000 TRAFFIC CONTROL
LOCATION	DAYS EACH	DAYS EACH	DAYS EACH	DAYS EACH	DAYS EACH	DAYS (3) EACH	EACH
MADISON STREET (WEST OF BRIDGE) (1)	30 5	150 -	- -	7 210	10 300	3 90	-
MADISON STREET (EAST OF BRIDGE)	30 -	- -	2 60	4 120	8 240	13 390	1
PEDESTRIAN DETOUR	30 -	- -	- -	10 300	20 600	10 300	-
PROJECT 2718-19-70	30 15 (2)	450 -	- -	- -	- -	- -	-
TOTALS	600	60	630	1,140	780	7	1

NOTES:

(1) TRAFFIC CONTROL DEVICES FOR MADISON STREET MAINLINE CLOSURES AND PEDESTRIAN DETOURS WEST OF BRIDGE, BY OTHERS.


(2) UNDISTRIBUTED QUANTITY

(3) PLACE PCMS SIGN FOR 7 DAYS PRIOR TO CLOSURE


UNLESS OTHERWISE NOTED
ALL ITEMS IN CATEGORY 0010

Standard Detail Drawing List


08D01-22A	CONCRETE CURB & GUTTER
08D01-22B	CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS
08E10-02	INLET PROTECTION TYPE A, B, C AND D
13B02-09A	CONCRETE PAVEMENT APPROACH SLAB
15C02-08A	BARRICADES AND SIGNS FOR MAINLINE CLOSURES
15C02-08B	BARRICADES AND SIGNS FOR VARIOUS CLOSURES
15C03-05	BARRICADES AND SIGNS FOR SIDEROAD CLOSURES
15C11-09B	CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS
15D30-06A	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D30-06B	TRAFFIC CONTROL, TEMPORARY ADA COMPLIANT PEDESTRIAN ACCOMMODATION
15D30-06C	TRAFFIC CONTROL, PEDESTRIAN ACCOMMODATION
15D38-02A	TEMPORARY TRAFFIC CONTROL SIGN MOUNTING
15D38-02B	ATTACHMENT OF SIGNS TO POSTS




TYPES A^① & D




6" SLOPED CURB TYPES G^① & J




4" SLOPED CURB TYPES G^① & J




TYPES K^① & L
(OPTIONAL CURB SHAPE)




TYPES K^① & L
CONCRETE CURB AND GUTTER 30"




TYPES A^① & D
CONCRETE CURB AND GUTTER 18"



6" SLOPED CURB TYPES A^① & D




4" SLOPED CURB TYPES A^① & D
CONCRETE CURB AND GUTTER 36"



4" SLOPED CURB TYPES R^① & T


TBT & TBTT	X
30"	22"
36"	28"



TYPES TBT & TBTT^①
CONCRETE CURB AND GUTTER


PAVEMENT THICKNESS
AND MAXIMUM CONCRETE
PANEL WIDTH TABLE

PAVEMENT THICKNESS	MAXIMUM PANEL WIDTH
LESS THAN 10"	12'
10" & ABOVE	15'



PARTIAL SECTION OF PAVEMENT *
WITH INTEGRAL CURB AND GUTTER

* BIKE LANE IS NOT SHOWN



REVERSE SLOPE GUTTER^⑥
(TYPICAL FOR ALL CURB & GUTTER TYPES)

GENERAL NOTES


DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.

PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.


INTEGRAL CURB AND GUTTER SHALL CONFORM TO THE DETAILS SHOWN FOR CONCRETE CURB AND GUTTER INCLUDING THE TRANSVERSE GUTTER SLOPE.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.

- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ③ USE 8" MINIMUM GUTTER THICKNESS WHEN USED WITH AN ADJACENT CONCRETE TRUCK APRON PLACED BEHIND BACK OF CURB.
- ④ THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 8" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑤ UNLESS OTHERWISE NOTED, FOR STAKING PURPOSES THE FACE OF CURB IS 6" FROM THE BACK OF CURB.
- ⑥ WHEN REVERSE SLOPE GUTTER IS REQUIRED, THE LOCATION(S) WILL BE SHOWN ELSEWHERE IN THE PLAN.
- ⑦ USE 4% GUTTER CROSS SLOPE UNLESS OTHERWISE NOTED IN THE PLANS.
- ⑧ INCLUDE LONGITUDINAL JOINT AND TIE BARS ALONG LANE EDGE WHEN CONCRETE PANEL WIDTH EXCEEDS THE MAXIMUM WIDTH PER TABLE BELOW. LONGITUDINAL JOINT(S) ARE NOT ALLOWED WITHIN TRAFFIC LANES AND BIKE LANES. LONGITUDINAL JOINT MAY BE SAWED.
- ⑨ CONCRETE CURB AND GUTTER 4-INCH SLOPED 30-INCH TYPE "R" AND "T" = 17 INCHES
CONCRETE CURB AND GUTTER 4-INCH SLOPED 36-INCH TYPE "R" AND "T" = 23 INCHES



END SECTION CURB AND GUTTER



DETAIL OF CURB AND GUTTER AT INLETS
(TYPICAL H INLET COVER SHOWN)


GENERAL NOTES

DETAILS OF CONSTRUCTION AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE CONTRACT.


PAVEMENT TIES AND TIE BARS SHALL BE EPOXY COATED IN CONFORMANCE WITH SUBSECTION 505.2.6.2 OF THE STANDARD SPECIFICATIONS.

UNLESS OTHERWISE SHOWN ON THE TYPICAL CROSS SECTIONS, THE BASE AGGREGATE AND COMMON EXCAVATION LIMITS ARE 2' - 0" BEHIND THE BACK OF CURBS.


- ① TIE BARS ARE REQUIRED FOR CURB AND GUTTERS TYPES A, G, K, R, AND TBTT.
- ② THE BOTTOM OF CURB AND GUTTER MAY BE CONSTRUCTED EITHER LEVEL OR PARALLEL TO THE SLOPE OF THE SUBGRADE OR BASE AGGREGATE PROVIDED A 6" MINIMUM GUTTER THICKNESS IS MAINTAINED.
- ⑨ REFER TO SDD 08D18 AND 08D19 FOR ADDITIONAL DRIVEWAY ENTRANCE CURB DETAILS.



TYPICAL TIE BAR LOCATION ①




TYPES A ① & D




TYPES G ① & J

CONCRETE CURB




PLAN VIEW



SECTION A - A

TIE BARS DRILLED INTO EXISTING PAVEMENT





DRIVEWAY ENTRANCE CURB ⑨
(WHEN DIRECTED BY THE ENGINEER)

CONCRETE CURB, TIES AND CURB AND GUTTER APPLICATIONS

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
February 2021 /S/ Rodney Taylor
DATE ROADWAY STANDARDS DEVELOPMENT
ENGINEER

FHWA



INLET PROTECTION, TYPE A


GENERAL NOTES

INLET PROTECTION DEVICES SHALL BE MAINTAINED OR REPLACED AT THE DIRECTION OF THE ENGINEER.

MANUFACTURED ALTERNATIVES APPROVED AND LISTED ON THE DEPARTMENT'S EROSION CONTROL PRODUCT ACCEPTABILITY LIST MAY BE SUBSTITUTED.


WHEN REMOVING OR MAINTAINING INLET PROTECTION, CARE SHALL BE TAKEN SO THAT THE SEDIMENT TRAPPED ON THE GEOTEXTILE FABRIC DOES NOT FALL INTO THE INLET. ANY MATERIAL FALLING INTO THE INLET SHALL BE REMOVED IMMEDIATELY.

- ① FINISHED SIZE, INCLUDING FLAP POCKETS WHERE REQUIRED, SHALL EXTEND A MINIMUM OF 10" AROUND THE PERIMETER TO FACILITATE MAINTENANCE OR REMOVAL.
- ② FOR INLET PROTECTION, TYPE C (WITH CURB BOX), AN ADDITIONAL 18" OF FABRIC IS WRAPPED AROUND THE WOOD AND SECURED WITH STAPLES. THE WOOD SHALL NOT BLOCK THE ENTIRE HEIGHT OF THE CURB BOX OPENING.
- ③ FLAP POCKETS SHALL BE LARGE ENOUGH TO ACCEPT WOOD 2X4.



**INLET PROTECTION, TYPE B
(WITHOUT CURB BOX)**

(CAN BE INSTALLED IN ANY INLET WITHOUT A CURB BOX)



INLET PROTECTION, TYPE C (WITH CURB BOX)

INSTALLATION NOTES

TYPE B & C

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.


THE CONTRACTOR SHALL DEMONSTRATE A METHOD OF MAINTENANCE, USING A SEWN FLAP, HAND HOLDS OR OTHER METHOD TO PREVENT ACCUMULATED SEDIMENT FROM ENTERING THE INLET.

TYPE D

DO NOT INSTALL INLET PROTECTION TYPE D IN INLETS SHALLOWER THAN 30", MEASURED FROM THE BOTTOM OF THE INLET TO THE TOP OF THE GRATE.

TRIM EXCESS FABRIC IN THE FLOW LINE TO WITHIN 3" OF THE GRATE.

THE INSTALLED BAG SHALL HAVE A MINIMUM SIDE CLEARANCE, BETWEEN THE INLET WALLS AND THE BAG, MEASURED AT THE BOTTOM OF THE OVERFLOW HOLES, OF 3". WHERE NECESSARY THE CONTRACTOR SHALL CINCH THE BAG, USING PLASTIC ZIP TIES, TO ACHIEVE THE 3" CLEARANCE. THE TIES SHALL BE PLACED AT A MAXIMUM OF 4" FROM THE BOTTOM OF THE BAG.




INLET PROTECTION, TYPE D

(CAN BE INSTALLED IN ANY INLET TYPE WITH OR WITHOUT A CURB BOX AS PER NOTE ②)


**INLET PROTECTION
TYPE A, B, C, AND D**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION


APPROVED
10/16/02 /S/ Beth Connestra
DATE
CHIEF ROADWAY DEVELOPMENT ENGINEER
FHWA



**SKewed APPROACH
(PAVEMENT MORE THAN TWO LANES)**




**SKews > 20°
(PAVEMENT WIDTH ≤ 30')**




**SKews ≤ 20°
(PAVEMENT WIDTH ≤ 30')**
APPROACH SLAB AND ADJACENT PAVEMENT


- * (RS) = REINFORCED CONCRETE SLAB
- * (PS) = PAVED CONCRETE SHOULDER OR CONCRETE DRAINAGE SLAB
- * (NRS) = NON - REINFORCED CONCRETE SLAB
- *** STANDARD DOWEL BAR DIAMETER (SEE SDD 13C11 AND SDD 13C13)



**SECTION A - A
REINFORCEMENT POSITIONING DETAIL**




**SECTION B - B
BEND DETAIL
BOTTOM REINFORCEMENT**




**SECTION C - C
TRANSITION DETAIL
APPROACH SLAB TO ADJACENT PAVEMENT**

GENERAL NOTES

- THE CONTRACTOR MAY SPLICE NO. 6 BARS IN THE APPROACH SLAB FOR SKEWED STRUCTURES ONLY. STAGGER SPLICES WITH A MAXIMUM OF ONE SPLICE PER BAR. THE LENGTH OF LAP IS 20 INCHES.
- TACK WELD DOWEL BARS TO THE BASKETS ON ALTERNATE ENDS.
- ① THE CONTRACTOR MAY USE NO. 4 BARS SPACED AT 2' - 0" C - C IN BOTH THE LONGITUDINAL AND TRANSVERSE DIRECTIONS FOR TOP REINFORCEMENT AS AN ALTERNATIVE TO THE WELDED WIRE FABRIC.
 - ② THE CONTRACTOR MAY OMIT THE BARS BETWEEN REINFORCED SLABS WHERE SLAB REINFORCEMENT BARS EXTEND ACROSS THE CENTERLINE OR REFERENCE LINE.
 - ③ DO NOT CONSTRUCT AN EXPANSION JOINT OR INSTALL DOWEL BARS WHEN ABUTTING AN HMA PAVEMENT.
 - ④ USE A JOINT SEALANT CONFORMING TO STANDARD SPECIFICATION 415.2.6.
 - ⑤ PLACE EXPANSION CAP ON THE END OF THE DOWEL THAT IS NOT TACK WELDED TO THE BASKET. DO NOT FORCE DOWEL BAR PAST THE DOWEL STOP.
 - ⑥ EXTEND EXPANSION JOINT THROUGH ANY ADJACENT TIED CONCRETE.
- (A) STANDARD CONTRACTION JOINT NORMAL TO \mathcal{C} OR \mathcal{R} .
- (B) STANDARD LONGITUDINAL JOINT WITH TIE BARS.
- (C) 1 1/2" EXPANSION JOINT WITH DOWEL BARS NORMAL TO \mathcal{C} OR \mathcal{R} .



**SECTION D - D
CONTRACTION JOINT**




EXPANSION JOINT DETAIL

**CONCRETE PAVEMENT
APPROACH SLAB**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2018 /S/ Peter Kemp, P.E.
DATE DATE PAVEMENT SUPERVISOR
FHWA



**DETAIL A
MAINLINE CLOSURE WITH POSTED DETOUR**

WORK ZONE GREATER THAN OR EQUAL TO 1/2 MILE FROM
DETOUR ROUTE (1000 FEET IF URBAN)

**DETAIL B
MAINLINE CLOSURE WITH POSTED DETOUR**


WORK ZONE LESS THAN 1/2 MILE FROM
DETOUR ROUTE (1000 FEET IF URBAN)

LEGEND

- SIGN ON PERMANENT SUPPORT
- TYPE III BARRICADE
- TYPE III BARRICADE WITH ATTACHED SIGN
- TYPE "A" WARNING LIGHT (FLASHING)
- WORK AREA
- FLAGS, 16" X 16" MIN. (ORANGE)
- M4 - 8
- M3 - X
- M1 - 4 OR M1 - 6 OR M1 - 5A
- M05 - 1 OR M06 - 1

SPEED LIMIT (MPH)	"STOP AHEAD" ADVANCE WARNING DISTANCE (FT)
25	200
30	200
35	350
40	350
45	500
50	550
55	750

SEE SDD 15C2-SHEET "b"
FOR GENERAL NOTES
AND FOOTNOTES ① THROUGH ⑦




**DETAIL C
MAINLINE CLOSURE, NO POSTED DETOUR**

**BARRICADES AND SIGNS
FOR MAINLINE CLOSURES**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
February 2020 /S/ Andrew Heidtke
DATE DATE WORK ZONE ENGINEER

FHWA



**DETAIL D
ROAD CLOSURE BARRICADE DETAIL
APPROACH VIEW**



**DETAIL E
LANE CLOSURE BARRICADE DETAIL
APPROACH VIEW**

SEE SDD 15C2 - SHEET "a" FOR LEGEND

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY RE-ESTABLISHED UPON COMPLETION OF THE OPERATION, OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN 7 CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW - INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11 - 2, R11 - 3, M4 - 9, R11 - 4, AND R10 - 61 SIGNS PLACED ON THE BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE RAIL OR BOTTOM RAILS.

"WO" AND "MO" SIGNS ARE THE SAME AS "W" AND "M" SIGNS EXCEPT THE BACKGROUND IS ORANGE.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:

- R11 - 2 SHALL BE 48" X 30"
- R11 - 3 SHALL, R11 - 4 AND R10 - 61 SHALL BE 60" X 30"
- M4 - 9 SHALL BE 30" X 24"
- M3 - X SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M4 - 8 SHALL BE 24" X 12" (36" X 18" IF NEEDED TO MATCH EXISTING SIGNS)
- M1 - 4, M1 - 5A AND M1 - 6 SHALL BE 24" X 24" (36" X 36" IF NEEDED TO MATCH EXISTING SIGNS)
- MO5 - 1 AND MO6 - 1 SHALL BE 21" X 21" (30" X 30" IF NEEDED TO MATCH EXISTING SIGNS)
- D1 - X SHALL BE AS SHOWN ON SPECIFIC PROJECT SIGNING DETAIL SHEETS.
- R1 - 1 SHALL BE 36" X 36"


- ① TWO WARNING LIGHTS SHALL BE PROVIDED ON THE CENTER BARRICADE AND A MINIMUM OF ONE WARNING LIGHT SHALL BE PROVIDED ON EACH OF THE OTHER BARRICADES WITHIN THE ROADWAY LIMITS. SPACING OF THE WARNING LIGHTS SHALL BE UNIFORM TO THE EDGE OF ROADWAY AS SHOWN (APPROX. 8 FOOT LIGHT SPACING).
- ② THESE SIGNS AND BARRICADES ARE NOT REQUIRED IF ROAD CLOSURE BEGINS AT AN INTERSECTION.
- ③ FOR ROAD CLOSURE WITHOUT LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "D".
- ④ FOR ROAD CLOSURE WITH LOCAL ACCESS TO PROJECT, SEE ROAD CLOSURE BARRICADE DETAIL "E".
- ⑤ FOR BRIDGE OR CULVERT REPLACEMENTS, SUBSTITUTE "BRIDGE OUT" INSTEAD OF "ROAD CLOSED" ON R11 - 2 AND R11 - 3 SIGNS.
- ⑥ INSTALL DETOUR AND COMMUNITY GUIDE SIGNS AND ARROWS ONLY IF SPECIFIED IN THE CONTRACT. IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR ROUTE SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES. MODIFY EXISTING SIGNS WHERE POSSIBLE. SEE SPECIFIC PROJECT DETOUR SIGNING DETAIL SHEETS. IF DETOUR SIGNS ARE BEING INSTALLED BY OTHERS, PLACE THE CONTRACTED TRAFFIC CONTROL SIGNS TO ALLOW FOR PLACEMENT OF ALL WARNING, DETOUR AND GUIDE SIGNS AS SHOWN.
- ⑦ "EAST" CARDINAL DIRECTION MARKERS AND RIGHT TURN ARROWS ARE SHOWN. USE OTHER CARDINAL DIRECTIONS AND ARROWS AS APPROPRIATE.

**BARRICADES AND SIGNS
FOR
VARIOUS CLOSURES**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
February 2020 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER


FHWA




DETAIL 1
(NO ACCESS TO PROJECT)



DETAIL 2
(PUBLIC CROSS-TRAFFIC MAINTAINED.
NO ACCESS TO PROJECT)



DETAIL 3
(PUBLIC CROSS-TRAFFIC MAINTAINED.
CONTRACTOR, LOCAL BUSINESS AND
RESIDENT ACCESS TO PROJECT)



DETAIL 4
(CONTRACTOR, LOCAL BUSINESS AND
RESIDENT ACCESS TO PROJECT)

GENERAL NOTES

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS AND BARRICADES SHALL BE ADJUSTED TO FIT FIELD CONDITIONS AS APPROVED BY THE ENGINEER.

ANY SIGNS TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE" SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER.

THE SPACING BETWEEN TRAFFIC CONTROL SIGNS SHOULD BE ADJUSTED TO NOT CONFLICT WITH AND SHOULD PROVIDE A DESIRABLE MINIMUM OF 200 FEET CLEARANCE (500 FEET DESIRABLE) TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

IF A "STOP" SIGN MUST BE REMOVED FOR A WORK OPERATION, A TEMPORARY "STOP" SIGN SHALL BE PLACED PRIOR TO THE SIGN REMOVAL, OR A FLAGGER SHALL BE PROVIDED UNTIL THE SIGN IS REESTABLISHED.

BARRICADES THAT MUST BE MOVED FOR A WORK OPERATION SHALL BE IMMEDIATELY REESTABLISHED UPON COMPLETION OF THE OPERATION OR FOR CONTINUING OPERATIONS, AT THE END OF EACH WORKING DAY.

SIGNS THAT WILL BE IN PLACE LESS THAN SEVEN CONTINUOUS DAYS AND NIGHTS MAY BE MOUNTED ON PORTABLE SUPPORTS.

ALL TYPE III BARRICADES SHALL HAVE RAILS REFLECTORIZED ON BOTH FACES. STRIPES SHALL BE PROPERLY SLOPED DOWN TOWARD THE TRAFFIC SIDE OR AS SHOWN IN THE ROAD CLOSURE BARRICADE DETAIL "D" FOR FULL ROAD CLOSURES.

TYPE "A" LOW-INTENSITY FLASHING WARNING LIGHTS SHALL BE VISIBLE ON BOTH SIDES OF THE BARRICADE.

THE R11-2, R11-3, AND R11-4 SIGNS PLACED ON BARRICADES SHALL COVER NO MORE THAN THE TOP RAIL. THE SIGNS SHALL NOT COVER ANY PORTION OF THE MIDDLE OR BOTTOM RAILS.

ALL SIGNS SHALL BE 48" X 48" UNLESS OTHERWISE NOTED BELOW:
R11-2 SHALL BE 48" X 30".
R11-4 AND R11-3 SHALL BE 60" X 30".

- * OMIT THE "ROAD CLOSED 500 FT." SIGN IF THE LAST INTERSECTION IS 500 FEET OR LESS FROM THE WORK ZONE.
- ** 500' MAX. OR AT LAST INTERSECTION, WHICHEVER IS CLOSEST.


LEGEND

- ⊙ SIGN ON PERMANENT SUPPORT
- ⊥ TYPE III BARRICADE
- ⊥ TYPE III BARRICADE WITH ATTACHED SIGN
- ⚡ TYPE "A" WARNING LIGHT (FLASHING)
- ▨ WORK AREA


**BARRICADES AND SIGNS
FOR
SIDEROAD CLOSURES**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
July 2018 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER




DRUM



42" CONE

DO NOT USE IN TAPERS
 1/2 SPACING OF DRUMS




VERTICAL PANEL

THE STRIPES SHALL SLOPE DOWNWARD TO THE TRAFFIC SIDE FOR CHANNELIZATION.


GENERAL NOTES

- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② LOCATION OF WARNING LIGHTS WHEN SHOWN ON THE PLAN.



TYPE II BARRICADE

FOR RAILS LESS THAN 36" LONG, 4" WIDE STRIPES MAY BE USED. ALL STRIPES SHALL SLOPE DOWNWARD TO THE TRAFFIC SIDE FOR CHANNELIZATION.




TYPE III BARRICADE

IF SIGN MOUNTED, DO NOT COVER MORE THAN 50% OF THE TOP TWO RAILS OR 33% OF THE TOTAL AREA OF THE THREE RAILS.


* IF USED FOR A PERMANENT APPLICATION USE RED SHEETING.

CHANNELIZING DEVICES DRUMS, CONES, BARRICADES AND VERTICAL PANELS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED May 2021 DATE	/S/ Andrew Heidtke WORK ZONE ENGINEER
FHWA	


NOTE: MAY BE USED ON ROADWAY WITH POSTED SPEED OF LESS THAN 40 MPH.



MID-BLOCK SIDEWALK CLOSURE IN PARKING LANE




MID-BLOCK SIDEWALK CLOSURE



CORNER SIDEWALK CLOSURE WITH TEMPORARY CROSSWALK

NOTE: LAYOUT SAME AS ABOVE.



SIDEWALK DIVERSION

GENERAL NOTES

WHEN CLOSING OR RELOCATING CROSSWALKS OR SIDEWALKS, PROVIDE DETECTABLE TEMPORARY FACILITIES AND INCLUDE ACCESSIBILITY FEATURES CONSISTENT WITH EXISTING PEDESTRIAN FACILITIES.

TEMPORARY TRAFFIC CONTROL DEVICES FOR PEDESTRIANS ARE SHOWN. OTHER DEVICES MAY BE NECESSARY TO CONTROL VEHICULAR TRAFFIC. STAGE WORK AS NECESSARY, TO PROVIDE A TEMPORARY PEDESTRIAN ACCESS ROUTE AT ALL TIMES. FOR ROADWAYS WITH NO AVAILABLE DETOURS, MAINTAIN ONE OPEN SIDEWALK AT ALL TIMES.

"WO" SIGN IS THE SAME AS "W" SIGN, EXCEPT THE BACKGROUND IS ORANGE.

FOR NIGHTTIME CLOSURE, USE TYPE "A" FLASHING WARNING LIGHTS ON BARRICADES, SUPPORTING SIGNS AND CLOSING SIDEWALK. USE TYPE "C" STEADY BURN LIGHTS ON CHANNELIZING DEVICES SEPARATING THE WORK AREA FROM VEHICULAR TRAFFIC.

PEDESTRIAN TRAFFIC SIGNAL DISPLAY CONTROLLING CLOSED CROSSWALK SHALL BE COVERED OR DEACTIVATED.

POST MOUNTED SIGNS LOCATED ADJACENT TO A SIDEWALK SHALL HAVE A 7 FOOT MINIMUM CLEARANCE FROM THE BOTTOM OF THE SIGN TO THE SIDEWALK SURFACE.

ALTERNATE SIDEWALK WORK BETWEEN LEFT AND RIGHT SIDE OF ROADWAY TO MAINTAIN PEDESTRIAN ACCESS.

- ① IF SIDEWALK CLOSURE AFFECTS AN ACCESSIBLE AND DETECTABLE FACILITY, MAINTAIN ACCESSIBILITY AND DETECTABILITY ALONG THE ALTERNATE PEDESTRIAN ROUTE
- ② "ROAD WORK AHEAD" SIGNS ARE NOT REQUIRED IF THE SIDEWALK CLOSURE OCCURS WITHIN A LARGER WORK ZONE WHERE ADVANCE WARNING SIGNS ARE ALREADY PRESENT, OR IF THE WORK AREA AND EQUIPMENT ARE MORE THAN 2 FEET BEHIND THE CURB.
- ③ IF TEMPORARY PEDESTRIAN CROSSWALK IS NOT PROVIDED, OMIT R9-8 AND WO11-2 SIGN ASSEMBLIES. IF PROVIDED INCLUDE ON BOTH SIDES OF THE CROSSWALK.
- ④ TEMPORARY CURB RAMPS. SEE SDD 15D30 SHEET "b".
- ⑤ DRUMS OR BARRICADES AT 25 FOOT SPACING. STREET PARKING SHALL BE PROHIBITED FOR AT LEAST 50 FEET IN ADVANCE OF THE MID-BLOCK CROSSWALK.
- ⑥ TEMPORARY PAVEMENT MARKING FOR CROSSWALK LINES.
- ⑦ LIMIT WORK TO ONE QUADRANT AT A TIME TO MINIMIZE PEDESTRIAN DISRUPTION.

LEGEND

- SIGN ON PERMANENT SUPPORT
- TRAFFIC CONTROL DRUM
- TYPE II BARRICADE WITH/WITHOUT SIGN (ALL WITH ONE WARNING LIGHT, TYPE A, LOW INTENSITY FLASHING)
- TYPE III BARRICADE WITH/WITHOUT SIGN (ALL WITH ONE WARNING LIGHT, TYPE A, LOW INTENSITY FLASHING)
- UNDER PEDESTRIAN TRAFFIC
- WORK AREA
- PEDESTRIAN CHANNELIZATION DEVICE
- DIRECTION OF TRAFFIC

**TRAFFIC CONTROL,
PEDESTRIAN ACCOMMODATION**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

GENERAL NOTES


NOTIFY THE BUS COMPANY 7 DAYS IN ADVANCE OF THE BUS STOP RELOCATION.

ALTERNATE SIDEWALK WORK BETWEEN LEFT AND RIGHT SIDE OF ROADWAY TO MAINTAIN PEDESTRIAN ACCESS.


- ① CURB RAMPS SHALL BE 48" MIN. WIDTH WITH A FIRM, STABLE AND SLIP RESISTANT SURFACE. INSTALL CONTRASTING DETECTABLE WARNING FIELD AT PEDESTRIAN STREET CROSSINGS. REFER TO SDD 08D05, SHEET "e".
- ② PROTECTIVE EDGING WITH A 2" MIN. HEIGHT SHALL BE INSTALLED WHEN A CURB RAMP OR LANDING PLATFORM HAS A VERTICAL DROP OF 6" OR GREATER OR HAS A SIDE APRON SLOPE STEEPER THAN 1:3 (33%). PROTECTIVE EDGING SHOULD BE CONSIDERED WHEN CURB RAMPS OR LANDING PLATFORMS HAVE A VERTICAL DROP OF 3" OR MORE.
- ③ DETECTABLE EDGING WITH 6" MIN. HEIGHT AND CONTRASTING COLOR SHALL BE INSTALLED ON ALL CURB RAMP LANDINGS WHERE THE WALKWAY CHANGES DIRECTION (TURNS).
- ④ CURB RAMPS AND LANDINGS SHALL HAVE A 1:50 (2%) MAX. CROSS-SLOPE.
- ⑤ CLEAR SPACE OF 48" X 48" SHALL BE PROVIDED ABOVE AND BELOW THE CURB RAMP.
- ⑥ THE CURB RAMP WALKWAY EDGE SHALL BE MARKED WITH A YELLOW COLOR, 4" WIDE MARKING, UNLESS A CONTRASTING DETECTABLE WARNING FIELD IS PROVIDED.
- ⑦ DO NOT RESTRICT WATER FLOW IN THE GUTTER SYSTEM.
- ⑧ LATERAL JOINTS OR GAPS BETWEEN SURFACES SHALL BE LESS THAN 1/2" WIDTH.
- ⑨ CHANGES BETWEEN SURFACE HEIGHTS SHALL NOT EXCEED 1/2". LATERAL EDGES SHALL BE VERTICAL UP TO 1/4" HIGH AND BEVELED AT 1:2 BETWEEN 1/4" AND 1/2".
- ⑩ 5" WIDE MIN. WITH PEDESTRIAN SAFETY BARRICADE, 10' WIDE MIN. WITHOUT PEDESTRIAN SAFETY BARRICADE.



TEMPORARY CURB RAMP PARALLEL TO CURB




WITH PROTECTIVE EDGE




WITH SIDE APRON

TEMPORARY CURB RAMP PERPENDICULAR TO CURB



PLAN VIEW



PROFILE VIEW

TEMPORARY BUS STOP PAD

LEGEND

- TRAFFIC CONTROL DRUM
- ⊥ TYPE III BARRICADE
- ▨ WORK AREA

**TRAFFIC CONTROL,
PEDESTRIAN ACCOMMODATION**


STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

6


6

SDD 15D30 - 06b


SDD 15D30 - 06b




NARROW SIDEWALK PASSING DETAIL




TEMPORARY PEDESTRIAN ACCESS




SECTION A - A



**PLAN VIEW
TEMPORARY TYPE 3 RAMP
(OUTSIDE OF CROSSWALK AREA)**



TEMPORARY PEDESTRIAN SURFACE PLYWOOD



TEMPORARY PEDESTRIAN BARRICADE *

GENERAL NOTES


- BARRICADE DEVICE SELECTED FROM APPROVED PRODUCT LIST
- ① REFLECTIVE SHEETING SHALL FOLLOW THE REQUIREMENTS IN THE APPROVED PRODUCTS LISTING FOR SIGN SHEETING.
- ② SHEETING REQUIRED ON MORE THAN 50% OF BARRICADE WIDTH.
- ③ PLACE SHEETING ON BOTH SIDES OF THE BARRICADE.
- * USE THIS DETAIL FOR SHEETING PLACEMENT REFERENCE.

**TRAFFIC CONTROL,
PEDESTRIAN ACCOMMODATION**

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION

APPROVED
November 2019 /S/ Andrew Heidtke
DATE WORK ZONE ENGINEER

FHWA




DETAIL OF TUBULAR STEEL SIGN POST

TUBULAR STEEL POSTS


AREA OF SIGN INSTALLATION (SQ. FT.)	NUMBER OF REQUIRED TUBULAR STEEL POSTS
9 OR LESS	1
GREATER THAN 9 LESS THAN OR EQUAL TO 18	2
GREATER THAN 18 LESS THAN OR EQUAL TO 27	3

SIGNS WIDER THAN 3 FEET OR LARGER THAN 9 SQ. FT. SHALL BE MOUNTED ON MULTIPLE POSTS (SEE ABOVE TABLE).


SIGNS LARGER THAN 27 SQ. FT. SHALL NOT BE MOUNTED ON TUBULAR STEEL POSTS.



SECTION A-A



4" X 6" WOOD POST MODIFICATION




URBAN AREA

POST MOUNTING DETAIL FOR TEMPORARY TRAFFIC CONTROL FIXED MESSAGE SIGNS

WOOD POST EMBEDMENT DEPTH

AREA OF SIGN INSTALLATION (SQ. FT.)	D (MIN)
20 OR LESS	4'
GREATER THAN 20	5'



RURAL AREA

4" X 6" WOOD POST

POST SPACING REQUIREMENTS		NUMBER OF WOOD POSTS REQUIRED
L	E	
48" OR LESS AND LESS THAN 20 SQ. FT.	-	1
LESS THAN 60"	12"	2
60" TO 120"	L/5	2
GREATER THAN 120" LESS THAN 168"	12"	3
168" AND GREATER	12"	4


SEE NOTE ③

GENERAL NOTES

- ① 6 FEET FROM THE EDGE OF PAVEMENT (EDGE LINE LOCATION) UNLESS OTHERWISE DIRECTED BY THE PROJECT ENGINEER. LATERAL OFFSET SHOULD BE ADJUSTED TO AVOID THE DITCH FLOWLINE.
- ② THE EXISTENCE OF CURB AND GUTTER DOES NOT IN ITSELF MANDATE THE VERTICAL CLEARANCE ILLUSTRATED. THAT HEIGHT IS TYPICALLY MEASURED WHERE THERE IS SIDEWALK ADJACENT TO THE ROADWAY OR PARKING IS PERMITTED. IN THE ABSENCE OF SIDEWALK, VERTICAL CLEARANCE IS MEASURED FROM THE TOP OF THE CURB. IF NO SIDEWALK AND NO PARKING, VERTICAL CLEARANCE MAY BE REDUCED TO 5 FOOT MINIMUM. OFFSET OF SIGNS IS MEASURED FROM THE CURB FLOWLINE.
- ③ FOR SIGNS REQUIRING 4 POSTS, SPACE INTERMEDIATE POSTS EVENLY.

TEMPORARY TRAFFIC CONTROL SIGN MOUNTING

STATE OF WISCONSIN
DEPARTMENT OF TRANSPORTATION



NUTS, BOLTS AND LAGS USED FOR MOUNTING SIGNS SHALL HAVE HEXAGONAL HEADS AND SHALL BE EITHER:

- A. HOT DIP GALVANIZED IN ACCORDANCE WITH ASTM DESIGNATION: A 153, CLASS D, OR SC 3
- B. ELECTRO-GALVANIZED IN ACCORDANCE WITH ASTM DESIGNATION: B 633, TYPE III, SC 3

THREADS ON BOLTS AND NUTS SHALL BE MANUFACTURED WITH SUFFICIENT ALLOWANCE FOR THE CADMIUM PLATE OR GALVANIZED COATING TO PERMIT THE NUTS TO RUN FREELY ON THE BOLTS.

WOOD POST (4" x 6")
 LAG SCREWS - 3/8" x 3"
 MACHINE BOLTS - 5/16" x 6 1/2" OR 7" LENGTH W/NUTS

SQUARE STEEL POST (2" x 2")
 MACHINE BOLTS - 3/8" x 3 1/4" LENGTH W/NUTS
 RIVETS - 3/32" (6605-9-6) BULB-TITE, TRI-FOLD, ALUMINUM
 BODY/MANDREL O.D. FLANGE 0.720 - 0.765 INCH,
 GRIP RANGE 0.042 - 0.375 INCH

WASHERS (ALL POSTS) -
 1 1/4" O.D. x 3/8" I.D. x 1/16" STEEL
 1 1/4" O.D. x 3/8" I.D. x 0.080 NYLON

* TWO DIFFERENT FASTENING SYSTEMS ARE SHOWN FOR ILLUSTRATION PURPOSES. ON ANY INDIVIDUAL SIGN, EITHER ONE OR THE OTHER SYSTEM SHALL BE USED. ACTUAL NUMBER OF FASTENERS PER SIGN VARIES WITH THE SIGN AREA. FOR A SINGLE POST INSTALLATION, ALL SIGNS GREATER THAN 9 SQ. FT. REQUIRE THE USE OF 3 FASTENERS.

ATTACHMENT OF SIGNS TO POSTS	
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION	
APPROVED June 2017 DATE	/S/ Andrew Heidtke WORK ZONE ENGINEER
FHWA	

DESIGN DATA

LIVE LOAD:
 INVENTORY RATING: HS-16
 OPERATING RATING: HS-30
 WISCONSIN STANDARD PERMIT VEHICLE (WIS-SPV) = 205 KIPS

MATERIAL PROPERTIES:
 CONCRETE MASONRY OVERLAY DECKS $f'_c = 4,000$ P.S.I.

TRAFFIC DATA

MADISON STREET:
 A.D.T. = 8,200 (2018)
 R.D.S. = 30 MPH

NOTES

DRAWINGS SHALL NOT BE SCALED.

DIMENSIONS SHOWN ARE BASED ON THE ORIGINAL STRUCTURE PLANS.

PROTECTIVE SURFACE TREATMENT SHALL BE APPLIED TO THE ENTIRE TOP SURFACE OF THE NEW CONCRETE OVERLAY.

PROTECTIVE SURFACE TREATMENT RESEAL SHALL BE APPLIED TO THE ENTIRE SURFACE OF THE SIDEWALKS AND CURBS. SURFACE PREPARATION IS INCLUDED IN THE BID ITEM "PROTECTIVE SURFACE TREATMENT RESEAL."

SEAL OVERLAY CONSTRUCTION JOINTS ACCORDING TO SECTION 502.3.13.1 OF THE STANDARD SPECIFICATIONS. COST INCIDENTAL TO BID ITEM "CONCRETE MASONRY OVERLAY DECKS".

A MINIMUM OF 1-INCH OF CONCRETE SHALL BE REMOVED FROM THE ENTIRE BRIDGE DECK UNDER THE BID ITEM "CLEANING DECKS".

THE AVERAGE OVERLAY THICKNESS IS BASED ON THE MINIMUM OVERLAY THICKNESS PLUS 1/2-INCH TO ACCOUNT FOR VARIATIONS IN THE DECK SURFACE AND ACCOUNTING FOR VARIATION IN THE EXISTING DECK CROSS SLOPE.

PREPARATION DECKS TYPE 1, PREPARATION DECKS TYPE 2 AND FULL-DEPTH DECK REPAIR AREAS ARE BASED ON THE PLANS AND AS DETERMINED BY THE ENGINEER. DECK PREPARATION, FULL-DEPTH DECK REPAIRS AND CURB REPAIRS SHALL BE FILLED WITH "CONCRETE MASONRY OVERLAY DECKS".

ANY EXCAVATION REQUIRED TO COMPLETE THE OVERLAY OR DECK REPAIRS AT THE ABUTMENTS TO BE CONSIDERED INCIDENTAL TO THE BID ITEM "CONCRETE MASONRY OVERLAY DECKS".

THE BROKEN LIGHTING CONDUIT UNDER THE BRIDGE IS TO BE REMOVED AND REPLACED. COORDINATE THE WORK WITH THE CITY OF WAUKESHA. PAYMENT FOR PULLING THE WIRE OUT, REMOVING THE BROKEN CONDUIT, INSTALLING THE NEW CONDUIT AND PULLING THE WIRE BACK THROUGH IS INCLUDED IN THE BID ITEM "CONDUIT RIGID NONMETALLIC SCHEDULE 40 2-INCH."

PROFILE GRADE LINE SHALL BE DETERMINED IN THE FIELD BASED ON MINIMUM OVERLAY THICKNESS OF 1/2" PLACED ABOVE THE DECK SURFACE AFTER SURFACE PREPARATION. EXPECTED AVERAGE OVERLAY THICKNESS IS GIVEN IN THE PLANS. IF EXPECTED AVERAGE OVERLAY THICKNESS IS EXCEEDED BY MORE THAN 1/2", CONTACT THE STRUCTURES DESIGN SECTION.

THE UTILITY INFORMATION SHOWN ON THESE DRAWINGS CONCERNING TYPE AND LOCATION OF UNDERGROUND UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR CONSIDERED ALL-INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING THEIR OWN DETERMINATION AS TO TYPE AND LOCATION OF UTILITIES.


LIST OF DRAWINGS

1. CONCRETE OVERLAY
2. CROSS SECTION
3. INFRARED SCAN DATA




STRUCTURES DESIGN CONTACTS

BUREAU OF STRUCTURES CONTACT - AARON BONK (608) 261-0261
 CONSULTANT CONTACT - MICHAEL ARNOLD (414) 831-4179



PLAN


(CONCRETE OVERLAY - SINGLE SPAN, PRESTRESSED CONCRETE GIRDER BRIDGE)




ELEVATION

NO.	DATE	REVISION	BY
<p>AECOM 1555 North Rivercenter Drive, Suite 214 Milwaukee, WI 53212 (414) 944-6080</p>			
<p>STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION</p>			
ACCEPTED		SDR	DATE
			08/27/21
<p>STRUCTURE B-67-99</p>			
<p>MADISON STREET OVER FOX RIVER</p>			
COUNTY	WAUKESHA	TOWN/CITY/VILLAGE	WAUKESHA
<p>DESIGN SPEC. REHABILITATION N/A</p>			
DESIGNED BY	CEB	DESIGN CK'D	AJC
DRAWN BY	CEB	PLANS CK'D	MJA
<p>CONCRETE OVERLAY</p>			<p>DRAWING 1 OF 3</p>

BATCH PRINT SHEET #CSD\$ OF #NSD\$
 PRINTER DRIVER: \$\$.printerdriver...\$\$
 PEN TABLE: \$\$.pentable...\$\$
 FILE NAME: \$\$.designfile...\$\$
 PLOT DATE: \$\$.plottingdate...\$\$ PLOT TIME: \$\$.plottingtime...\$\$



CROSS SECTION THRU ROADWAY
(LOOKING EAST)



CURB REPAIR DETAIL

TOTAL ESTIMATED QUANTITIES



BID ITEM NUMBER	BID ITEM	UNIT	TOTALS
502.3200	PROTECTIVE SURFACE TREATMENT	SY	364
502.3215	PROTECTIVE SURFACE TREATMENT RESEAL	SY	121
509.0301	PREPARATION DECKS TYPE 1	SY	45
509.0302	PREPARATION DECKS TYPE 2	SY	7
509.0500	CLEANING DECKS	SY	364
509.1200	CURB REPAIR	LF	27
509.1500	CONCRETE SURFACE REPAIR	SF	30
509.2000	FULL-DEPTH DECK REPAIR	SY	2
509.2500	CONCRETE MASONRY OVERLAY DECKS	CY	23
652.0225	CONDUIT RIGID NONMETALLIC SCHEDULE 40 2-INCH	LF	66

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-67-99			
DRAWN BY		CEB	PLANS CK'D. MJA
CROSS SECTION			SHEET 2 OF 3

BATCH PRINT SHEET #CSD\$ OF #NSD\$

PRINTER DRIVER: \$\$.printerdriver...\$\$
PEN TABLE: \$\$.pentable...\$\$
FILE NAME: \$\$.designfile...\$\$
PLOT DATE: \$\$.plottingdate...\$\$ PLOT TIME: \$\$.plottingtime...\$\$

PRINTER DRIVER: \$\$.printerdriver...\$\$
 PEN TABLE: \$\$.penable...\$\$
 FILE NAME: \$\$.designfile...\$\$
 PLOT DATE: \$\$.plottingdate...\$\$
 PLOT TIME: \$\$.plottingtime...\$\$
 BATCH PRINT SHEET #CSD\$ OF #NSD\$




☉ BRG.
W. ABUT.

☉ BRG.
E. ABUT.

PLAN

PROPOSED REHABILITATION AREAS



STRUCTURE NO. B-67-099

REHABILITATION AREA SUMMARY		ROADWAY		SIDEWALKS		LEGEND	
ITEM	UNIT	QUANT.	%	QUANT.	%		
TOTAL AREA	yd ²	363.9		118.1		DECK PREPARATION AREA	
SHADE/DEBRIS	yd ²	0		0		SHADE/DEBRIS	
PREPARATION, DECKS, TYPE 1	yd ²	29.0	8.0	15.6	13.2	DELAMINATION	
PREPARATION, DECKS, TYPE 2	yd ²	4.4	1.2	2.3	1.9	SPALL	
FULL DEPTH DECK REPAIR	yd ²	1.0	0.3	1.0	0.8	DEBOND	
						ASPHALT PATCH	
						CONCRETE PATCH	

SURFACE TYPE: CONCRETE - NO OVERLAY
 INFRARED INSPECTION DATE: 8/9/19
 INFRARED INSPECTION PERFORMED BY AECOM

NO.	DATE	REVISION	BY
STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION			
STRUCTURE B-67-99			
DRAWN BY		JT	PLANS CK'D. DU
INFRARED SCAN DATA			SHEET 3 OF 3



Wisconsin Department of Transportation

Dedicated people creating transportation solutions through innovation and exceptional service.

<http://www.dot.wisconsin.gov>