

FACILITIES DEVELOPMENT MANUAL

Wisconsin Department of Transportation

TABLE OF CONTENTS

Chapter 14: Pavements

Sectio	n 14-1 General
	<u>14-1-1</u> General
	<u>1.1</u> Originator
	<u>1.2</u> Objective
	1.3Asset Management
	1.4Design Procedures1.5WisDOT Pavement Design Software: WisPave
Contin	
Section	n 14-5 Subgrade and Base Course 14-5-1Soils
	1.1General
	14-5-5Subgrade
	5.1Subgrade Improvement Impact on Pavement Thickness Design
	5.2Policy
	Attachment 5.1Soil Support Value vs. Design Group Index
	14-5-10Base Aggregate Dense
	<u>10.1</u> General
	10.2Paving Platform
	10.3Design Guidance
	14-5-15Base Aggregate Open Graded (BAOG)
	<u>15.1</u> General
	15.2BAOG Filter Layer
	<u>15.3</u> Use of BAOG
	15.4Stabilization
	<u>15.5</u> Edge Drains
Section	on 14-7 Traffic
	<u>14-7-1</u> General
	1.1Traffic Information
	1.2Traffic Loading
Section	on 14-10 Pavement Design
	<u>14-10-1</u> General
	<u>1.1</u> Design
	1.2Pavement Type Selection Policy
	1.3Soil Support
	1.4Traffic Loading
	1.5International Roughness Index (IRI)
	1.6Terminal Serviceability
	1.7Design Equation 14-10-5Concrete Pavement Design
	5.1Standard Pavement Type
	5.2 Design Equation
	5.3Modulus of Subgrade Reaction
	5.4Design Thickness
	5.6Filling Joints
	5.7Construction Joints
	<u>5.8</u> Tining
	14-10-10Hot Mix Asphalt (HMA) Pavement Design
	<u>10.1</u> Basis of Design <u>10.2</u> Design Equation

August 15, 2023 Page 1

10.3Design Thickness
10.4Structural Layer Coefficients
<u>10.5</u> Subbase
10.6Staged Construction
10.7HMA Mixture Layers
10.8Edge and End Joints
10.9Longitudinal Joints
<u>10.10</u> Tack Coats
10.11 HMA Cold Weather and Multi-Season Paving
10.12 General Application Guidelines
Attachment 10.1Structural Layer Coefficients
Attachment 10.2Relative Strength Coefficients for Granular Subbase
Attachment 10.3WisDOT HMA Mixture Selection Process Guide
Attachment 10.4WisDOT Allowable HMA Mixture Types
Attachment 10.5WisDOT Asphalt Zones
Attachment 10.6HMA Mixture Type Selection Process Examples
Attachment 10.7Edge Joints
Attachment 10.8End Joints
<u>14-10-15</u> Overlay Design
<u>15.1</u> General
<u>15.2</u> Design
14-10-20Paved Shoulders
20.1Policy
20.2Thickness Design
20.3Type Selection
14-10-25Bridge Approach Pavements 25.1General
25.2Local Roads
14-10-30Highway Ramp Design
30.1Pavement Type and Thickness
14-10-35Intersections
35.1General
35.2Pavement Type Selection
35.3Pavement Design
35.4Roundabout Design Features
Section 14-15 Pavement Type Selection
14-15-1General
1.1Objective
1.2Pavement Type Selection Policy
14-15-5Structural Design
5.1 Structural Design Process
5.2Structural Design Need
14-15-10Life-Cycle Cost Analysis (LCCA)
10.1 LCCA Process
10.2LCCA Need
10.3LCCA Parameters
10.4LCCA Computation
<u>14-15-15</u> Exception Process <u>15.1</u> General

14-15-20Pavement Design Report
20.1Requirement and Purpose
20.2Need for Reevaluation
20.3Pavement Design Report and Certification Approval
20.4Pavement Design Report Submittal
14-15-25Pavement Design Report Content
<u>25.1</u> Introduction

Attachment 25.1Pavement Design Report Template
Attachment 25.2 Abbreviated Pavement Design Report Template
Section 14-25 Pavement Rehabilitation
14-25-10 Pavement Rehabilitation Guidelines
<u>10.1</u> General
10.2Concrete Pavement
10.3Hot Mix Asphalt (HMA) Pavement
Exhibit 10.1Concrete Pavement Rehabilitation Manual
14-25-15Concrete Pavement Rubblization
<u>15.1</u> General
15.2Why Rubblize
<u>15.3</u> Selecting Rubblization Projects <u>15.4</u> Structural Design
15.5Structura Design
15.6Other Considerations
15.7Staging
14-25-20HMA Pavement Pulverization
20.1General
20.2Why Pulverize
20.3Selecting Pulverization Projects
20.4Structural Design of Pavements Over Pulverized Material
20.5How to Pulverize
20.6Pavement Design Report
20.7Pavement Widening
20.8Curb and Gutter
20.9Structure Clearance
20.10Traffic Over Pulverized HMA
20.11Tack Coat
14-25-25HMA Pavement Cold In-Place Recycling (CIR)
25.1General
25.2Reasons for CIR
25.3 Selecting CIR Projects
25.4Structural Design of Pavements Over CIR Material
25.5How to Construct CIR
25.6Pavement Design Report
25.7Curb and Gutter

25.8.....Structural Clearance

25.10.....Surfacing 25.11.....Tack Coat

25.9.....Traffic Over CIR Rehabilitated Surface

25.2....Report Content